

AS 2887—1993

Reconfirmed 2017

Australian Standard[®]

Plastic waste fittings

This Australian Standard was prepared by Committee PL/28, Plastic Waste Fittings. It was approved on behalf of the Council of Standards Australia on 2 August 1993 and published on 15 November 1993.

The following interests are represented on Committee PL/28:

Australian Chamber of Commerce and Industry
Department of Housing, Local Government and Planning, Qld
Engineering and Water Supply Department, S.A.
Melbourne Water
The Plastics Industry Association
Water Authority of Western Australia

Review of Australian Standards. *To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.*

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 91272.

STANDARDS AUSTRALIA

RECONFIRMATION

OF

AS 2887—1993

Plastic waste fittings

RECONFIRMATION NOTICE

Technical Committee PL-006 has reviewed the content of this publication and in accordance with Standards Australia procedures for reconfirmation, it has been determined that the publication is still valid and does not require change.

Certain documents referenced in the publication may have been amended since the original date of publication. Users are advised to ensure that they are using the latest versions of such documents as appropriate, unless advised otherwise in this Reconfirmation Notice.

Approved for reconfirmation in accordance with Standards Australia procedures for reconfirmation on 20 January 2017.

The following are represented on Technical Committee PL-006:

Association of Accredited Certification Bodies
Australian Industry Group
Energy Networks Association
Engineers Australia
New Zealand Employers and Manufacturers Association (Central)
Plastics Industry Pipe Association of Australia
Plastics New Zealand
Plumbing Products Industry Group
Water New Zealand
Water Services Association of Australia

NOTES

Australian Standard[®]

Plastic waste fittings

First published as part of AS A162—1969.
Revised and redesignated in part as AS 2887—1986.
Second edition 1993.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 8484 X

PREFACE

This Standard was prepared by the Standards Australia Committee on Plastic Waste Fittings under the direction of the Plastics Standards Policy Board, to supersede AS 2887—1986, *Plastics waste fittings*.

This Standard has been written to allow for any plastic material other than UPVC to be used, provided that the requirements set down can be met. Both dimensional and performance requirements have been specified. Requirements for UPVC fittings are covered by AS 1415, *Unplasticized PVC (UPVC) pipes and fittings for soil, waste and vent (SWV) applications*.

This edition is an editorially revised and updated version of AS 2887—1986 with the following major technical changes:

- (a) Requirements have been included for telescopic trap inlets, overflow relief gratings, pop-up waste outlets, supplementary fixture overflows, and bath and shower connectors.
- (b) The mean diameter waterway requirement of traps and gullies has been deleted in favour of minimum cross-sectional area.
- (c) The guidelines on determining the compliance of a lot have been deleted. This was thought appropriate in view of the requirement by water authorities for products within the scope of AS 2887 to be manufactured under a system of quality control that is certified by an independent third party.

The term 'normative' is used in this Standard to define the application of the Appendix. A 'normative' Appendix is an integral part of a Standard.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE	4
1.2 REFERENCED DOCUMENTS	4
1.3 DEFINITIONS	4
1.4 DESIGN	5
1.5 MATERIALS	5
1.6 CONNECTION ENDS	6
1.7 INTERMEDIATE JOINTS	6
1.8 THREAD FORMS	7
1.9 FREEDOM FROM DEFECTS	7
1.10 GENERAL PERFORMANCE REQUIREMENTS	10
1.11 MARKING	10
 SECTION 2 PLASTIC WASTE TRAPS AND GULLIES	
2.1 SCOPE OF SECTION	11
2.2 DESIGNATION OF SIZE	11
2.3 DESIGN	11
2.4 CONNECTION ENDS	12
2.5 INSPECTION OPENINGS	12
2.6 PERFORMANCE REQUIREMENTS	14
 SECTION 3 PLASTIC WASTE OUTLETS AND GRATINGS	
3.1 SCOPE OF SECTION	15
3.2 DESIGNATION OF SIZE	15
3.3 DESIGN	15
3.4 OUTLET CONNECTION ENDS	18
3.5 PERFORMANCE REQUIREMENTS	18
 SECTION 4 PLASTIC SOIL AND WASTE CONNECTORS	
4.1 SCOPE OF SECTION	19
4.2 DISHWASHER CONNECTORS	19
4.3 FOOD WASTE DISPOSAL CONNECTORS	19
4.4 PAN CONNECTORS	19
4.5 DOUBLE BOWL CONNECTORS	21
4.6 BATH AND SHOWER CONNECTORS	22
4.7 SUDS SAVER BYPASS	22
4.8 CAPS AND LININGS	22
4.9 SOIL/WASTE DUMP POINT CONNECTORS	24
4.10 PERFORMANCE REQUIREMENTS	25
 APPENDIX A REFERENCED DOCUMENTS	 26

STANDARDS AUSTRALIA

Australian Standard
Plastic waste fittings

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE This Standard specifies requirements for moulded or fabricated plastic waste fittings for use in plumbing installations. Such fittings are suitable for receiving short-duration, intermittent liquid discharges at temperatures not exceeding 95°C.

NOTE: Where it is envisaged that a plastic waste fitting will be used in an environment where temperatures in excess of 95°C are common, advice should be sought from the manufacturer.

UPVC fittings for soil, waste and vent applications are not covered by this Standard (see AS 1415).

1.2 REFERENCED DOCUMENTS Appendix A contains a list of documents that are referred to in this Standard.

1.3 DEFINITIONS For the purpose of this Standard, the definitions in AS 3500.0 and those below apply.

1.3.1 Bath and shower connector—a fitting that is interposed between a fixture outlet and a waste trap to facilitate installation or attenuate the effects of thermally-induced movement, or both.

1.3.2 Combination trap—a trap with a swivel joint to facilitate use as an S-trap or P-trap.

1.3.3 Connector—a fitting used to convey liquids from a fixture to discharge pipework.

1.3.4 Horizontal stub pan connector—a fitting designed as an adaptor for use with one or more matched WC pans. It connects directly to the integral spigot end of the pan to enable the pan to be used in S-trap, P-trap and side inlet situations.

1.3.5 Loose coupling nut—a nut retained to the fitting by means of a shoulder and capable of turning relative to the fitting.

1.3.6 Overflow relief grating—a grating that is designed for use in conjunction with an overflow relief gully. Overflow relief gratings fit loosely in the corresponding gully such that an upward movement, under the influence of a surge of liquid in the gully, is not restricted by other than the mass and waterway of the grating.

1.3.7 Plastic waste fitting—a fitting made from moulded or fabricated plastic material for use in plumbing installations for the conveyance of liquid waste.

1.3.8 Soil connector—a fitting which conveys soil liquid from a fixture to discharge pipework.

1.3.9 Supplementary fixture overflow—an overflow that is designed for installation to an existing fixture rather than incorporated as an integral component of a fixture.

1.3.10 Telescopic trap inlet—a waste fitting that incorporates a telescopic inlet tube intended to facilitate installation in situations where there is a need for increased or decreased length of fitting.