

Australian/New Zealand Standard™

Explosive atmospheres

**Part 2: Equipment protection by
pressurized enclosure 'p'**



AS/NZS 60079.2:2015

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee EL-014, Equipment for Explosive Atmospheres. It was approved on behalf of the Council of Standards Australia on 20 October 2015 and on behalf of the Council of Standards New Zealand on 22 October 2015.
This Standard was published on 17 December 2015.

The following are represented on Committee EL-014:

Auckland Regional Chamber of Commerce
Australian Chamber of Commerce and Industry
Australian Industry Group
Australian Institute of Petroleum
Australian Petroleum Production and Exploration Association
Australian Pipeline and Gas Association
Aviation and Marine Engineers Association
Bureau of Steel Manufacturers of Australia
Department of Natural Resources and Mines, Qld
Department of Trade and Investment, NSW
Electrical Compliance Testing Association
Electrical Contractors Association of New Zealand
Electrical Regulatory Authorities Council
Engineers Australia
Institute of Electrical Inspectors
Institute of Instrumentation, Control & Automation Australia
Institution of Professional Engineers New Zealand
Mining Electrical and Mining Mechanical Engineering Society
Ministry of Business, Innovation and Employment, New Zealand
University of Newcastle
WorkCover New South Wales

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.saiglobal.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

This Standard was issued in draft form for comment as DR AS/NZS 60079.2:2015.

Australian/New Zealand Standard™

Explosive atmospheres

Part 2: Equipment protection by pressurized enclosure 'p'

Originated as AS/NZS 60079.2:2002.
Previous edition 2007.
Third edition 2015.

COPYRIGHT

© Standards Australia Limited/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Australia) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, Private Bag 2439, Wellington 6140.

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee EL-014, Equipment for Explosive Atmospheres, to supersede AS/NZS 60079.2:2007 and AS/NZS 61241.4:2002.

The objective of this Standard is to set out the requirements for the construction and testing of electrical apparatus with pressurized enclosures, of protection type 'p', intended for use in explosive gas atmospheres or explosive dust atmospheres. It also includes the requirements for pressurized enclosures containing a limited release of a flammable substance.

This Standard is identical with, and has been reproduced from IEC 60079-2 Ed.6.0 (2014), *Explosive atmospheres, Part 2: Equipment protection by pressurized enclosure "p"*. Changes to the Standard introduced by this edition are listed in the IEC Foreword.

This Standard is to be read in conjunction with AS/NZS 60079.0, *Explosive atmospheres, Part 0: Equipment—General requirements*.

As this Standard is reproduced from an International Standard, the following applies:

- (a) In the source text 'this part of IEC 60079' should read 'this Australian/New Zealand Standard'.
- (b) A full point substitutes for a comma when referring to a decimal marker.

References to International Standards should be replaced by references to Australian or Australian/New Zealand Standards, as follows:

<i>Reference to International Standard</i>		<i>Australian or Australian/New Zealand Standard</i>	
IEC		AS	
60034	Rotating electrical machines	60034	Rotating electrical machines
60034-5	Part 5: Degrees of protection provided by the integral design of rotating electrical machines (IP code)—Classification	60034.5	Part 5: Degrees of protection provided by the integral design of rotating electrical machines (IP code)—Classification
60529	Degrees of protection provided by enclosures (IP Code)	60529	Degrees of protection provided by enclosures (IP Code)
		AS/NZS	
60079	Explosive atmospheres	60079	Explosive atmospheres
60079-0	Part 0: Equipment—General requirements	60079.0	Part 0: Equipment—General requirements
60079-11	Part 11: Equipment protection by intrinsic safety "i"	60079.11	Part 11: Equipment protection by intrinsic safety 'i'
60079-15	Part 15: Equipment protection by type of protection "n"	60079.15	Part 15: Equipment protection by type of protection 'n'

Only normative references that have been adopted as Australian or Australian/New Zealand Standard have been listed.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the annex to which they apply. A 'normative' annex is an integral part of a Standard, whereas an 'informative' annex is only for information and guidance.

CONTENTS

1	Scope	15
2	Normative references	15
3	Terms and definitions	16
4	Protection levels	18
5	Constructional requirements for pressurized enclosures	21
5.1	Enclosure	21
5.2	Materials	21
5.3	Doors and covers	21
5.3.1	Group I pressurized enclosures	21
5.3.2	Group I pressurized enclosures with static pressurization	21
5.3.3	Group II and Group III pressurized enclosures	21
5.3.4	Group II and Group III pressurized enclosures with static pressurization	22
5.3.5	Group II and Group III Level of Protection "pxb"	22
5.3.6	Group II and Group III Door and Cover warning	22
5.4	Mechanical strength	22
5.5	Group I and Group II Apertures, partitions, compartments and internal components	22
5.6	Apertures for Static Pressurization	23
5.7	Insulating materials for Group I equipment	23
5.8	Sealing	23
5.9	Spark and particle barriers	23
5.10	Cells and batteries	24
6	Temperature limits	24
6.1	General	24
6.2	For Level of Protection "pxb" or Level of Protection "pyb"	24
6.3	For Level of Protection "pzc"	24
7	Safety provisions and safety devices (except for static pressurization)	24
7.1	Suitability of safety devices for hazardous area	24
7.2	Integrity of safety devices	24
7.3	Provider of safety devices	25
7.4	Pressurization System evaluated as associated equipment	25
7.4.1	Pressurization systems for Level of Protection "pzc"	25
7.4.2	Pressurization systems for Level of Protection "pyb"	26
7.4.3	Pressurization systems for Level of Protection "pxb"	26
7.5	Sequence diagram for Level of Protection "pxb"	26
7.6	Ratings for safety devices	26
7.7	Group I and Group II Purging automated for Level of Protection "pxb"	26
7.8	Group I or Group II – Purging criteria	27
7.9	Group III – Cleaning	27
7.10	Requirements when a minimum flow rate required	27
7.11	Safety devices to detect minimum overpressure	27
7.12	Value of minimum overpressure	28
7.13	Pressurizing multiple enclosures	29
7.14	Safety devices on doors and covers	29

7.15	Equipment that may remain energized	29
7.16	Equipment permitted within Level of Protection “pyb”	29
8	Safety provisions and safety devices for static pressurization	30
8.1	Suitability of safety devices for hazardous area	30
8.2	Protective gas	30
8.3	Internal sources of release	30
8.4	Group I and Group II Filling procedure	30
8.5	Group III Filling Procedure	30
8.6	Safety devices	30
8.7	Equipment that may remain energized	30
8.8	Overpressure	30
9	Supply of protective gas	31
9.1	Backup supply	31
9.2	Independent supplies	31
9.3	Type of gas	31
9.4	Temperature	31
10	Pressurized equipment with an internal source of release	31
11	Release conditions	31
11.1	No release	31
11.2	Limited release of a gas or vapour	32
11.3	Limited release of a liquid	32
12	Design requirements for the containment system	32
12.1	General design requirements	32
12.2	Infallible containment system	32
12.3	Containment system with a limited release	33
13	Protective gas and pressurizing techniques when there is an internal source of release	33
13.1	General	33
13.2	Pressurization with leakage compensation	34
13.2.1	No release	34
13.2.2	Limited release of a gas or liquid	34
13.3	Pressurization with dilution	34
13.3.1	General	34
13.3.2	No release	34
13.3.3	Limited release of a gas or vapour	35
13.3.4	Limited release of a liquid	35
14	Ignition-capable equipment	35
15	Internal hot surfaces	35
16	Type verification and tests	36
16.1	Determining the maximum overpressure rating	36
16.2	Maximum overpressure test	36
16.3	Leakage test	36
16.3.1	Other than static pressurization	36
16.3.2	Static pressurization	36
16.4	Purging test for pressurized enclosures with no internal source of release and filling procedure test for static pressurization	37
16.4.1	General	37
16.4.2	Pressurized enclosure where the protective gas is air	37

16.4.3	Pressurized enclosure where the protective gas is inert.....	37
16.4.4	Pressurized enclosure where the protective gas may be either air or an inert gas with a density equal to air $\pm 10\%$	37
16.4.5	Filling procedure test for a pressurized enclosure protected by static pressurization.....	37
16.5	Purging and dilution tests for a pressurized enclosure with an internal source of release.....	37
16.5.1	Test gas.....	37
16.5.2	Pressurized enclosure where the flammable substance has less than 2 % (V/V) oxygen and the protective gas is inert.....	38
16.5.3	Pressurized enclosure with pressurization by continuous flow, containment system with less than 21 % (V/V) oxygen and the protective gas is inert.....	38
16.5.4	Pressurized enclosure where the flammable substance is not a liquid, pressurization by continuous flow and the protective gas is air.....	39
16.6	Verification of minimum overpressure.....	39
16.7	Tests for an infallible containment system.....	40
16.7.1	Overpressure test.....	40
16.7.2	Infallibility test.....	40
16.8	Overpressure test for a containment system with a limited release.....	40
17	Routine tests.....	40
17.1	Functional test.....	40
17.2	Leakage test.....	40
17.3	Tests for an infallible containment system.....	40
17.4	Test for a containment system with a limited release.....	40
18	Marking.....	40
18.1	General.....	40
18.2	Identifying as pressurized.....	41
18.3	Supplementary marking.....	41
18.4	Internal source of release.....	41
18.5	Static pressurization.....	41
18.6	Pressurization systems.....	41
18.7	Warnings required in other clauses.....	42
18.8	Overpressure limited by user.....	42
18.9	Inert gas.....	42
19	Instructions.....	43
Annex A (normative)	Purging and dilution tests.....	44
A.1	General.....	44
A.2	Criteria for compliance where the protective gas is air.....	44
A.3	Criteria for compliance where the protective gas is inert.....	44
Annex B (informative)	Examples of functional sequence diagram.....	45
Annex C (informative)	Examples of the changes in pressure in ducts and enclosures.....	47
Annex D (informative)	Information to be provided to the user.....	52
D.1	General.....	52
D.2	Ducting of protective gas.....	52
D.2.1	Location of inlet.....	52
D.2.2	Ducting between pressurized enclosure and inlet.....	52
D.2.3	Outlets for protective gas.....	52
D.2.4	Additional purge time to account for ducting.....	53

D.2.5	Temperature of protective gas at the inlet.....	53
D.3	Power for protective gas supply	53
D.4	Static pressurization	53
D.5	Enclosures with a containment system.....	53
D.6	Enclosure maximum overpressure	53
Annex E (normative)	Classification of the type of release within enclosures	54
E.1	General.....	54
E.2	No normal release, no abnormal release	54
E.3	No normal release, limited abnormal release.....	54
E.4	Limited normal release.....	54
Annex F (informative)	Examples for the use of the dilution area concept.....	55
Annex G (normative)	Internal Cells and Batteries for Level of Protection “pxb” and Level of Protection “pyb”.....	57
G.1	General Requirements	57
G.1.1	General	57
G.1.2	Accepted Electrochemical Systems	57
G.1.3	Secondary cells and secondary batteries.....	57
G.1.4	Mechanical Protection	57
G.2	Electrical Protection by energy limiting circuits.....	58
G.2.1	Assessing as energy limited	58
G.2.2	Protective Components.....	58
G.2.3	Preventing excessive gas pressure.....	58
G.3	Additional requirements for Primary batteries.....	59
G.3.1	Prevention of reverse charging.	59
G.3.2	Prevention of accidental charging of primary batteries	59
G.4	Additional requirements for secondary batteries.....	60
G.4.1	Charging of secondary batteries inside the pressurized housing	60
G.5	Specific requirements for Inherently Safe (IhS) cells and batteries	60
G.6	Equipment located inside a pressurized enclosure connected to a battery which is also located inside the pressurized enclosure and not disconnected in the event of loss of pressurization	61
G.6.1	General	61
G.6.2	Circuit Isolation.....	61
G.6.3	Intrinsically safe battery or inherently safe battery used with “Ex” equipment.....	61
G.6.4	Intrinsically Safe or Inherently Safe battery with non-“Ex” equipment.....	61
G.7	Supplementary marking and constructional requirements for pressurized enclosures containing one or more cells or batteries	63
G.7.1	General	63
G.7.2	Battery removal warning	63
G.7.3	Batteries requiring routine maintenance.....	63
G.8	Type tests	63
G.8.1	Voltage	63
G.8.2	Short circuit test for an Inherently Safe Cell or Battery.....	63
G.8.3	Full load test for other than Inherently safe batteries	63
Annex H (normative)	Internal Cells and Batteries for Level of Protection “pzc”	64
H.1	General Requirements	64
H.1.1	General	64
H.1.2	Accepted Electrochemical Systems	64

H.1.3	Secondary cells and secondary batteries	64
H.1.4	Mechanical Protection	64
H.2	Equipment located inside a pressurized enclosure connected to a battery which is also located inside the pressurized enclosure and is not disconnected when power is removed from the enclosure.	65
H.3	Supplementary marking and constructional requirements for pressurized enclosures containing one or more cells or batteries	65
H.3.1	General	65
H.3.2	Battery removal warning	65
H.3.3	Batteries requiring routine maintenance.....	65
	Bibliography.....	66
	Figure B.1 – State diagram of a leakage-compensation purge control system	45
	Figure C.1 – Protective gas outlet.....	48
	Figure C.2 – Pressurized enclosures with leakage compensation, enclosures without moving parts	49
	Figure C.3 – Pressurized enclosures with leakage compensation, rotating electrical machine with an internal cooling fan	50
	Figure C.4 – Pressurized enclosure with a leakage compensation, rotating electrical machine with an external cooling fan	51
	Figure F.1 – Diagram showing the use of the dilution area concept to simplify the purge and dilution test requirements	55
	Figure F.2 – Diagram showing the use of the infallible containment system concept to simplify the purging and dilution requirements around ICE.....	56
	Figure F.3 – Diagram showing the use of internal partitions around the potential source of release to simplify the purging and dilution requirements around ICE located outside the partitions.....	56
	Figure G.1 – Reverse charging protection	59
	Figure G.2 – Accidental charging protection.....	59
	Table 1 – Determination of protection level	19
	Table 2 – Design criteria based upon level of protection	20
	Table 3 – Safety devices based upon Level of Protection.....	25
	Table 4 – Protective gas requirements for a pressurized enclosure with a containment system	34
	Table 5 – Equipment Protection Levels permitted within the dilution area based upon the Level of Protection of the pressurized enclosure	35
	Table 6 – Text of warning markings	42
	Table B.1 – Truth table of a leakage-compensation purge control system	45

IEC FOREWORD

The significance of changes between IEC 60079-2, Edition 6.0, 2014 and IEC 60079-2, Edition 5.0, 2007 are as listed below:

Changes	Clause	Type		
		Minor and Editorial Changes	Extension	Major Technical Changes
Scope Expanded to include combustible dust	1		X	
Protective Gas Replaced "apparatus" with "equipment"	3			
Protective Gas Revised to show that purging is not required for explosive dust atmospheres	3.16	X		
Level of Protection "pxb" Term and definitions revised to reflect EPL and level of protection	3.21	X		
Level of Protection "pyb" Term and definitions revised to reflect EPL and level of protection	3.22	X		
Level of Protection "pzc" Term and definitions revised to reflect EPL and level of protection	3.23	X		
Lower Flammable Limit Term and definition revised to agree with 60079-0	3.26	X		
Upper Flammable Limit Term and definition revised to agree with 60079-0	3.27	X		
Table 1 – Determination of protection level Revised to use EPL terminology	Table 1	X		
Table 2 – Design Criteria based upon level of protection Revised to use EPL terminology	Table 2	X		
Enclosure Requirements relaxed for specific designs	5.1		X	
Group II and Group III pressurized enclosures Text revised to use EPL terminology	5.3.3	X		
Group II and Group III Level of Protection "pxb" Added that warning also applies for explosive dust atmospheres	5.3.5		X	
Group II and Group III door and cover warning Added that warning also applies for explosive dust atmospheres	5.3.6		X	
Group II and Group III door and cover warning Revised warning from atmosphere "may be present" to "is present"	5.3.6	X		
Mechanical Strength Removed reference to 60079-0 by clause number for "X" condition	5.4	X		
Spark and particle barriers Removed reference to 60079-0 by clause number for "X" condition	5.9	X		
Cells and batteries Added requirements for cells and batteries	5.10			C1
For Level of Protection "pxb" or Level of Protection "pyb" Revised Table to use terminology consistent with EPLs	6.2	X		

Changes	Clause	Type		
		Minor and Editorial Changes	Extension	Major Technical Changes
Suitability of safety devices for hazardous area Word “explosion” changed to “ignition” to reflect UFL/LFL terms	7.1	X		
Integrity of safety devices Added requirement for detecting fan failure	7.2			C2
Table 3 – Safety devices based upon Level of Protection Revised column labels to use Level of Protection terminology	Table 3	X		
Provider of safety devices Remove reference to 60079-0 by clause number for “X” condition	7.3	X		
Pressurization System evaluated as associated equipment Added requirements for pressurization systems	7.4			C3
Sequence diagram for Level of Protection “pxb” Revised text to use Level of Protection terminology	7.5	X		
Group I and Group II purging automated for Level of Protection “pxb” Revised text to use Level of Protection terminology	7.7	X		
Group I and Group II purging automated for Level of Protection “pxb” Added text specifying that for “pxb”, control must be automated	7.7			C4
Group I or Group II – purging criteria Revised text to use Level of Protection terminology	7.8	X		
Group III – cleaning Added text for cleaning enclosures used in explosive dust atmospheres	7.9		X	
Safety devices to detect minimum overpressure Add word “minimum” to clause title to be consistent with text	7.11	X		
Safety devices to detect minimum overpressure Revised text to use Level of Protection terminology	7.11 d)	X		
Value of minimum overpressure Added word “minimum” to clause title to be consistent with text	7.12	X		
Value of minimum overpressure Revised text to use Level of Protection terminology	7.12	X		
Value of minimum overpressure Added text to reflect a note in Annex C	7.12		X	
Pressurizing multiple enclosures Revised text to use Level of Protection terminology	7.13	X		
Safety devices on doors and covers Revised text to use Level of Protection terminology	7.14	X		
Equipment that may remain energized Revised text to use EPL and level of protection terminology	7.15	X		
Equipment permitted within Level of Protection “pyb” Revised text to use EPL and level of protection terminology	7.16	X		
Group I and Group II Filling procedure Allow filling in a hazardous location if tested as non-hazardous	8.4		X	

Changes	Clause	Type		
		Minor and Editorial Changes	Extension	Major Technical Changes
Group III Filling Procedure Added static pressurization filling procedure for combustible dust	8.5		X	
Safety devices Revised text to use Level of Protection terminology	8.6	X		
Equipment that may remain energized Revised text to use EPL terminology	8.7	X		
Overpressure Removed reference to 60079-0 by clause number	8.8	X		
Backup supply Added requirements for a backup supply of protective gas	9.1			C5
Independent supplies Provided requirements for independence of pressurization	9.2		X	C6
Release Conditions Removed reference to 60079-0 by clause number for "X" condition	11.1.2	X		
Containment system with a limited release Removed reference to 60079-0 by clause number for "X" condition	12.3	X		
13.3.3 Limited release of a gas or vapour Revised text to reflect UFL/LFL terms	13.3.3	X		
Ignition-capable equipment Revised text to use Level of Protection terminology	14	X		
Type verification and tests Edition 5 clauses 16.1 to 16.7 moved to Edition 6 clauses 16.2 to 16.8	16	X		
Determining the maximum overpressure rating Added requirements to determine maximum overpressure	16.1			C7
Maximum overpressure test Moved Maximum overpressure test to 16.2	16.2			C7
Leakage test Clarify the acceptance criteria for the test	16.3.2		X	
Tests for an infallible containment system Clarify the rating used for the test	16.7.1			C8
Tests for an infallible containment system Modified test for infallible containment	16.7.2			C9
Edition 5 – Verifying ability of the pressurized enclosure to limit internal pressure Eliminated test	16.8			C7
Functional test Clarified that applies only to safety devices provided with enclosures	17.1	X		
Tests for an infallible containment system Waived helium leak tests for liquid systems	17.3		X	

Changes	Clause	Type		
		Minor and Editorial Changes	Extension	Major Technical Changes
Supplementary marking Allowed continued use of type of protection marking	18.3			
Pressurization systems Clarified use of Ex [p] and [Ex p] marking	18.6	X		
Warnings required in other clauses Added table number	18.7	X		
Warnings required in other clauses Added warning from 7.9	18.7		X	
Warnings required in other clauses Added warnings from Annex G and Annex H	18.7			C1
Instructions Added requirements for Group III	19		X	
Edition 5 Annex G – Infallibility test for containment system Deleted and replaced	Annex G	X		
Edition 5 Annex H – Introduction of an alternative risk assessment method encompassing “equipment protection levels” Deleted and replaced	Annex H	X		
Annex G – Internal Cells and Batteries for Level of Protection “pxb” and Level of Protection “pyb” Added requirements for cells and Batteries			X	
Annex H – Internal Cells and Batteries for Level of Protection “pzc” Added requirements for cells and Batteries			X	

Explanations:

A) Definitions

Minor and editorial changes clarification decrease of technical requirements minor technical change editorial corrections

These are changes which modify requirements in an editorial or a minor technical way. They include changes of the wording to clarify technical requirements without any technical change, or a reduction in level of existing requirement.

Extension addition of technical options

These are changes which add new or modify existing technical requirements, in a way that new options are given, but without increasing requirements for equipment that was fully compliant with the previous standard. Therefore, these will not have to be considered for products in conformity with the preceding edition. 5.

Major technical changes addition of technical requirements increase of technical requirements

These are changes to technical requirements (addition, increase of the level or removal) made in a way that a product in conformity with the preceding edition will not always be able to fulfill the requirements given in the later edition. These changes have to be considered for products in conformity with the preceding edition. For these changes additional information is provided in clause B) below

B) Information about the background of ‘Major Technical Changes’

C1 – Added annexes with requirements for using cells and batteries.

C2 – Added requirement that fan failure cannot be based upon loss of power to the fan.

- C3 – Added requirements for equipment evaluated as a pressurization system to provide uniformity in the testing of such equipment.
- C4 – Although, in Edition 5, the title of clause 7.6 stated automated purging, the word automated was not in the requirement. It is intended that all “pxb” equipment have an automated purging system to prevent energizing of ignition capable circuits until the purge cycle has been properly completed. This requires verifying that the flow is at least the minimum required for the purge time as well as verifying that the minimum overpressure exists within the enclosure.
- C5 – If a backup supply of protective gas is provided, then both the primary and the backup supply needs to be capable of maintaining the required pressurization.
- C6 – If a pressurized enclosure is used within a larger pressurized enclosure the protective gas supplies need to be independent.
- C7 – The previous text in 16.1 of Edition 5, assumed that the enclosures had a maximum overpressure rating, but this is rarely the case. Some test houses relied upon the test in 16.8 to determine the maximum overpressure. Various methods were used to simulate regulator failure such as removing the regulator, but this also removed the orifices that would limit the flow. Based upon test house experience, the danger of flying fragments from the enclosure is acceptably small as either the enclosure or the gaskets will deform to relieve the internal pressure. A decision was taken to eliminate the overpressure test based upon the failed regulator. In addition, the definition of maximum overpressure is now based upon the value obtained when the pressurized enclosure is operated within its ratings. This maximum overpressure will generally occur when the equipment is in rapid purge mode with the maximum rated pressure applied to the inlet of the regulator. The Edition 5 text of 16.1 was modified and moved to 16.2.
- C8 – The term overpressure in most cases implies operation outside of the normal ratings. Text was clarified to use the term “maximum operating pressure” rather than maximum internal overpressure. Test was 16.6.1 in Edition 5.
- C9 – The test was modified to use helium leak detection rather than rely on maintaining a vacuum since this would depend upon the capability of the vacuum system. Test was 16.6.2 in Edition 5.

INTRODUCTION

This part of IEC 60079 gives requirements for the design, construction, testing and marking of electrical equipment for use in explosive atmospheres in which

- a) a protective gas maintained at a pressure above that of the external atmosphere is used to guard against the formation of an explosive gas atmosphere within enclosures which do not contain an internal source of release of flammable gas or vapour;
- b) a protective gas maintained at a pressure above that of the external atmosphere is used to guard against the formation of an explosive gas atmosphere within enclosures and is supplied to an enclosure containing one or more internal sources of release in order to guard against the formation of an explosive gas atmosphere; or
- c) a protective gas maintained at a pressure above that of the external atmosphere, is used to prevent the entry of combustible dust which might otherwise lead to the formation of an explosive dust atmosphere within enclosures, but only where there is no internal source of release of combustible dust.

This standard includes requirements for the equipment and its associated equipment including the inlet and exhaust ducts, and also for the auxiliary control equipment necessary to ensure that pressurization and/or dilution is established and maintained.

AUSTRALIAN/NEW ZEALAND STANDARD

Explosive atmospheres

Part 2:

Equipment protection by pressurized enclosure 'p'

1 Scope

This part of IEC 60079 contains the specific requirements for the construction and testing of electrical equipment with pressurized enclosures, of type of protection "p", intended for use in explosive gas atmospheres or explosive dust atmospheres. It also includes the requirements for pressurized enclosures containing a limited release of a flammable substance.

This standard supplements and modifies the general requirements of IEC 60079-0. Where a requirement of this standard conflicts with a requirement of IEC 60079-0, the requirements of this standard take precedence.

This standard does not include the requirements for:

- pressurized enclosures where the containment system may release
 - a) air with an oxygen content greater than normal, or
 - b) oxygen in combination with inert gas where the oxygen is in a proportion greater than 21 %.
- pressurized rooms or analyser houses; see IEC 60079-13;
- pressurized enclosures used where "explosives" or pyrotechnics are present;
- pressurized enclosures used where hybrid mixtures of gas/vapour and combustible dust are present;
- pressurized enclosures used where pyrophoric substances such as explosives or propellants containing their own oxidizers are present
- pressurized enclosures with an internal source of release of combustible dust.

NOTE When the user acts in the role of the manufacturer, it is typically the user's responsibility to ensure that all relevant parts of this standard are applied to the manufacturing and testing of the equipment.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60034-5, *Rotating electrical machines – Part 5: Degrees of protection provided by the integral design of rotating electrical machines (IP code) – Classification*

IEC 60050 (all parts), *International Electrotechnical Vocabulary*

IEC 60079-0, *Explosive atmospheres – Part 0: Equipment – General requirements*

IEC 60079-11, *Explosive atmospheres – Part 11: Equipment protection by intrinsic safety "i"*

IEC 60079-15, *Explosive atmospheres – Part 15: Equipment protection by type of protection "n"*