

Australian/New Zealand Standard™

**High visibility safety garments**

**Part 1: Garments for high risk applications**



## **AS/NZS 4602.1:2011**

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee SF-004, Occupational Protective Clothing. It was approved on behalf of the Council of Standards Australia on 28 June 2010 and on behalf of the Council of Standards New Zealand on 23 July 2010.

This Standard was published on 17 February 2011.

---

The following are represented on Committee SF-004:

Australasian Fire and Emergency Service Authorities Council  
Australian Chamber of Commerce and Industry  
Australian Industry Group  
Australia Post  
AWTA Textile Testing  
Certification Interests (Australia)  
Council of Textile and Fashion Industries of Australia  
CSIRO Textile and Fibre Technology  
NZ Safety/Protector Safety  
Road Safety Manufacturers Association New Zealand  
Safety Institute of Australia  
Textile Clothing & Footwear Union of Australia  
University of Otago, New Zealand

---

### **Keeping Standards up-to-date**

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at [www.saiglobal.com](http://www.saiglobal.com) or Standards New Zealand web site at [www.standards.govt.nz](http://www.standards.govt.nz) and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of Standards Australia or the New Zealand Standards Executive at the address shown on the back cover.

---

*This Standard was issued in draft form for comment as DR 10013.*

---

# Australian/New Zealand Standard™

## High visibility safety garments

### Part 1: Garments for high risk applications

Originated as AS/NZS 4602:1999.  
Jointly revised and redesignated as AS/NZS 4602.1:2011.  
Reissued incorporating Amendment No. 1 (November 2016).

#### **COPYRIGHT**

© Standards Australia Limited/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Australia) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, PO Box 1473, Wellington 6011.

## PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Subcommittee SF-004-03, Light Reflective Protective Clothing, for Committee SF-004, Occupational Protective Clothing, and supersedes AS/NZS 4602:1999, *High visibility safety garments*.

*This Standard incorporates Amendment No. 1 (November 2016). The changes required by the Amendment are indicated in the text by a marginal bar and amendment number against the clause, note, table, figure or part thereof affected.*

EN 471, *High-visibility warning clothing for professional use—Test methods and requirements*, was consulted in the preparation of this Standard.

The principal change from the previous edition is the more rigorous specification of the amount of background material required on a garment for daytime visibility in high risk applications, and the way it is to be measured.

Provision is also made for separate standards for firefighters' garments and garments for general application in situations of lower risk to be developed.

Statements expressed in mandatory terms in notes to figures are deemed to be requirements of this Standard.

The term 'informative' has been used in this Standard to define the application of the appendix to which it applies. An 'informative' appendix is only for information and guidance.

## CONTENTS

	<i>Page</i>
FOREWORD.....	4
1 SCOPE.....	5
2 OBJECTIVE .....	5
3 REFERENCED DOCUMENTS .....	5
4 DEFINITIONS.....	5
5 CLASSIFICATION OF GARMENTS .....	6
6 CLASS D GARMENTS.....	6
7 CLASS N GARMENTS.....	9
8 CLASS D/N GARMENTS .....	14
9 ATTACHMENT TO BODY .....	14
10 INSTRUCTIONS, LABELLING AND MARKING .....	15
11 SELECTION AND SAFE USE.....	15
 APPENDICES	
A MEASUREMENT OF HIGH VISIBILITY BACKGROUND MATERIAL ON A GARMENT .....	16
B RECOMMENDED USE OF RETROREFLECTIVE STRIPS ON SLEEVES AND LEGS OF GARMENTS.....	20
C SELECTION AND SAFE USE OF HIGH VISIBILITY GARMENTS .....	22

## FOREWORD

This Standard specifies high visibility safety garment requirements for use in high risk applications without reference to particular types or styles. This has been done so as to give the designer as much flexibility as possible in selecting a suitable garment design to meet differing needs as regards weather conditions, type of work and the like, and to be innovative in devising means of encouraging users to wear the garments properly. Different requirements apply to garments for fire services, which are dealt with in AS/NZS 4602.2\*.

The design of garments has been based primarily on the needs of workers in road and rail traffic situations to be seen in field situations by the operators of vehicles approaching them at speed, in time for any necessary safety action to be taken. Their use is, however, recommended in all industrial situations of similar risk level where workers need to be seen at distance, against a complex visual background, in conditions of poor visibility or where they may appear suddenly in the path of a vehicle or item of moving plant.

It is important that, in order to gain the most effective use from high visibility garments, users have some understanding of the way fluorescent and retroreflective materials achieve high visibility. These mechanisms are explained as follows:

- (a) *Fluorescent material*—is impregnated with a substance that may be a dye or pigment and has the property of converting energy at shorter wavelengths (including ultraviolet) to light in the visible spectrum, hence noticeably increasing the amount of visible light and colour reflected and emitted from its surface. It will therefore work best where this is an appreciable amount of shorter wavelengths (most notably, in this context, daylight and sunlight) falling on the material. Artificial night-time light sources (with the exception of xenon arc headlights) contain little UV radiation. Two important points to note are firstly that fluorescent materials are susceptible to fairly rapid fading. Secondly, the fluorescent substances can usually only be applied to man-made fibres. Garments made from some man-made fibres may not be as comfortable to wear under hot humid conditions as natural fibres except where the man-made fibre materials have been designed to encourage air circulation without reducing their luminance factor.
- (b) *Retroreflective materials*—as the name suggests, cause practically all of the light reflected from their surface to be directed back along the path of the incoming light beam. An observer will not gain the benefit of a retroreflective article unless he/she is observing it from a position closely aligned with, usually just behind, the light source, e.g. a motor vehicle driver sitting almost directly behind the vehicle headlights.

---

\* Yet to be prepared at time of publication of this Standard.

## STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

**Australian/New Zealand Standard**  
**High visibility safety garments**

**Part 1: Garments for high risk applications**

**1 SCOPE**

This Standard specifies the visual requirements for high visibility safety garments for occupational wear by people who may be exposed to the hazard of moving traffic, moving plant or equipment in high risk situations. The Standard covers garments suitable for daytime wear, night-time wear where they will be seen by retroreflected light or for wear under both conditions but excludes garments for use by fire services.

## NOTES:

- A1 | 1 This Standard covers only the visual requirements of garments. It does not cover their physical integrity or fitness for use in adverse physical environments.
- 2 Requirements for firefighters' garments are specified in AS/NZS 4602.2.
- 3 A Standard for garments to be used in lower risk applications was under consideration at the time of publication of this Standard.

**2 OBJECTIVE**

The objective of this Standard is to provide both manufacturers of garments and persons responsible for workers in the relevant high risk situations, with minimum requirements for high visibility safety garments.

**3 REFERENCED DOCUMENTS**

The following documents are referred to in this Standard:

## AS/NZS

- 1906 Retroreflective materials and devices for road traffic control purposes
- 1906.4 Part 4: High visibility materials for safety garments
- 1957 Textiles—Care labelling
- 4399 Sun protective clothing—Evaluation and classification

**4 DEFINITIONS**

For the purpose of this Standard, the definitions in AS/NZS 1906.4 and the following apply.

**4.1 Background material**

Material providing high daytime visibility on either a daytime-only garment or a garment designed for use both day and night.

**4.2 Garment reference points**

- A1 | (a) *Elbow reference point*
- A point on the sleeve of a garment as measured not more than 400 mm below the highest shoulder point to the side seam.