

Australian/New Zealand Standard™

**Electric cables—Aerial bundled—
Polymeric insulated—Voltages
6.35/11 (12) kV and 12.7/22 (24) kV**

Part 1: Metallic screened

AS/NZS 3599.1:2003

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee EL-003, Electric Wires and Cables. It was approved on behalf of the Council of Standards Australia on 8 August 2003 and on behalf of the Council of Standards New Zealand on 19 August 2003. It was published on 11 September 2003.

The following are represented on Committee EL-003:

Australasian Railway Association
Australian Electrical and Electronic Manufacturers Association
Australian Industry Group
Canterbury Manufacturers Association of New Zealand
Department of Defence, Australia
Department of Mineral Resources, N.S.W.
Electrical Contractors Association of New Zealand
Electrical Regulatory Authorities Council
Electricity Supply Association of Australia
Institution of Engineers, Australia
Ministry of Economic Development, New Zealand
National Electrical and Communications Association

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Australia web site at www.standards.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

Alternatively, both organizations publish an annual printed Catalogue with full details of all current Standards. For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia International or Standards New Zealand at the address shown on the back cover.

Australian/New Zealand Standard™

Electric cables—Aerial bundled— Polymeric insulated—Voltages 6.35/11 (12) kV and 12.7/22 (24) kV

Part 1: Metallic screened

Originated as AS 3599.1—1988.
Jointly revised and designated AS/NZS 3599.1:2003.

COPYRIGHT

© Standards Australia/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Jointly published by Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001 and Standards New Zealand, Private Bag 2439, Wellington 6020

ISBN 0 7337 5487 2

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee EL-003, Electric Wires and Cables, and is based on requirements laid down by the Electricity Supply Association of Australia. This Standard supersedes AS 3599.1—1988.

The objective of the Standard is to specify construction, dimensions and test requirements for cross-linked polyethylene insulated individually metallic screened, three phase, aerial bundled cables (ABCs), steel wire supported, for working voltages 6.35/11 (12) kV and 12.7/22 (24) kV.

For reasons of standardization and rationalization, this Standard provides for the construction, dimensions, and test requirements of only a limited range of individually screened three-core cables.

This Standard is complementary to the range of cables covered in AS/NZS 3599.2, *Electric cables—Aerial bundled—Polymeric insulated—Voltages 6.35/11 (12) kV and 12.7/22 (24) kV*, Part 2: *Non-metallic screened*, and in AS/NZS 1429.1, *Electric cables—Polymeric insulated*, Part 1: *For working voltages 1.9/3.3 (3.6) kV up to and including 19/33 (36) kV*. This Standard is generally compatible with the appropriate requirements specified in those Standards.

This Standard differs from the previous edition in the following significant ways.

- (a) The Standard has been published as a Joint Australian/New Zealand Standard.
- (b) The specifications for the conductor screen, insulation and insulation screen have been referenced to AS/NZS 1429.1.
- (c) The HDPE sheath material has been referenced to AS/NZS 3808.
- (d) The word ‘catenary’ has been deleted from the definition of the support wire.
- (e) Current carrying capacities have been provided for both a 30°C and a 40°C ambient air temperature.
- (f) Recalculated values have been provided for the recommended copper screen wires and the mechanical characteristics of the support wire.

The term ‘informative’ has been used in this Standard to define the application of the appendix to which it applies. An ‘informative’ appendix is only for information and guidance.

CONTENTS

| | <i>Page</i> |
|---|-------------|
| 1 SCOPE..... | 4 |
| 2 REFERENCED DOCUMENTS..... | 4 |
| 3 DEFINITIONS..... | 5 |
| 4 VOLTAGE DESIGNATION | 6 |
| 5 MAXIMUM CONDUCTOR TEMPERATURES..... | 8 |
| 6 CONDUCTORS..... | 8 |
| 7 CONDUCTOR SCREEN..... | 8 |
| 8 INSULATION..... | 8 |
| 9 INSULATION SCREEN..... | 8 |
| 10 BEDDING TAPE..... | 8 |
| 11 METALLIC SCREEN..... | 8 |
| 12 WATER-BLOCKING OF SCREENS (OPTIONAL)..... | 9 |
| 13 SEPARATOR TAPE(S)..... | 9 |
| 14 SHEATH..... | 9 |
| 15 PHASE IDENTIFICATION..... | 10 |
| 16 CABLE IDENTIFICATION | 10 |
| 17 METRE MARKING | 10 |
| 18 SUPPORT WIRE | 10 |
| 19 LAYING UP | 12 |
| 20 PREPARATION FOR DELIVERY | 12 |
| 21 MARKING OF DRUMS..... | 12 |
| 22 TESTS..... | 13 |
| APPENDICES | |
| A CABLE DATA AND RECOMMENDATIONS..... | 16 |
| B PURCHASING GUIDELINES..... | 21 |
| C DIAMETER OF DRUM BARRELS AND INSTALLATION BENDING RADI FOR CABLES..... | 22 |

STANDARDS AUSTRALIA/STANDARDS NEW ZEALAND

Australian/New Zealand Standard**Electric cables—Aerial bundled—Polymeric insulated—Voltages
6.35/11 (12) kV and 12.7/22 (24) kV****Part 1: Metallic screened****1 SCOPE**

This Standard specifies the construction, dimensions, and test requirements for cross-linked polyethylene (XLPE) insulated, individually metallic screened, high density polyethylene (HDPE) sheathed, steel wire supported, three phase, aerial bundled cable (ABC) (see Figure 1), for electricity supply.

NOTES:

- 1 Cable data and recommendations to assist in the selection of the appropriate cables are given in Appendix A.
- 2 Purchasing guidelines are provided in Appendix B.

2 REFERENCED DOCUMENTS

The documents below are referred to in this Standard.

AS

- | | |
|--------|---|
| 1222 | Steel conductors and stays—Bare overhead |
| 1222.1 | Part 1: Galvanized (SC/GZ) |
| 1222.2 | Part 2: Aluminium clad (SC/AC) |
| 3983 | Metal drums for insulated electric cables and bare conductors |

AS/NZS

- | | |
|----------|---|
| 1125 | Conductors in insulated electric cables and flexible cords |
| 1429 | Electric cables—Polymeric insulated |
| 1429.1 | Part 1: For working voltages 1.9/3.3 (3.6) kV up to and including 19/33 (36) kV |
| 1660 | Test methods for electric cables, cords and conductors |
| 1660.2.1 | Part 2.1: Insulation, extruded semi-conductive screens and non-metallic sheaths—Methods for general application |
| 1660.2.2 | Part 2.2: Insulation, extruded semi-conductive screens and non-metallic sheaths—Methods specific to elastomeric, XLPE and XLPVC materials |
| 1660.3 | Part 3: Electrical tests |
| 2857 | Timber drums for insulated electric cables and bare conductors |
| 3008 | Electrical installations—Selection of cables |
| 3008.1.1 | Cables for alternating voltages up to and including 0.6/1 kV—Typical Australian installation conditions |
| 3008.1.2 | Cables for alternating voltages up to and including 0.6/1 kV—Typical New Zealand installation conditions |
| 3808 | Insulating and sheathing materials for electric cables |