

Australian/New Zealand Standard™

**Household refrigerating appliances—
Characteristics and test methods**

Part 3: Energy consumption and volume



AS/NZS IEC 62552.3:2018

This Joint Australian/New Zealand Standard™ was prepared by Joint Technical Committee EL-060, Household Refrigerating Appliances. It was approved on behalf of the Council of Standards Australia on 11 December 2017 and by the New Zealand Standards Approval Board on 20 December 2017.

This Standard was published on 22 January 2018.

The following are represented on Committee EL-060:

- Airconditioning and Refrigeration Equipment Manufacturers Association of Australia
- Australian Industry Group
- Business New Zealand
- CHOICE
- Consumer Electronics Suppliers Association
- Consumers' Federation of Australia
- Department of the Environment and Energy (Australian Government)
- Electrical Compliance Testing Association of Australia
- Energy Efficiency and Conservation Authority of New Zealand
- Energy Safe Victoria

This Standard was issued in draft form for comment as DR AS IEC 62552.3:2017.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

www.standards.govt.nz

www.saiglobal.com (sales and distribution)

ISBN 978 1 76035 980 5

Australian/New Zealand Standard™

Household refrigerating appliances— Characteristics and test methods

Part 3: Energy consumption and volume

Originated in Australia as AS B116—1956.
Originated in New Zealand as NZS 6205:1982.
Previous edition AS/NZS 4474.1:1997.
Second edition 2007.
Republished and redesignated (in part) as AS/NZS IEC 62552.3:2018.

COPYRIGHT

© IEC — All rights reserved
© Standards Australia Limited/the Crown in right of New Zealand, administered by the New Zealand Standards Executive 2018

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, PO Box 1473, Wellington 6140.

Preface

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee EL-060, Household Refrigerating Appliances, to supersede part of AS/NZS 4474.1:2007, *Performance of household electrical appliances—Refrigerating appliances, Part 1: Energy consumption and performance*.

The objective of this Standard is to specify the essential characteristics of household and similar refrigerating appliances cooled by internal natural convection or forced air circulation, and establishes test methods for checking these characteristics. This part of AS/NZS IEC 62552 describes the methods for the determination of energy consumption characteristics and defines how these can be assembled to estimate energy consumption under different usage and climate conditions. This part of AS/NZS IEC 62552 also defines the determination of volume.

This Standard is identical with, and has been reproduced from, IEC 62552-3:2015, *Household refrigerating appliances — Characteristics and test methods, Part 3: Energy consumption and volume*.

As this document has been reproduced from an International Standard, the following applies:

- (a) In the source text 'this part of IEC 62552' should read 'this Australian Standard';
- (b) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms 'normative' and 'informative' are used in Standards to define the application of the appendices or annexes to which they apply. A 'normative' appendix or annex is an integral part of a Standard, whereas an 'informative' appendix or annex is only for information and guidance.

NOTES

CONTENTS

| | |
|---|----|
| FOREWORD..... | 8 |
| INTRODUCTION..... | 11 |
| 1 Scope..... | 12 |
| 2 Normative references | 12 |
| 3 Terms, definitions and symbols..... | 12 |
| 3.1 Terms and definitions..... | 12 |
| 3.2 Symbols..... | 13 |
| 4 Applicable test steps for determination of energy and volume..... | 13 |
| 4.1 Setup for energy testing..... | 13 |
| 4.2 Steady state power consumption..... | 13 |
| 4.3 Defrost and recovery energy and temperature change | 13 |
| 4.4 Defrost frequency | 13 |
| 4.5 Number of test points and interpolation | 13 |
| 4.6 Load processing efficiency..... | 14 |
| 4.7 Specified auxiliaries | 14 |
| 4.8 Volume determination | 14 |
| 5 Target temperatures for energy determination | 14 |
| 5.1 General..... | 14 |
| 5.2 Temperature control settings for energy consumption test | 15 |
| 6 Determination of energy consumption..... | 15 |
| 6.1 General..... | 15 |
| 6.2 Objective | 16 |
| 6.3 Number of test runs | 17 |
| 6.4 Steady state power consumption..... | 17 |
| 6.5 Defrost and recovery energy and temperature change | 17 |
| 6.6 Defrost interval | 18 |
| 6.7 Specified auxiliaries | 18 |
| 6.8 Calculation of energy consumption | 18 |
| 6.8.1 General | 18 |
| 6.8.2 Daily energy consumption..... | 18 |
| 6.8.3 Interpolation | 19 |
| 6.8.4 Specified auxiliaries..... | 19 |
| 6.8.5 Total energy consumption..... | 20 |
| 7 Circumvention devices..... | 20 |
| 8 Uncertainty of measurement | 21 |
| 9 Test report..... | 21 |
| Annex A (normative) Set up for energy testing | 22 |
| A.1 General..... | 22 |
| A.2 Additional set up requirements for energy testing..... | 22 |
| A.2.1 Ice making trays | 22 |
| A.2.2 User adjustable controls | 22 |
| A.2.3 Ambient temperature | 22 |
| A.2.4 Accessories and shelves | 22 |
| A.2.5 Anti-condensation heaters | 23 |
| A.2.6 Automatic icemakers – ice storage bins | 23 |

| | |
|---|----|
| Annex B (normative) Determination of steady state power and temperature | 26 |
| B.1 General..... | 26 |
| B.2 Setup for testing and data collection | 26 |
| B.3 Case SS1: no defrost control cycle or where stability is established for a period between defrosts | 26 |
| B.3.1 Case SS1 approach..... | 26 |
| B.3.2 Case SS1 acceptance criteria..... | 29 |
| B.3.3 Case SS1 calculation of values..... | 30 |
| B.4 Case SS2: steady state determined between defrosts | 30 |
| B.4.1 Case SS2 approach..... | 30 |
| B.4.2 Case SS2 acceptance criteria..... | 32 |
| B.4.3 Case SS2 calculation of values..... | 33 |
| B.5 Correction of steady state power..... | 34 |
| Annex C (normative) Defrost and recovery energy and temperature change | 36 |
| C.1 General..... | 36 |
| C.2 Setup for testing and data collection | 36 |
| C.3 Case DF1: where steady state operation can normally be established before and after defrosts..... | 37 |
| C.3.1 Case DF1 approach..... | 37 |
| C.3.2 Case DF1 acceptance criteria..... | 39 |
| C.3.3 Case DF1 calculation of values..... | 40 |
| C.4 Number of valid defrost and recovery periods | 42 |
| C.5 Calculation of representative defrost energy and temperature..... | 42 |
| Annex D (normative) Defrost interval | 44 |
| D.1 General..... | 44 |
| D.2 Elapsed time defrost controllers | 44 |
| D.3 Compressor run time defrost controllers..... | 45 |
| D.4 Variable defrost controllers | 47 |
| D.4.1 General | 47 |
| D.4.2 Variable defrost controllers – declared defrost intervals..... | 48 |
| D.4.3 Variable defrost controllers – no declared defrost intervals (demand defrost)..... | 48 |
| D.4.4 Variable defrost controllers – non compliant | 49 |
| Annex E (normative) Interpolation of results..... | 50 |
| E.1 General..... | 50 |
| E.2 Temperature adjustment prior to interpolation | 51 |
| E.3 Case 1: linear interpolation – two test points..... | 51 |
| E.3.1 General | 51 |
| E.3.2 Requirements | 51 |
| E.3.3 Calculations..... | 51 |
| E.4 Case 2: triangulation – three (or more) test points..... | 55 |
| E.4.1 General | 55 |
| E.4.2 Requirements for two (or more) compartment triangulation | 56 |
| E.4.3 Calculations for two compartment triangulation – manual interpolation | 59 |
| E.4.4 Calculations for two compartment triangulation – matrices..... | 60 |
| E.4.5 Checking temperature validity where there are more than two compartments for triangulation..... | 62 |
| E.4.6 Calculations for three compartment triangulation – matrices | 63 |
| Annex F (normative) Energy consumption of specified auxiliaries | 67 |

| | | |
|-----------------------|---|-----|
| F.1 | Purpose | 67 |
| F.2 | Ambient controlled anti-condensation heaters | 67 |
| F.2.1 | Outline of the method | 67 |
| F.2.2 | Measurement procedure | 67 |
| F.2.3 | Data requirements | 68 |
| F.2.4 | Regional weather data | 68 |
| F.2.5 | Calculation of power consumption | 68 |
| F.2.6 | Where anti-condensation heater(s) cannot be disabled but their power consumption can be measured directly | 69 |
| F.2.7 | Where anti-condensation heater(s) cannot be disabled and their power consumption cannot be measured directly | 70 |
| F.2.8 | Where anti-condensation heater(s) has a user-adjustable setting | 70 |
| F.3 | Automatic icemakers – energy to make ice | 70 |
| F.3.1 | General | 70 |
| F.3.2 | Tank type automatic icemakers..... | 70 |
| Annex G (normative) | Determination of load processing efficiency | 77 |
| G.1 | Purpose | 77 |
| G.2 | General description..... | 77 |
| G.3 | Setup, equipment and preparation | 78 |
| G.3.1 | General | 78 |
| G.3.2 | Equipment | 79 |
| G.3.3 | Quantity of water to be processed | 79 |
| G.3.4 | Position of the water load in compartments..... | 80 |
| G.3.5 | Temperature of the water to be processed..... | 83 |
| G.4 | Load processing efficiency test method..... | 84 |
| G.4.1 | Commencement of the load processing efficiency test | 84 |
| G.4.2 | Placement of the load | 84 |
| G.4.3 | Measurements to be taken..... | 85 |
| G.4.4 | Conclusion of load processing efficiency test..... | 85 |
| G.5 | Determination of load processing efficiency | 86 |
| G.5.1 | General | 86 |
| G.5.2 | Quantification of input energy | 87 |
| G.5.3 | Quantification of additional energy used to process the load..... | 88 |
| G.5.4 | Load processing efficiency..... | 89 |
| G.5.5 | Load processing multiplier | 90 |
| G.5.6 | Addition of user related loads into daily energy..... | 91 |
| Annex H (normative) | Determination of volume | 93 |
| H.1 | Scope | 93 |
| H.2 | Total volume | 93 |
| H.2.1 | Volume measurements | 93 |
| H.2.2 | Determination of volume | 93 |
| H.2.3 | Volume of evaporator space | 93 |
| H.2.4 | Two-star sections and/or compartments..... | 94 |
| H.3 | Key for Figures H.1 through H.5..... | 94 |
| Annex I (informative) | Worked examples of energy consumption calculations..... | 98 |
| I.1 | Example calculation of daily energy consumption..... | 98 |
| I.2 | Variable defrost – calculation of defrost intervals | 99 |
| I.3 | Examples of Interpolation..... | 100 |
| I.3.1 | General | 100 |

| | | |
|---|--|-----|
| 1.3.2 | Linear interpolation | 100 |
| 1.3.3 | Two compartments – manual triangulation | 109 |
| 1.3.4 | Two compartments – triangulation using matrices | 113 |
| 1.3.5 | Three compartments – triangulation using matrices | 115 |
| 1.4 | Calculating the energy impact of internal temperature changes | 117 |
| 1.4.1 | General | 117 |
| 1.4.2 | One compartment | 117 |
| 1.4.3 | Triangulation | 118 |
| 1.5 | Automatically controlled anti-condensation heater(s) | 119 |
| 1.6 | Calculation of load processing efficiency | 121 |
| 1.7 | Determination of annual energy consumption | 123 |
| 1.8 | Examples of determination of power and temperature from raw data | 124 |
| 1.8.1 | Manual review of data | 124 |
| 1.8.2 | Review of data and selection of minimum spread using bespoke software | 144 |
| Annex J (informative) Development of the IEC global test method for refrigerating appliances | | 146 |
| J.1 | Purpose | 146 |
| J.2 | Overview | 146 |
| J.3 | Test method objective | 146 |
| J.4 | Description of key components of energy consumption | 147 |
| Annex K (normative) Analysis of a refrigerating appliance without steady state between defrosts | | 149 |
| K.1 | Purpose | 149 |
| K.2 | Products with regular characteristics but without steady state operation | 149 |
| K.2.1 | General | 149 |
| K.2.2 | Special case DF2 approach | 149 |
| K.2.3 | Case DF2 acceptance criteria | 150 |
| K.2.4 | Case DF2 calculation of values | 150 |
| Annex L (informative) Derivation of ambient temperature correction formula | | 152 |
| L.1 | Purpose | 152 |
| L.2 | Background | 152 |
| L.3 | Approach | 153 |
| Figure B.1 – Illustration of a test period made of blocks of 5 temperature control cycles – temperatures for Case SS1 | | 27 |
| Figure B.2 – Illustration of a test period made of blocks of 5 temperature control cycles – power for Case SS1 | | 28 |
| Figure B.3 – Case SS2 – typical operation of a refrigerating appliance with a defrost control cycle | | 31 |
| Figure C.1 – Conceptual illustration of the additional energy associated with a defrost and recovery period | | 37 |
| Figure C.2 – Case DF1 with steady state operation before and after a defrost | | 38 |
| Figure E.1 – Interpolation where temperatures change in multiple compartments (compartment D critical) | | 54 |
| Figure E.2 – Interpolation with valid results in both Compartment A and B | | 54 |
| Figure E.3 – Interpolation with no valid results | | 55 |
| Figure E.4 – Schematic representation of interpolation by triangulation | | 57 |
| Figure G.1 – Conceptual illustration of the load processing efficiency test | | 78 |

| | |
|--|-----|
| Figure G.2 – Shelf locations and loading sequence (example showing 10 PET bottles)..... | 81 |
| Figure G.3 – Ice cube tray locations and clearances | 83 |
| Figure G.4 – Representation of the additional energy to process the added load | 87 |
| Figure G.5 – Case where a defrost and recovery period occurs during load processing | 89 |
| Figure H.1 – Basic view of top mounted freezer appliance | 95 |
| Figure H.2 – Automatic ice-maker dispenser and chute..... | 96 |
| Figure H.3 – Automatic ice-making compartment | 96 |
| Figure H.4 – Rail of drawer type shelves or baskets..... | 97 |
| Figure H.5 – Rotary divider of fresh food compartment for French Doors | 97 |
| Figure I.1 – Example linear interpolation two compartments (Compartment B critical) | 102 |
| Figure I.2 – Example linear interpolation two compartments (Compartment B critical) | 103 |
| Figure I.3 – Example Interpolation where both test points have both compartments below target (two valid results) | 104 |
| Figure I.4 – Example Interpolation where both test points have both compartments below target (two valid results) | 105 |
| Figure I.5 – Example Interpolation where neither test point has both compartments below target (no valid results) | 106 |
| Figure I.6 – Example Interpolation where neither test point has both compartments below target (no valid results) | 107 |
| Figure I.7 – Example Interpolation for 4 compartments | 109 |
| Figure I.8 – Example of triangulation (temperatures)..... | 111 |
| Figure I.9 – Example of triangulation (temperature and energy) | 112 |
| Figure I.10 – An example of power and temperature data | 125 |
| Figure I.11 – Example of finding a test period with minimum spread in power | 145 |
| Figure K.1 – Special Case SS2 – where steady state operation is never reached between defrost and recovery periods and Annex C stability may not be established | 149 |
| | |
| Table 1 – Target temperatures for energy determination by compartment type..... | 15 |
| Table B.1 – Assumed ΔCOP adjustment..... | 35 |
| Table F.1 – Format for temperature and humidity data – ambient controlled anti- condensation heaters..... | 69 |
| Table I.1 – Example of linear interpolation, single compartment | 100 |
| Table I.2 – Example 1 of linear interpolation, two compartments | 101 |
| Table I.3 – Example 2 of linear interpolation, two compartments | 103 |
| Table I.4 – Example 3 of linear interpolation, two compartments | 105 |
| Table I.5 – Example of linear interpolation, test data for four compartments..... | 107 |
| Table I.6 – Example of linear interpolation, results for four compartments..... | 109 |
| Table I.7 – Example of triangulation, two compartments..... | 110 |
| Table I.8 – Example of triangulation, three compartments | 115 |
| Table I.9 – Example of population-weighted humidity probabilities and heater wattages at 16 °C, 22 °C and 32 °C | 120 |
| Table I.10 – An example of calculation of energy, power and temperature for each temperature control cycle (TCC) | 126 |
| Table I.11 – An example of calculation of energy, power and temperature for all possible blocks (size = 3 TCC)..... | 128 |

| | |
|--|-----|
| Table I.12 – An example of calculation of energy, power and temperature for all possible test periods (3 blocks each of 3 TCC) | 130 |
| Table I.13 – An example of calculation of energy, power and temperature for all possible blocks (size = 5 TCC)..... | 133 |
| Table I.14 – An example of calculation of energy, power and temperature for all possible blocks (size = 9 TCC)..... | 135 |
| Table I.15 – An example of calculation of energy, power and temperature for all possible test periods (3 blocks each of 5 TCC) | 137 |
| Table I.16 – An example of calculation of energy, power and temperature for all possible test periods (3 blocks each of 9 TCC) | 139 |
| Table I.17 – Determination of defrost validity DF1 | 141 |
| Table I.18 – Determination of steady state values using SS2 | 143 |
| Table L.1 – Assumed relative insulation value for multi-compartment products | 155 |

INTERNATIONAL ELECTROTECHNICAL COMMISSION

HOUSEHOLD REFRIGERATING APPLIANCES – CHARACTERISTICS AND TEST METHODS –

Part 3: Energy consumption and volume

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62552-3 has been prepared by subcommittee 59M: Performance of electrical household and similar cooling and freezing appliances, of IEC technical committee 59: Performance of household and similar electrical appliances

IEC 62552-1, IEC 62552-2 and IEC 62552-3 cancel and replace the first edition of IEC 62552 published in 2007. IEC 62552-1, IEC 62552-2 and IEC 62552-3 together constitute a technical revision and include the following significant technical changes with respect to IEC 62552:2007:

- a) All parts of the standard have been largely rewritten and updated to cope with new testing requirements, new product configurations, the advent of electronic product controls and computer based test-room data collection and processing equipment.
- b) In Part 1 there are some changes to test room equipment specifications and the setup for testing to provide additional flexibility especially when testing multiple appliances in a single test room.

- c) For more efficient analysis and to better characterise the key product characteristics under different operating conditions, the test data from many of the energy tests in Part 3 (this part) is now split into components (such as **steady state** operation and defrost and recovery). The approach to determination of energy consumption has been completely revised, with many internal checks now included to ensure that data complying with the requirements of the standard is as accurate as possible and of high quality.
- d) Part 3 (this part) now provides a method to quantify each of the relevant energy components and approaches on how these can be combined to estimate energy under different conditions on the expectation that different regions will select components and weightings that are most applicable when setting both their local performance and energy efficiency criteria while using a single set of global test measurements.
- e) For energy consumption measurements in Part 3 (this part), no thermal mass (test packages) is included in any compartment and compartment temperatures are based on the average of air temperature sensors (compared to the temperature in the warmest test package). There are also significant differences in the position of temperature sensors in unfrozen compartments.
- f) The energy consumption test in Part 3 (this part) now has two specified ambient temperatures (16°C and 32°C).
- g) While, in Part 2 test packages are still used for the storage test to confirm performance in different operating conditions, in Part 1 they have been standardised to one size (100 mm × 100 mm × 50 mm) to simplify loading and reduce test variability. A clearance of at least 15 mm is now specified between test packages and the compartment liner.
- h) A load processing energy efficiency test has been added in Part 3 (this part).
- i) A tank-type ice making energy efficiency test has been added in Part 3 (this part).
- j) A cooling capacity test has been added in Part 2.
- k) A pull-down test has been added in Part 2.
- l) Shelf area and storage volume measurement methods are no longer included. In Part 3 the volume measurement has been revised to be the total internal volume with only components necessary for the satisfactory operation of the refrigeration system considered as being in place.
- m) Tests (both performance (Part 2) and energy (Part 3 – this part)) have been added for wine storage appliances.

The following print types are used in this international standard:

- requirements: in roman type;
- test specifications: in *italic type*;
- notes: in small roman type.
- Words in **bold** are defined in IEC 62552-1:2015, Clause 3 or in this part.

The text of this standard is based on the following documents:

| | |
|-------------|------------------|
| FDIS | Report on voting |
| 59M/63/FDIS | 59M/66/RVD |

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62252 series, published under the general title *Household refrigerating appliances – characteristics and test methods*, can be found on the IEC website.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

IEC 62552 is split into 3 parts as follows:

- IEC 62552-1: Scope, definitions, instrumentation, test room and set up of refrigerating products;
- IEC 62552-2: General performance requirements for **refrigerating appliances** and methods for testing them;
- IEC 62552-3: **Energy consumption** and **volume** determination (this part).

HOUSEHOLD REFRIGERATING APPLIANCES – CHARACTERISTICS AND TEST METHODS –

Part 3: Energy consumption and volume

1 Scope

This part of IEC 62552 specifies the essential characteristics of household and similar **refrigerating appliances** cooled by internal natural convection or forced air circulation, and establishes test methods for checking these characteristics.

This part of IEC 62552 describes the methods for the determination of **energy consumption** characteristics and defines how these can be assembled to estimate **energy consumption** under different usage and climate conditions. This part of IEC 62552 also defines the determination of **volume**.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62552-1:2015, *Household refrigerating appliances – Characteristics and test methods – Part 1: General requirements*

IEC 62552-2:2015, *Household refrigerating appliances – Characteristics and test methods – Part 2: Performance requirements*

3 Terms, definitions and symbols

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 62552-1, as well as the following apply.

3.1.1 specified auxiliaries

functions or features that affect the **energy consumption** of a **refrigerating appliance** and where their actual **energy consumption** depends on the conditions of use or operation

Note 1 to entry: This standard makes optional provision for determining the **energy consumption** impacts of these functions or features in accordance with regional requirements.

Note 2 to entry: Test requirements for specified auxiliaries, where applicable, are set out in Annex F and their application specified in 6.8.4. The only specified auxiliaries in this edition of the standard are ambient controlled anti-condensation heaters and tank type automatic icemakers.

3.1.2 defrost interval

the measured or estimated length of a **defrost control cycle**, starting from the point of initiation of one **defrost control cycle** to the point of initiation of the subsequent **defrost control cycle**, expressed in hours of elapsed (clock) time