

Australian Standard[®]

**Guide to the safe use of preservative-
treated timber**



This Australian Standard® was prepared by Committee TM-006, Timber Preservation and Durability. It was approved on behalf of the Council of Standards Australia on 2 January 2007. This Standard was published on 22 March 2007.

The following are represented on Committee TM-006:

- Australian Pesticides and Veterinary Medicines Authority
- Consumers' Federation of Australia
- Department of Primary Industries and Fisheries
- Engineered Wood Products Association of Australasia
- Engineers Australia
- Ensis
- Forests NSW
- Glued Laminated Timber Association of Australia
- Housing Industry Association, Australia
- LOSP Treated Timber Association
- New Zealand Timber Industry Federation
- New Zealand Timber Preservation Council
- Timber Preservers Association of Australasia
- Timber Queensland

Additional Interests:

- Dr Harry Greaves
-

This Standard was issued in draft form for comment as DR 03476.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

Keeping Standards up-to-date

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting www.standards.org.au

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

STANDARDS AUSTRALIA

RECONFIRMATION

OF

AS 5605—2007

Guide to the safe use of preservative-treated timber

RECONFIRMATION NOTICE

Technical Committee TM-012 has reviewed the content of this publication and in accordance with Standards Australia procedures for reconfirmation, it has been determined that the publication is still valid and does not require change.

Certain documents referenced in the publication may have been amended since the original date of publication. Users are advised to ensure that they are using the latest versions of such documents as appropriate, unless advised otherwise in this Reconfirmation Notice.

Approved for reconfirmation in accordance with Standards Australia procedures for reconfirmation on 27 April 2017.

The following are represented on Technical Committee TM-012:

Australian and New Zealand Timber Preservative Manufacturers Association
Australian Forest Products Association
Australian Pesticides and Veterinary Medicines Authority
Australian Timber Flooring Association
Australian Timber Importers Federation
Building Research Association of New Zealand
Department of Agriculture, Fisheries and Forestry (QLD)
Engineered Wood Products Association of Australasia
Forest and Wood Products Australia
Forestry Corporation of NSW
Glued Laminated Timber Association of Australia
Ministry of Business, Innovation and Employment (NZ)
NATSPEC
New Zealand Timber Industry Federation
New Zealand Timber Preservation Council
New Zealand Wood Processors Association
Responsible Care New Zealand
Scion
Tasmanian Timber Promotion Board
Timber Preservers Association of Australia

NOTES

Australian Standard[®]

**Guide to the safe use of preservative-
treated timber**

First published as AS 5605—2007.
Reissued incorporating Amendment No. 1 (February 2008).

COPYRIGHT

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia, GPO Box 476, Sydney, NSW 2001, Australia

ISBN 0 7337 8124 1

PREFACE

This Standard was prepared by the Standards Australia Committee TM-006, Timber Preservation and Durability. After consultation with stakeholders in both countries, Standards Australia and Standards New Zealand decided to develop this Standard as an Australian Standard rather than an Australian/New Zealand Standard.

This Standard incorporates Amendment No. 1 (February 2008). The changes required by the Amendment are indicated in the text by a marginal bar and amendment number against the clause, note, table, figure or part thereof affected.

The objectives of this Standard are to promote the safe use of preservative-treated timber and to reduce any potential health and environmental risk.

Timber preservatives are registered for use in Australia and regularly reviewed by the APVMA (Australian Pesticides and Veterinary Medicines Authority). The recommendations from the APVMA's recent review on copper chrome arsenate (CCA) have been incorporated in this Standard.

CONTENTS

	<i>Page</i>
FOREWORD.....	4
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE	5
1.2 APPLICATION	5
1.3 REFERENCED DOCUMENTS	5
1.4 DEFINITIONS	6
1.5 GENERAL	6
1.6 IDENTIFICATION OF PRESERVATIVE-TREATED TIMBER	6
1.7 EXPOSURE PATHWAYS	6
1.8 REFERENCES	7
SECTION 2 WATERBORNE PRESERVATIVE-TREATED TIMBER	
2.1 CCA (COPPER CHROME ARSENATE)-TREATED TIMBER.....	8
2.1.1 General	8
2.1.2 Use-site precautions.....	8
2.1.3 Handling precautions	8
2.1.4 Disposal.....	9
2.2 OTHER WATERBORNE PRESERVATIVE-TREATED TIMBER.....	9
SECTION 3 OIL-BORNE PRESERVATIVE-TREATED TIMBER	
3.1 GENERAL	10
3.2 USE-SITE PRECAUTIONS	10
3.3 HANDLING PRECAUTIONS	10
3.4 DISPOSAL	11
SECTION 4 LIGHT OIL/ORGANIC SOLVENT-BORNE PRESERVATIVE (LOSP)- TREATED TIMBER	
4.1 GENERAL	12
4.2 USE-SITE PRECAUTIONS	12
4.3 HANDLING PRECAUTIONS	12
4.4 DISPOSAL	13
SECTION 5 GLUELINE ADDITIVE-TREATED TIMBER PRODUCTS	
5.1 GENERAL	14
5.2 USE-SITE PRECAUTIONS	14
5.3 HANDLING PRECAUTIONS	14
5.4 DISPOSAL	14

FOREWORD

Preservative-treated timber is widely used throughout the community in a multitude of applications from agricultural and rural uses to supporting the very structure of our homes.

All the preservatives used for the protection of wood against biodegradation are toxic to some degree and, therefore, may be potentially hazardous. For instance, some preservative components may migrate in very small quantities from the treated wood into surrounding soil over time and there may also be incidental contact with skin during construction or use. In rare cases, the preservative, the wood itself, or other additives may cause irritation to some individuals.

The preservative-treated timber is always to be used in a fit-for-purpose manner. For instance, some of the preservatives used to protect timber for H1 and H2 exposure conditions may not be used if subjected to significant wetting.

Preservatives are localized on and within the wood. Therefore, preservatives are highly resistant to removal from the wood, being either chemically bonded to it, or physically immobile.

As with hundreds of other chemicals in regular use, precautions are required and/or advisable to ensure that the risk to the occupationally exposed, the general public, and the environment are within acceptable limits at all times.

STANDARDS AUSTRALIA

Australian Standard

Guide to the safe use of preservative-treated timber

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard is a guide to the public on the safe use of preservative-treated timber. It provides precautions and recommendations to be taken into account to reduce any potential health and environmental risks associated with using, handling and disposing of preservative-treated timber.

NOTES:

- 1 More specific occupational guidance may be found in Worksafe Australia's documents and various material safety data sheets (MSDS).
- 2 The Supplements to this Standard, AS 5605 Supp 1 to AS 5605 Supp 6, provide consumers with safety information on the use of timber treated with CCA, ACQ, copper azole, LOSP, creosote/PEC, and bifenthrin.
- 3 Recycling spent treated timber may also be considered as an option at the end of the treated commodity's service life.
- 4 AS/NZS 2843.1 specifies safety requirements for the siting, design and layout of timber preservation plants.
- 5 AS/NZS 2843.2 specifies safety requirements for the operation of timber preservation plants.

1.2 APPLICATION

Based on the type of timber preservative, this Standard is categorized into the following Sections:

- | | |
|--|------------|
| (a) Waterborne preservatives | Section 2. |
| (b) Oil-borne preservatives | Section 3. |
| (c) Light organic solvent-borne preservatives (LOSP) | Section 4. |
| (d) Glueline additives | Section 5. |

1.3 REFERENCED DOCUMENTS

AS

- | | |
|-----------|---|
| 1604 | Specification for preservative treatment (all Parts) |
| 1716 | Respiratory protective devices |
| 2161 | Occupational protective gloves |
| 2161.1 | Part 1: Selection, use and maintenance |
| 2161.2 | Part 2: General requirements |
| 2161.10.1 | Part 10.1: Protective gloves against chemicals and micro-organisms—
Terminology and performance requirements |
| 2161.10.2 | Part 10.2: Protective gloves against chemicals and micro-organisms—
Determination of resistance to penetration |
| 2161.10.3 | Part 10.3: Protective gloves against chemicals and micro-organisms—
Determination of resistance to permeation by chemicals |