

Australian Standard™

**Water supply—Metallic gate, globe and
non-return valves**



This Australian Standard was prepared by Committee WS/22, Valves for Water Supply Purposes. It was approved on behalf of the Council of Standards Australia on 15 October 1999 and published on 5 December 1999.

The following interests are represented on Committee WS/22:

Australian Chamber of Commerce and Industry
Australian Chamber of Manufactures
Australian Industry Group
Australian Valve Manufacturers Association
Hunter Water Corporation
Master Plumbers Australia
Metal Trades Industry Association of Australia
New Zealand Water and Wastes Association
Society of Mechanical Engineers Australasia
Water Services Association of Australia (WSAA)

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Australian Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for the improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

Australian Standard™

**Water supply—Metallic gate, globe and
non-return valves**

Originated as AS B310—1971.
Previous edition AS 1628—1994.
Final edition 1999.
Reissued incorporating Amendment No. 1 (November 2001).

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 3036 1

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee WS/3, Valves for Water Supply Purposes, to supersede AS 1628—1994, *Water supply—Copper alloy gate, globe and non-return valves*.

This Standard incorporates Amendment No. 1 (November 2001). The changes required by the Amendment are indicated in the text by a marginal bar and amendment number against the clause, note, table, figure or part thereof affected.

This Standard is the result of a consensus among Australia/New Zealand representatives on the Committee to produce it as an Australian Standard.

The objective of this Standard is to include design, materials and type tests required for valves nominated in this Standard.

This edition includes modification to the title, amendments and additional smaller DN sizes.

The terms ‘normative’ and ‘informative’ have been used in this Standard to define the application of the appendix to which they apply. A ‘normative’ appendix is an integral part of a Standard, whereas an ‘informative’ appendix is only for information and guidance.

Statements expressed in mandatory terms in notes to tables and figures are deemed to be requirements of this Standard.

Support and contribution is acknowledged from water authorities, manufacturers, importers and Water Services Association of Australia (WSAA).

CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE.....	5
1.2 REFERENCED DOCUMENTS.....	5
1.3 DEFINITIONS.....	5
1.4 DESIGNATION OF SIZE.....	5
1.5 MARKING.....	5
1.6 ALLOWABLE PRESSURES.....	6
SECTION 2 MATERIALS	
2.1 SCOPE OF SECTION.....	7
2.2 COPPER.....	7
2.3 COPPER ALLOY.....	7
2.4 STAINLESS STEEL.....	7
2.5 OTHER MATERIALS.....	7
2.6 CORROSION-RESISTANT METALLIC MATERIALS.....	8
2.7 CONTAMINATION OF WATER.....	8
SECTION 3 DESIGN AND MANUFACTURE	
3.1 SCOPE OF SECTION.....	9
3.2 END CONNECTORS.....	9
3.3 INTERCHANGEABILITY OF PARTS.....	9
3.4 SCREW THREADS (for factory-assembled components).....	9
3.5 THICKNESS OF METAL PARTS.....	10
3.6 OPERATING METHODS FOR GATE AND GLOBE VALVES.....	10
3.7 WATERWAY AND FLOW CAPABILITY.....	11
3.8 FLOW-WAY AREA.....	11
3.9 FINISH.....	12
SECTION 4 TESTING REQUIREMENTS	
4.1 SCOPE OF SECTION.....	13
4.2 PRESSURE TESTS.....	13
4.3 WATERTIGHTNESS.....	13
4.4 STRENGTH OF OPERATING MECHANISM.....	13
4.5 STRENGTH OF VALVE ASSEMBLY.....	13
4.6 TYPE TESTS.....	13
SECTION 5 GATE AND GLOBE VALVES	
5.1 SCOPE OF SECTION.....	14
5.2 BODY SEATS.....	14
5.3 FACE-TO-FACE DIMENSIONS.....	14
5.4 GATES.....	15
5.5 STEMS.....	15
5.6 BONNETS.....	15
5.7 GLANDS.....	15

	<i>Page</i>
SECTION 6 NON-RETURN VALVES	
6.1 SCOPE OF SECTION.....	16
6.2 DESIGN.....	16
6.3 VALVE BODIES.....	16
6.4 NON-RETURN MECHANISM	17
6.5 COVERS.....	17
APPENDICES	
A LIST OF REFERENCED DOCUMENTS.....	18
B WATERTIGHTNESS TEST.....	20
C TORQUE TEST FOR OPERATING MECHANISM.....	22
D STRENGTH TEST FOR VALVE ASSEMBLY	24

STANDARDS AUSTRALIA**Australian Standard****Water supply—Metallic gate, globe and non-return valves****SECTION 1 SCOPE AND GENERAL****1.1 SCOPE**

This Standard specifies requirements for metallic gate, globe and non-return valves of nominal sizes DN 8 to DN 100 for use in hot and cold water applications where the operating temperature does not exceed 99°C.

1.2 REFERENCED DOCUMENTS

A list of the documents referred to in this Standard is given in Appendix A.

1.3 DEFINITIONS

For the purpose of this Standard, the definitions given in AS/NZS 3500.0 and those below apply.

1.3.1 Component

That part, or a sub-assembly of parts, which contribute to the construction of a total assembly by choice or design which may offer variations of fitment for the application to the major element of the product, whether produced by that same manufacturer or not.

1.3.2 Dashpot

A device, usually an integral component of a valve, designed for the purpose of reducing the fluid velocity or damping vibration in the valve and the associated connected pipework system.

1.4 DESIGNATION OF SIZE

The size of a valve that is nominally designated shall be the nominal size of the pipe with which it is intended to be used.

1.5 MARKING**1.5.1 Marking requirements**

All valves shall be legibly marked by a casting or indenting process with the following:

- (a) Manufacturer's name or mark.
- (b) Nominal size.
- (c) Maximum operating pressure
- (d) An arrow (\leftrightarrow), permanently marked on the handwheel, showing the open \leftrightarrow closure operating direction.
- (e) In the case of non-return valves, an indication on the top of the valve showing direction of flow.
- (f) For copper alloy valves the letters DR.