

Australian Standard[®]

**Adhesives—For fixing
ceramic tiles**

This Australian Standard was prepared by Committee CH/17, Adhesives. It was approved on behalf of the Council of Standards Australia on 6 April 1990 and published on 12 November 1990.

The following interests are represented on Committee CH/17:

Adhesives and Sealants Manufacturers Association of Australia
Chemical Federation of Australia
Confederation of Australian Industry
Division of Building, Construction and Engineering, CSIRO
Footwear Manufacturers Association of Australia
Furniture Manufacturers Association of Australia
Plywood Association of Australia
Printing and Allied Trades Employers Federation of Australia
Society of Automotive Engineers-Australasia
Telecom Australia

Review of Australian Standards. *To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.*

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 88091.

AS 2358—1990

Australian Standard[®]

**Adhesives—For fixing
ceramic tiles**

First published as AS 2358—1980.
Second edition 1990.

Incorporating:
Amdt 1—1994

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 6305 2

PREFACE

This Standard was prepared by the Standards Australia Committee on Adhesives, under the direction of the Chemical Standards Board, to supersede AS 2358 — 1980, *Adhesives for ceramic wall tiles and mosaics*. It is to be used in conjunction with the Standard for fixing of ceramic tiles, which is under preparation.

This edition has been expanded to comprise four sections.

Unlike the previous edition, adhesives for fixing ceramic floor tiles have been included, and provision has been made for the testing of the adhesive with tiles of low water absorption. Requirements for shear modulus of elasticity have also been included and the test for staining has been amended. Performance requirements for cement-based tile fixing mortars incorporating organic additives have been included in a separate section (Section 4). The previous edition applied to cement-based adhesives where latex-modified mortars requiring the addition of a specified amount of the latex was to be added to a mortar of a specified composition. However, there was no requirement for specifying the mortar composition or the amount of latex.

The method of test for strain development has been excluded from this edition as it is no longer considered to be necessary. Should a question arise regarding the compatibility of a cement-based adhesive with a specific tile, reference should be made to BS 5980 — 1980.

In the preparation of this Standard, cognizance was taken of the following Standards:

BS 5385 *Wall and floor tiling*

Part 1: *Code of practice for internal ceramic wall tiling and mosaics in normal conditions*

Part 2: *Code of practice for external ceramic wall tiling and mosaics*

Part 4: *Code of practice for ceramic tiling and mosaics in specific conditions*

BS 5980 *Specification for adhesives for use with ceramic tiles and mosaics*

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE OF SECTION	5
1.2 REFERENCED DOCUMENTS	5
1.3 DEFINITIONS	5
1.4 CLASSIFICATION OF ORGANIC-BASED ADHESIVES	5
1.5 APPEARANCE	6
1.6 PRODUCT INFORMATION	6
1.7 PACKAGING	6
1.8 MARKING	6
SECTION 2 ORGANIC-BASED ADHESIVES FOR WALL AND FLOOR APPLICATIONS	
2.1 SCOPE OF SECTION	7
2.2 BOND STRENGTH IN SHEAR AT ROOM TEMPERATURE AFTER 28 DAYS AIR DRYING	7
2.3 BOND STRENGTH IN SHEAR AT ROOM TEMPERATURE AFTER WATER IMMERSION (FOR WATER-RESISTANT ADHESIVES ONLY)	7
2.4 BOND STRENGTH IN SHEAR AT ROOM TEMPERATURE AFTER CYCLIC WATER IMMERSION (FOR ORGANIC-BASED, GENERAL PURPOSE ADHESIVES ONLY)	7
2.5 CYCLIC ACCELERATED AGEING TEST	7
2.6 BOND STRENGTH IN TENSION AT ROOM TEMPERATURE AFTER AIR DRYING ...	7
2.7 SHEAR MODULUS OF ELASTICITY	7
2.8 STAINING	7
2.9 RESISTANCE TO FUNGAL GROWTH	7
SECTION 3 CEMENT-BASED ADHESIVES FOR WALL AND FLOOR APPLICATIONS	
3.1 SCOPE OF SECTION	8
3.2 BOND STRENGTH IN SHEAR AT ROOM TEMPERATURE AFTER SEVEN DAYS AIR DRYING	8
3.3 BOND STRENGTH IN SHEAR AT ROOM TEMPERATURE AFTER 14 DAYS AIR DRYING	8
3.4 BOND STRENGTH IN SHEAR AT ROOM TEMPERATURE AFTER WATER IMMERSION .	8
3.5 BOND STRENGTH IN TENSION AT ROOM TEMPERATURE AFTER AIR DRYING ...	8
3.6 SHEAR MODULUS OF ELASTICITY	8
3.7 STAINING	8
3.8 RESISTANCE TO FUNGAL GROWTH	8
SECTION 4 CEMENT-BASED TILE FIXING MORTARS CONTAINING ORGANIC ADDITIVES FOR WALL AND FLOOR APPLICATIONS	
4.1 SCOPE OF SECTION	9
4.2 BOND STRENGTH IN SHEAR AT ROOM TEMPERATURE AFTER SEVEN DAYS AIR DRYING	9
4.3 BOND STRENGTH IN SHEAR AT ROOM TEMPERATURE AFTER 14 DAYS AIR DRYING	9
4.4 BOND STRENGTH IN SHEAR AT ROOM TEMPERATURE AFTER WATER IMMERSION .	9
4.5 BOND STRENGTH IN TENSION AT ROOM TEMPERATURE AFTER AIR DRYING ...	9
4.6 SHEAR MODULUS OF ELASTICITY	9
4.7 STAINING	9
4.8 RESISTANCE TO FUNGAL GROWTH	9

APPENDICES

A	METHOD FOR DETERMINING BOND STRENGTH IN SHEAR OF AN ADHESIVE OR PREPARED MORTAR AFTER CONDITIONING	10
B	METHOD FOR DETERMINING BOND STRENGTH IN SHEAR OF A WATER-RESISTANT ADHESIVE OR PREPARED MORTAR AT ROOM TEMPERATURE, AFTER WATER IMMERSION	14
C	METHOD FOR DETERMINING BOND STRENGTH IN SHEAR OF AN ADHESIVE AT ROOM TEMPERATURE, AFTER CYCLIC WATER IMMERSION (ORGANIC-BASED, GENERAL PURPOSE ADHESIVE ONLY)	16
D	METHOD FOR DETERMINING BOND STRENGTH IN SHEAR OF AN ADHESIVE, AFTER CYCLIC ACCELERATED AGEING (ORGANIC-BASED ADHESIVE ONLY)	18
E	METHOD FOR DETERMINING BOND STRENGTH IN TENSION OF AN ADHESIVE OR PREPARED MORTAR AT ROOM TEMPERATURE AFTER AIR DRYING	20
F	METHOD OF DETERMINING SHEAR MODULUS OF ELASTICITY OF AN ADHESIVE OR PREPARED MORTAR AFTER CONDITIONING IN AIR	24
G	METHOD OF TEST FOR STAINING	27
H	METHOD FOR DETERMINING RESISTANCE TO FUNGAL GROWTH	29

STANDARDS AUSTRALIA

Australian Standard
Adhesives—For fixing ceramic tiles

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE. This Standard specifies performance requirements for organic-based adhesives, cement-based adhesives and cement-based mortars containing organic additives used as adhesives for the installation of ceramic wall and floor tiles and mosaics.

The Standard is not intended to cover adhesives such as chemical resistant epoxy and furan-based compositions, which are designed for the installation of ceramic tiles in industrial applications.

Specialized installations such as swimming pools, hot wall service conditions (e.g. tiled areas in close proximity to high heat output), industrial and institutional installations and cold wall service conditions (e.g. tiled areas in freezer chambers, cold rooms) are not specifically covered by this Standard:

1.2 REFERENCED DOCUMENTS. The following documents are referred to in this Standard.

AS

1157 Methods of testing materials for resistance to fungal growth

1157.1 Part 1: General principles of testing

1157.10 Part 10: Resistance of adhesives and glues to fungal growth

1309 Glossary of terms used in the adhesives industry

2193 Methods for calibration and grading of force-measuring systems of testing machines

BS

6431 Ceramic floor and wall tiles

Part 11: Method for determination of water absorption

1.3 DEFINITIONS. For the purpose of this Standard, the definitions given in AS 1309 and those below apply.

1.3.1 Thin-bed—a finished adhesive bedding coat not exceeding 3 mm in thickness.

1.3.2 Thick-bed—a finished adhesive bedding coat exceeding 3 mm in thickness.

1.3.3 Organic-based adhesive—an adhesive which may be supplied as either a one-part or a two-part mix, and in which the principal bonding component is an organic material.

1.3.4 Cement-based adhesive—an adhesive in which the principal bonding component is a hydraulic cement, e.g. Portland cement, modified by the inclusion of such other admixtures as may be necessary in order to achieve satisfactory bonding of ceramic wall and floor tiles and mosaics.

1.3.5 Organic additive—material added to a cement-based mortar for modifying its properties.

1.3.6 Cement-based mortar—a mixture with Portland cement and sand as the primary constituents.

1.3.7 Prepared mortar—a mortar containing a specified organic additive in a specified quantity in accordance with the additive manufacturer's instructions.

1.3.8 Tiles of low water absorption—tiles having water absorption of not more than 3 percent, by mass.

1.3.9 Tiles of high water absorption—tiles having water absorption greater than 10 percent and not more than 20 percent, by mass.

1.3.10 Staining—discolouration, due to the adhesive, of the body of the tile visible through the glaze, or of the glaze in some intensely coloured decorative tiles.

1.3.11 Shelf life—the period during which the adhesive or organic additive will comply with the requirements of this Standard when stored in an unopened container supplied by the manufacturer, under the conditions recommended by the manufacturer.

1.4 CLASSIFICATION OF ORGANIC-BASED ADHESIVES. Organic-based adhesives are classified as follows:

- (a) *General purpose*—for installation of ceramic tiles and mosaics in interior areas where the face of the tile is subjected to intermittent exposure to water.
- (b) *Water-resistant*—for installation of ceramic tiles and mosaics in areas where the face of the tile is subjected to prolonged exposure to water.