

3310—1988 Approval and Test Specification—Particular requirements for range hoods (In Update Service 28) A4 9pp C
Specifies essential safety requirements for approval and test purposes and is intended to be read in conjunction with AS 3300. Generally technically equivalent to IEC 335-2-31—1979.
Committee EL/2: Supersedes AS 3310—1984: Publication date 1988-04-05: ISBN 0 7262 4907 6.

1988 ED.

AS 3310—1984
UDC 621.31:644.1:643.3:641.53

Australian Standard 3310—1984

Amend .1 —1986

APPROVAL AND TEST SPECIFICATION — PARTICULAR REQUIREMENTS FOR RANGE HOODS



PUBLISHED BY THE STANDARDS ASSOCIATION OF AUSTRALIA
STANDARDS HOUSE, 80 ARTHUR ST, NORTH SYDNEY, N.S.W.

Incorporated by Royal Charter

This Australian standard was prepared by Committee EL/2, Electrical Approvals Standards. It was approved on behalf of the Council of the Standards Association of Australia on 31 July 1984 and published on 5 October 1984.

The following interests are represented on Committee EL/2:

- Australian Consumers Association
 - Australian Electrical and Electronic Manufacturers Association
 - Confederation of Australian Industry
 - Consumer Electronics Suppliers Association
 - Electrical Apparatus Approvals Authorities
 - Electrical Testing Laboratories
 - Electricity Supply Association of Australia
 - Electronics Importers Association
-

Review of Australian Standards. To keep abreast of progress in industry, Australian standards are subject to periodic review and are kept up-to-date by the issue of amendments or new editions as necessary. It is important therefore that standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all SAA publications will be found in the Catalogue of Australian Standards; this information is supplemented each month by SAA's journal 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn standards.

Suggestions for improvements to Australian standards, addressed to the head office of the Association, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian standard should be made without delay in order that the matter may be investigated and appropriate action taken.

First published 1984

This standard was issued in draft form for comment as DR 81253.

©Copyright — STANDARDS ASSOCIATION OF AUSTRALIA 1984

Users of standards are reminded that copyright subsists in all SAA publications. No part of this publication may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing of the Standards Association of Australia.

ISBN 0 7262 3507 5

STANDARDS ASSOCIATION OF AUSTRALIA
Incorporated by Royal Charter

AMENDMENT No 1
to
AS 3310—1984
Approval and Test Specification—
PARTICULAR REQUIREMENTS FOR RANGE HOODS

REVISED TEXT

The 1984 edition of AS 3310 is amended as follows; the amendment should be inserted in the appropriate place.

SUMMARY: The following section of the standard is covered by this amendment: Clause 30.

Published on 3 March 1986.

AMDT
No 1
MAR.
1986

Page 8. Clause 30.

Delete the following:

'Clauses 30.1 and 30.2 are not required.'

Delete Clause 30.101 and *substitute* the following:

30.101.2 Glow-wire tip temperature and duration of test.

Item (a)—replace 'As specified in the individual approval and test specification' with '850 °C for 30 s'.

Item (b)—replace 'As specified in the individual approval and test specification' with '750 °C for 30 s'.

In addition, non-metallic decorative trims, diffusers and other material used on the underside of the hood, and in the air-handling compartment and any associated ducting, shall be subjected to the needle flame test of AS 2420 and the results determined in accordance with the provisions thereof.

NOTES:

1. The requirement for decorative trims, etc is similar to that of Clause 22.15 of IEC 335-2-31, except that for Australian conditions, reference has been made to the needle flame test of AS 2420 in lieu of the burning test of IEC 553, and no limit on the total volume of these parts is specified (IEC specified < 300 cm³), provided that the materials pass the needle flame test.
2. Consideration is being given to the inclusion of a mandatory requirement that a means of stopping the range hood air flow to prevent any fire originating from the cooking appliance being discharged by the range hood be incorporated.

This amendment forms part of the specification on publication.

PREFACE

This standard was prepared by the Association's Committee on Electrical Approvals Standards.

It contains specific requirements for range hoods and is a supplementary specification to AS 3300, Approval and Test Specification for General Requirements for Household and Similar Electrical Appliances (which closely follows IEC 335-1).

The clauses of this standard supplement or modify the corresponding clauses in AS 3300. Where the reference in the text of this standard indicates an 'addition' or 'replacement' of the relevant requirements, tests or explanatory notes of AS 3300, these changes are made to the relevant text which then become part of the standard. It will be observed that when no such change is necessary, the words 'this Clause of AS 3300 is applicable' are used.

This standard closely follows IEC 335-2-31, Particular Requirements for Range Hoods; however, some of the requirements of that publication have been modified to take account of local conditions. Where this standard deviates technically from IEC 335-2-31 by

way of additional or different requirements, the deviation is indicated by a rule in the margin against the clause, or part thereof, affected. Where the requirements of AS 3300 do not apply to range hoods, the words, 'not applicable' are used. Where the requirements of AS 3300 are additional to the essential safety requirements presently specified in the AS 3100 series of specifications and are not to be applied, the words 'not required' are used. An annex to the standard lists the variations from IEC 335-2-31. It should be noted that there are variations between AS 3300 and IEC 335-1 (see AS 3300 for such information which must also be taken into account).

Preparation of this standard was undertaken to progressively align Australian approval and test specifications and IEC standards for appliances.

This standard requires reference to the following approval and test specifications:

AS 3191 Electric Flexible Cords

AS 3300 General Requirements for Household and Similar Electrical Appliances.

CONTENTS

	<i>Page</i>		<i>Page</i>
1. Scope	4	24. Components	7
2. Definitions	4	25. Supply Connection and External Flexible Cables and Cords	7
3. General Requirements	4	26. Terminals for External Conductors	7
4. General Notes on Tests	4	27. Provision for Earthing	8
5. Rating	4	28. Screws and Connections	8
6. Classification	4	29. Creepage Distances, Clearances and Distances Through Insulation	8
7. Marking	4	30. Resistance to Heat, Fire and Tracking	8
8. Protection Against Electric Shock	5	31. Resistance to Rusting	8
9. Starting of Motor-operated Appliances	5	32. Radiation, Toxicity and Similar Hazards	8
10. Input and Current	5		
11. Heating	5	APPENDICES	
12. Operation Under Overload Conditions of Appliances with Heating Elements	5	A (Void)	9
13. Electrical Insulation and Leakage Current at Operating Temperature	5	B Electronic Circuits	9
14. Radio and Television Interference	6	C (Void)	9
15. Moisture Resistance	6	D Alternative Requirements for Protected Motor Units	9
16. Insulation Resistance and Electric Strength	6	E Measurement of Creepage Distances and Clearances	9
17. Overload Protection	6	F Motors not Isolated from the Supply Mains and having Basic Insulation not Designed for the Rated Voltage of the Appliance	9
18. Endurance	6	G Circuit for Measuring Leakage Currents	9
19. Abnormal Operation	6		
20. Stability and Mechanical Hazards	6	ANNEX. VARIATIONS BETWEEN THIS STANDARD AND IEC 335-2-31	
21. Mechanical Strength	6		
22. Construction	6		
23. Internal Wiring	7		10

STANDARDS ASSOCIATION OF AUSTRALIA

Australian Standard
APPROVAL AND TEST SPECIFICATION—
PARTICULAR REQUIREMENTS FOR RANGE HOODS

1. SCOPE

This Clause of AS 3300 is applicable except as follows:
REPLACEMENT. Replace Clause 1.1. with the following:

1.1 SCOPE AND APPLICATION. This specification applies to range hoods incorporating electrical equipment, such as fans, lamps and controls, intended for mounting above household cooking ranges, ovens and similar cooking appliances.

NOTES:

1. This specification does not apply to range hoods for industrial purposes or for use in locations where a corrosive or explosive atmosphere may be present.
2. For range hoods intended to be used in vehicles or on board ships or aircraft, additional requirements may be necessary.

2. DEFINITIONS

This Clause of AS 3300 is applicable except as follows:
REPLACEMENT. Replace Clause 2.2.30 with the following:

2.2.30 Normal load denotes the load obtained when the range hood is operated as in normal use, the hood being assembled in accordance with the manufacturer's instructions, but not connected to a duct or the like.

ADDITION. Add the following new definition:

2.2.101 Range hoods (cooker hood or canopy hood) denotes an appliance intended to collect contaminated air from above a cooking appliance. It may pass the contaminated air through a filter and discharge it into the room, or remove it from the room.

3. GENERAL REQUIREMENTS

This Clause of AS 3300 is applicable except as follows:
REPLACEMENT.

3.101 D.C. FROM A.C. APPLIANCES. Replace the fifth paragraph and Notes 1 and 2 with the following:

The permissible direct current in the equipment neutral shall not exceed 20 mA.

4. GENERAL NOTES ON TESTS

This Clause of AS 3300 is applicable except as follows:
REPLACEMENT.

4.3 ORDER OF TESTS. Replace the first paragraph with the following:

The tests are carried out in the order of the clauses of this specification, except that the test of Clause 19.101 is made before that of Clause 19.11.

Clauses 4.8 and 4.12 are not applicable.

5. RATING

This Clause of AS 3300 is applicable.

6. CLASSIFICATION

This Clause of AS 3300 is applicable.

7. MARKING

This Clause of AS 3300 is applicable except as follows:
 Clause 7.1 item (h) is not applicable.

REPLACEMENT.

7.1 GENERAL. Replace item (m) with the following:

- (m) Range hoods shall be marked with the substance of the following warnings, unless these warnings are included in the instruction sheet:
 - (i) Clean frequently all deposits from the fan and other contaminated surfaces.
 - (ii) Frequently remove and clean, or replace any filter unit provided.

ADDITION.

7.1 GENERAL. Add the following new item, and a new Note:

- (n) Maximum rated input of any replaceable lamp other than a pilot lamp, in watts.

NOTES:

6. See also the requirements of Clause 7.14.

Clauses 7.2 and 7.3 are not applicable.

Clause 7.5. The third paragraph is not applicable.

ADDITION.

7.12 INSTRUCTIONS FOR INSTALLATION AND USE. Add the following new paragraph:

The instruction sheet shall specify the minimum distance between the surface of hob elements and/or burners, and the lower part of the range hood and shall include the substance of the following warning:

Exhaust air must not be discharged into any chimney or flue which may carry combustion products from other sources. In addition, exhaust air must not be discharged into a wall cavity, unless designed for the purpose.