

Australian/New Zealand Standard™

Specification for radio disturbance and immunity measuring apparatus and methods

Part 4.5: Uncertainties, statistics and limit modelling—Conditions for the use of alternative test methods



AS/NZS CISPR 16.4.5:2013

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee TE-003, Electromagnetic Interference. It was approved on behalf of the Council of Standards Australia on 31 May 2013 and on behalf of the Council of Standards New Zealand on 23 April 2013.
This Standard was published on 20 June 2013.

The following are represented on Committee TE-003:

Australian Broadcasting Corporation
Australian Communications and Media Authority
Australian Industry Group
Australian Information Industry Association
Consumer Electronics Suppliers Association
Consumers Federation of Australia
Curtin University of Technology
Department of Defence, Australia
Electrical Compliance Testing Association
Energy Networks Association
Engineers Australia
Lighting Council New Zealand
Lighting Council of Australia
Ministry of Economic Development, New Zealand
National Measurement Institute
Wireless Institute Australia

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Web Shop at www.saiglobal.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia or Standards New Zealand at the address shown on the back cover.

Australian/New Zealand Standard™

Specification for radio disturbance and immunity measuring apparatus and methods

Part 4.5: Uncertainties, statistics and limit modelling—Conditions for the use of alternative test methods

First published as AS/NZS CISPR 16.4.5:2013.

COPYRIGHT

© Standards Australia Limited/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Australia) or the Copyright Act 1994 (New Zealand).

Jointly published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001 and by Standards New Zealand, Private Bag 2439, Wellington 6140.

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee TE-003, Electromagnetic Interference.

The objective of this Standard is to specify a method to enable product committees to develop limits for alternative test methods, using conversions from established limits.

This Standard is identical with, and has been reproduced from CISPR/TR 16-4-5, Ed. 1.0 (2006), *Specification for radio disturbance and immunity measuring apparatus and methods—Part 4-5: Uncertainties, statistics and limit modelling—Conditions for the use of alternative test methods*.

As this Standard is reproduced from an International Standard, the following applies:

- (a) In the source text ‘this part of CISPR 16-4’ should read ‘this Australian/New Zealand Standard’.
- (b) A full point substitutes for a comma when referring to a decimal marker.

References to International Standards should be replaced by references to Australian or Australian/New Zealand Standards, as follows:

<i>Reference to International Standard</i>	<i>Australian/New Zealand Standard</i>
CISPR	AS/NZS CISPR
16 Specification for radio disturbance and immunity measuring apparatus and methods	16 Specification for radio disturbance and immunity measuring apparatus and methods
16-4-1 Part 4-1: Uncertainties, statistics and limit modelling—Uncertainties in standardized EMC tests (2003)	16.4.1 Part 4.1: Uncertainties, statistics and limit modelling—Uncertainties in standardized EMC tests (2004)
16-4-2 Part 4-2: Uncertainties, statistics and limit modelling—Uncertainty in EMC measurements (2003)	16.4.2 Part 4.2: Uncertainties, statistics and limit modelling—Uncertainty in EMC measurements (2004)

Only international references that have been adopted as Australian or Australian/New Zealand Standards have been listed.

The term ‘informative’ has been used in this Standard to define the application of the annex to which it applies. An ‘informative’ annex is only for information and guidance.

CONTENTS

1	Scope	6
2	Normative references	6
3	Terms and definitions	6
4	Symbols and abbreviated terms	7
5	Introduction	8
6	Procedure to derive limits for an alternative test method	9
6.1	Overview	9
6.2	Select the reference quantity X	12
6.3	Describe the test methods and measurands	12
6.4	Determine the deviations of the measured quantities from the reference quantity	13
6.5	Determine the average values of the deviations	13
6.6	Estimate the standard uncertainties of the test methods	14
6.7	Estimate the expanded uncertainties of the test methods	15
6.8	Calculate the average conversion factor	16
6.9	Verify the calculated values	17
6.10	Apply the conversion	17
	Annex A (informative) Remarks on EUT modelling	18
	Annex B (informative) Examples of application of the test method comparison procedure	19
	Bibliography	49
	Figure 1 – Overview of quantities to estimate for use in conversion procedure	10
	Figure 2 – Overview of limit conversion procedure using estimated quantities	11
	Figure B.1 – Example reference quantity	19
	Figure B.2 – EUT and antenna set-up for fully anechoic room emission measurement	20
	Figure B.3 – EUT and antenna set-up for open-area test site measurement	20
	Figure B.4 – Radiation characteristics of elementary radiator (left), and scheme of EUT-model (right)	21
	Figure B.5 – Maximum average deviations for 3 m FAR (top) and 10 m OATS (bottom)	24
	Figure B.6 – Sample cumulative distribution function	26
	Figure B.7 – Uncertainties due to the unknown EUT characteristic for 3 m FAR (top) and 10 m OATS (bottom)	28
	Figure B.8 – Expanded uncertainties ($k = 2$) of alternative (3 m FAR, top) and established (10 m OATS, bottom) test methods	32
	Figure B.9 – Maximum average conversion factors for different volumes	33
	Figure B.10 – Photo (left) and cut-view of simulation model (right) of the specimen EUT	35
	Figure B.11 – Deviations of the specimen EUT: 3 m fully anechoic room (top) and 10 m open area test site (bottom)	36
	Figure B.12 – Sample FAR measurement	37
	Figure B.13 – OATS 10 m limit line converted to FAR 3 m conditions	37

	<i>Page</i>
Figure B.14 – Expanded uncertainties.....	37
Figure B.15 – Comparison of the measured values with the corrected converted limit.....	38
Figure B.16 – EUT and antenna set-up of 3 m open area test site measurement.....	39
Figure B.17 – Maximum average deviations for 3 m OATS.....	40
Figure B.18 – Uncertainties due to the unknown EUT characteristic for 3 m OATS.....	41
Figure B.19 – Expanded uncertainties ($k = 2$) of alternative test method [OATS (3 m)].....	43
Figure B.20 – Maximum average conversion factors	44
Figure B.21 – Deviations of the specimen EUT: Open area test site (3 m).....	46
Figure B.22 – Sample OATS (3 m) measurement.....	47
Figure B.23 – OATS (10 m) limit line converted to OATS (3 m) conditions	47
Figure B.24 – Expanded uncertainties.....	48
Figure B.25 – Comparison of the corrected values with the converted limit	48
Table 1 – Summary of steps in conversion procedure	9
Table 2 – Overview of quantities and defining equations for conversion process.....	12
Table B.1 – Instrumentation uncertainty of the 3 m fully anechoic chamber test method	25
Table B.2 – Uncertainties in dB due to the unknown EUT characteristic for 3 m FAR	30
Table B.3 – Uncertainties in dB due to the unknown EUT characteristic for 10 m OATS.....	31
Table B.4 – Maximum average conversion factors in dB between 10 m OATS and 3 m FAR	34
Table B.5 – Uncertainties in dB due to the unknown EUT characteristic for 3 m OATS.....	42
Table B.6 – Maximum average conversion factors in dB between 10 m and 3 m OATS.....	45

AUSTRALIAN/NEW ZEALAND STANDARD

Specification for radio disturbance and immunity measuring apparatus and methods**Part 4.5:****Uncertainties, statistics and limit modelling—Conditions for the use of alternative test methods****1 Scope**

This part of CISPR 16-4 specifies a method to enable product committees to develop limits for alternative test methods, using conversions from established limits. This method is generally applicable for all kinds of disturbance measurements, but focuses on radiated disturbance measurements (i.e. field strength), for which several alternative methods are presently specified. These limits development methods are intended for use by product committees and other groups responsible for defining emissions limits in situations where it is decided to use alternative test methods and the associated limits in product standards.

2 Normative references

IEC 60050-161, *International Electrotechnical Vocabulary (IEV) – Chapter 161: Electromagnetic compatibility*

CISPR 16-4-1:2003, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-1: Uncertainties, statistics and limit modelling – Uncertainty in standardized EMC tests*

CISPR 16-4-2:2003, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 4-2: Uncertainties, statistics and limit modelling – Uncertainty in EMC measurements*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-161 and the following apply.

3.1**established test method**

test method described in a basic standard with established emissions limits defined in corresponding product or generic standards. An established test method consists of a specific test procedure, a specific test set-up, a specific test facility or site, and an established emissions limit

NOTE The following test methods have been considered to be established test methods in CISPR:

- conducted disturbance measurements: test method defined in CISPR 16-2-1:2003, Clause 7;
- radiated disturbance measurements up to 1 GHz: the test method defined in CISPR 16-2-3, 7.2.1;
- radiated disturbance measurements up to 18 GHz: the test method defined in CISPR 16-2-3, 7.3.

3.2**alternative test method**

test method described in a basic standard without established emissions limits. The alternative test method is designed for the same purpose as the established test method. An alternative test method consists of a specific test procedure, a specific test set-up, a specific test facility or site, and a derived emissions limit that was determined by the application of the proposed method stated in this document