

American National Standard for
Rotodynamic Pumps
for Design and Application

Sponsor
Hydraulic Institute
www.Pumps.org

Approved February 1, 2019
American National Standards Institute, Inc.

American National Standard

Approval of an American National Standard requires verification by ANSI that the requirements for due process, consensus and other criteria for approval have been met by the standards developer.

Consensus is established when, in the judgement of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

The use of American National Standards is completely voluntary; their existence does not in any respect preclude anyone, whether he has approved the standards or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the standards.

The American National Standards Institute does not develop standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on the title page of this standard.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute require that action be taken periodically to reaffirm, revise, or withdraw this standard. Purchasers of American National Standards may receive current information on all standards by calling or writing the American National Standards Institute.

Published By

Hydraulic Institute
6 Campus Drive, First Floor North
Parsippany, NJ 07054-4406
www.Pumps.org

Copyright © 2019 Hydraulic Institute
All rights reserved.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without prior written permission of the publisher.

Printed in the United States of America
ISBN 978-1-935762-81-2



Recycled
paper

Contents

Page

Forewordxiii	
14.3	Rotodynamic pump design and application..... 1	
14.3.1	Introduction	1
14.3.1.1	Purpose	1
14.3.1.2	Scope	1
14.3.1.3	Preferred terms, units, and symbols for pump applications	2
14.3.2	Rotodynamic pump classifications	5
14.3.2.1	Pump types	5
14.3.3	Performance	20
14.3.3.1	Characteristic curves	20
14.3.3.2	Pump and system curve interaction	21
14.3.3.3	Typical curve shape	22
14.3.3.4	Predicting pump performance after speed of rotation or impeller diameter change ..	28
14.3.3.5	Variable-speed drives	33
14.3.4	Applications	34
14.3.4.1	Pump selection process	34
14.3.4.2	Continuous, intermittent, and cyclic service	37
14.3.4.3	System pressure limitation	37
14.3.4.4	Operation away from the best efficiency point	38
14.3.4.5	Liquid temperature rise in a rotodynamic pump	40
14.3.4.6	Pump priming	45
14.3.4.7	Viscosity	46
14.3.4.8	Two-phase flow	46
14.3.4.9	Solids	51
14.3.4.10	NPSHA considerations for temperature and elevation	51
14.3.4.11	Application considerations – viscous liquids	56
14.3.4.12	Special axial flow pump application considerations – siphon system	58
14.3.4.13	Intake	58
14.3.4.14	Self-primer features	61
14.3.4.15	Losses	63
14.3.4.16	Start-up and shut-down	65
14.3.4.17	Pump and motor speed torque curves	67
14.3.4.18	Discharge valve position for start-up	72

14.3.4.19	Shut-down	73
14.3.4.20	Self-priming pumps, start-up and shut-down considerations (valve position)	74
14.3.4.21	Reverse runaway speed.	74
14.3.4.22	Water hammer (hydraulic shock)	74
14.3.4.23	Vibration/dynamics.	75
14.3.4.24	Sound.	75
14.3.5	Hydraulic features	78
14.3.5.1	Specific speed	78
14.3.5.2	Impeller configurations	81
14.3.5.3	Casing design.	84
14.3.5.4	Hydraulic loading	88
14.3.6	Mechanical features.	119
14.3.6.1	Casing design.	119
14.3.6.2	Column design (vertical pumps).	119
14.3.6.3	Discharge head (structural element)	122
14.3.6.4	Rotor shaft design	126
14.3.6.5	Design of vertical lineshaft	136
Appendix A	Introduction to general applications.	141
A.1	General service applications	141
Appendix B	Special effects pumps	151
B.1	Introduction	151
B.2	Regenerative turbine pumps	151
B.3	Pitot tube pumps	156
B.4	Vortex pumps.	162
B.5	Screw centrifugal pump.	164
B.6	High-speed pumps	167
B.7	Vertically suspended sump pumps	170
Appendix C	Materials	179
C.1	Materials of construction	179
Appendix D	Seals	186
D.1	Seals	186
D.2	Shaft seals.	186
D.3	Bearing housing sealing	193
Appendix E	Bearings	197
E.1	Introduction	197
E.2	Bearings	197

E.3	Bearing life.	203
E.4	Lubricant life	206
E.5	Handling and installation damage	206
E.6	Shipping damage.	207
E.7	Minimum loading requirements	207
E.8	Cage fractures	207
E.9	Electric arcing	207
E.10	Sleeve bearing life	207
Appendix F	Lubrications systems.	208
F.1	Lubricant types	208
F.2	Quantity and quality of lubrication	209
Appendix G	Couplings.	217
G.1	Types of couplings.	217
G.2	Speed limitations	221
G.3	Equipment alignment.	221
Appendix H	Baseplates and foundations	222
H.1	Introduction	222
H.2	Seismic analysis	222
H.3	Foundation and anchorage for horizontal pumps	223
H.4	Baseplates – introduction	224
H.5	Foundation and anchorage for vertical pumps	239
H.6	Mounting plate (integral to discharge head)	240
Appendix I	Drivers	242
I.1	Introduction	242
I.2	Electric motors.	242
I.3	Engines	255
I.4	Steam turbine	263
I.5	Gears.	263
I.6	Deceleration devices	263
Appendix J	Monitoring and controls.	264
J.1	Introduction	264
J.2	Monitoring frequency.	264
J.3	Control limits	264
J.4	Appendix contents ANSI/HI 9.6.5	265
Appendix K	Index	267

Figures

14.3.2 — Overhung pump types and classifications 5

14.3.2.1.1a — OH0 pump 5

14.3.2.1.1b — OH1 pump 6

14.3.2.1.1c — OH1h pump 6

14.3.2.1.1d — OH2 pump 6

14.3.2.1.1e — OH3 pump 6

14.3.2.1.1f — OH4 pump 7

14.3.2.1.1g — OH5 pump 7

14.3.2.1.1h — OH5g pump 7

14.3.2.1.1i — OH6 pump 8

14.3.2.1.1j — OH7 pump 8

14.3.2.1.1k — OH7h pump 8

14.3.2.1.1l — OH8, OH8b pumps 9

14.3.2.1.1.1a — OH1i pump 9

14.3.2.1.1.1b — OH2i pump 10

14.3.2.1.1.1c — OH3i pump 10

14.3.2.1.1.1d — OH4i pump 10

14.3.2.1.1.1e — OH5i pump 11

14.3.2.1.1.1f — OH7i pump 11

14.3.2.1.1.1g — OH13i pump 12

14.3.2.1.1.2a — OH7j pump 12

14.3.2.1.1.2b — OH1j pump 12

14.3.2.1.1.2c — OH13j pump 12

14.3.2.1.2a — BB1 pump 13

14.3.2.1.2b — BB2 pump 13

14.3.2.1.2c — BB3 pump 13

14.3.2.1.2d — BB4 pump 14

14.3.2.1.2e — BB5 pump 14

14.3.2.1.3a — VS0 pump 14

14.3.2.1.3b — VS1 pump 15

14.3.2.1.3c — VS2 pump 15

14.3.2.1.3d — VS3 pump 15

14.3.2.1.3e — VS4 pump 16

14.3.2.1.3f — VS5 pump 16

14.3.2.1.3g — VS6 pump	16
14.3.2.1.3h — VS7 pump	17
14.3.2.1.3j — VS8 pump	17
14.3.2.1.1.1h — VS4i pump	17
14.3.2.1.1.1i — VS5i pump	18
14.3.2.1.4a — RT1 pump: overhung, close-coupled, side channel design	18
14.3.2.1.4b — RT2 pump: overhung, close-coupled, peripheral design	18
14.3.2.1.4c — RT3 pump: between-bearing, flexibly coupled, side channel design	19
14.3.2.1.4d — RT4 pump: between-bearing, flexibly coupled, peripheral design	19
14.3.2.1.5 — OHOd Pitot tube pump	19
14.3.2.1.6.1a — Closed coupled circulator CP1	20
14.3.2.1.6.1b — Closed coupled circulator CP2	20
14.3.2.1.6.2 — Flexibly coupled circulator pumps CP3	20
14.3.3.1.1 — n_s examples	21
14.3.3.2 — Simple system and pump performance curves	21
14.3.3.2.1 — Operating point	22
14.3.3.3.1 — Typical system curve shape	22
14.3.3.3.2 — Head versus rate of flow of various specific speed pumps	23
14.3.3.3.2.4a — Test curve with dip	24
14.3.3.3.2.4b — Dip occurring at trimming of Impeller	24
14.3.3.3.2.4c — Dip occurring with increase in pitch angle	24
14.3.3.3.2.5 — Dip with hysteresis	25
14.3.3.3.3 — Power versus rate of flow of various specific speed pumps	25
14.3.3.3.4 — Efficiency vs Rate of Flow for various specific speed pumps	26
14.3.3.3.5a — NPSH3 vs Rate of Flow for various specific speed pumps	26
14.3.3.3.5b — Datum elevation for various pump designs at eye of first-stage impeller	27
14.3.3.4a — Impeller with straight outside diameter	29
14.3.3.4b — Impeller with angled outside diameter	29
14.3.3.4c — Diameter reduction of a radial diffuser pump	29
14.3.3.4 — Vane overlap, radial flow impeller	31
14.3.3.4.1 — Mixed flow impeller trim	31
14.3.3.4.2a — Typical axial flow pump impeller chord angle	32
14.3.3.5.1a — Power consumption by discharge throttling	33
14.3.3.5.1b — Power consumption using a VSD	33
14.3.3.5.1c — Potential savings flat pump curve	34

14.3.3.5.1d — Potential savings steep pump curve	34
14.3.4.1.1.1a — Series operation	35
14.3.4.1.1.1b — Pumps operating in series	35
14.3.4.1.1.3 — Pumps operating in parallel	36
14.3.4.1.1.3.1 — H (<i>Q</i>) of different pumps in parallel operation	37
14.3.4.4.1 — Typical preferred operating region	38
14.3.4.8.1 — Two-phase pumping applications	46
14.3.4.8.2 — Effect of gas on pump performance	47
14.3.4.8.2.1a — Venting the eye of the impeller	48
14.3.4.8.2.1b — Top suction impeller	49
14.3.4.8.2.2a — Self-priming pump — construction industry	49
14.3.4.8.2.2b — Self-priming pump — chemical industry	50
14.3.4.8.2.2c — Helico-axial multiphase pump	50
14.3.4.10.5a — NPSHR reduction for pumps handling hydrocarbon liquids and high-temperature water (metric units)	55
14.3.4.10.5b — NPSHR reduction for pumps handling hydrocarbon liquids and high-temperature water (US customary units)	56
14.3.4.12 — Siphon system	58
14.3.4.13 — Inlet configurations	59
14.3.4.13.1 — Suction cans (barrels) with vents	60
14.3.4.14 — Typical self-priming installation	61
14.3.4.16a — Torque versus speed template (metric units)	67
14.3.4.16b — Torque versus speed template (US customary units)	68
14.3.4.17a — Torque curve	68
14.3.4.17b — Plotting torque versus speed (metric units)	71
14.3.4.17c — Plotting torque versus speed (US customary units)	72
14.3.4.18.1 — Axial pump with low system head	73
14.3.4.24.2a — Combining sound pressure	77
14.3.4.24.2b — dBA correction for impeller trim and percent BEP operation	77
14.3.5.1 — General impeller types	79
14.3.5.1.1.2 — Single suction impeller	80
14.3.5.1.1.3 — Single-stage, horizontal, double suction pump	80
14.3.5.2.1 — Enclosed impeller	81
14.3.5.2.2a — Open impeller	82
14.3.5.2.2b — Semi-open impeller with a full back shroud	82
14.3.5.2.2c — Semi-open impeller with a scalloped back shroud	82

14.3.5.2.3 — Typical Barske impeller	83
14.3.5.2.4 — Typical vortex impellers	83
14.3.5.2.5a — Inducer, end suction pump.	84
14.3.5.2.5b — Inducer, vertically suspended pump	84
14.3.5.3.1 — Single volute casing.	85
14.3.5.3.2 — Double volute casing	85
14.3.5.3.3 — Circular (concentric) casing	85
14.3.5.3.4 — Diffuser casing	86
14.3.5.3.7 — Typical bowl and stage casing	86
14.3.5.3.8 — Self-primer casing	87
14.3.5.3.9 — Double suction casing – horizontal split case	87
14.3.5.3.10 — Double suction casing – vertically suspended	88
14.3.5.4.1.1.1 — Approximate boundaries of radial thrust direction, single volute pump	89
14.3.5.4.2a — Radial thrust factor for single volute with various specific speeds	91
14.3.5.4.2b — Radial thrust factor for double volute with various specific speeds	91
14.3.5.4.2c — Sketch to illustrate D_2 and b_2	91
14.3.5.4.2d — Radial thrust factor for circular (concentric) casing typical for specific speed 20 (1000)	92
14.3.5.4.3.2.1 — Typical thrust profile	94
14.3.5.4.3.2.4 — Alternate thrust balancing methods	95
14.3.5.4.3.3.1a — Pressure distribution on enclosed impeller	96
14.3.5.4.3.3.1b — Enclosed impeller thrust factors for various specific speeds	98
14.3.5.4.3.3.1c — Average values of K_{Bal} , pressure reduction factor as a function of total balance hole area and rear wear ring clearance area	99
14.3.5.4.3.3.1d — Enclosed impeller with plain back shroud	99
14.3.5.4.3.3.1e — Impeller with back ring	102
14.3.5.4.3.3.2 — Cross section of semiopen impeller showing diameter locations.	107
14.3.5.4.3.3.3 — Axial impeller dimensions	108
14.3.5.4.3.3.4a — Enclosed impeller plain top shroud, vertically suspended pump	109
14.3.5.4.3.3.4b — Semiopen impeller, vertically suspended pump.	109
14.3.5.4.3.3.4c — Enclosed impeller with back ring and balance holes, vertically suspended pump.	110
14.3.5.4.3.3.4d — Enclosed end of shaft at suction	110
14.3.5.4.3.3.4e — Shaft sleeve through packing or mechanical seal	110
14.3.5.4.3.3.4f — Shaft sleeve through pressure breakdown bushing	111
14.3.5.4.3.3.5 — Experimental thrust coefficient $C^{1,2}$	112
14.3.5.4.3.3.7 — Axial thrust versus rate of flow curves	117

14.3.6.2.3a — Open lineshaft	121
14.3.6.2.3b — Enclosed lineshaft	121
14.3.6.3.2 — Cast discharge head	123
14.3.6.3.3 — Fabricated discharge head	123
14.3.6.3.4 — Subsurface discharge head	124
14.3.6.3.5 — Separate discharge types VS4 and VS5	125
14.3.6.3.9a — Internal seal arrangement	126
14.3.6.3.9b — Special seal arrangement	127
14.3.6.4.1.1 — Horizontal, between-bearings, axially split, multistage pump	128
14.3.6.4.2.1 — Overhung impeller.	129
14.3.6.4.2.2 — Between-bearings, single-stage pump	130
A.1 — Turbine characteristics	143
A.2 — Turbine performance.	145
A.3 — Dry-pit pump overhung flexibly coupled vertical end suction	146
A.4 — Dry-pit pump overhung, close-coupled, vertical end suction.	146
A.5 — Dry-pit pump overhung, foot-mounted, flexibly coupled, horizontal, end suction.	147
A.6 — Self-priming pump construction industry	149
A.7 — Self-priming pump chemical industry	150
B.1 — Regenerative turbine pump types and classifications.	151
B.2 — Regenerative turbine – impeller between bearings – two stage.	152
B.3 — Regenerative turbine flow path	153
B.4 — Regenerative turbine pump performance.	155
B.5 — Pitot tube pump	157
B.6 — Pitot tube pump rotating assembly (1)	158
B.7 — Pitot tube pump performance	161
B.8 — Vortex pump	163
B.9 — Screw centrifugal pump	164
B.10 — Screw centrifugal pump impeller	165
B.11 — High-solidity (left) versus low-solidity (right) straight radial vane impeller common in high-speed pumps	168
B.12 — Tailpipe and float control.	172
B.13 — Rate of flow versus minimum submergence.	173
B.14 — Schematic showing vaporproof/pressurized design	175
B.15 — Lubrication cleanliness.	176
B.16 — Nozzle loads	176

D.1 — Stuffing box without lantern ring	186
D.2 — Stuffing box with lantern ring	187
D.3 — Mechanical seal classification by arrangement	187
D.4 — Mechanical seal classification by design	188
D.5 — Mechanical seal classification by construction	188
D.6 — Seal chamber for external component seal	191
D.7 — Seal chamber for internal cartridge seal.	192
D.8 — Types of bearing housing shaft seals	193
D.9 — Lip seal	194
D.10 — Lip seal with secondary V-ring	195
D.11 — Bearing isolator.	196
E.1 — Cylindrical-type radial journal (sleeve) bearing.	201
E.2 — Pivot-shoe-type thrust bearing feed lubrication	201
E.3 — Pivot-shoe-type thrust bearing – complete with shaft-driven oil pump arranged for force-feed lubrication.	201
E.4 — Type OH arrangement	202
E.5 — Type BB arrangement.	202
E.6 — Vertical turbine pumps	203
F.1 — Oil bath lubrication system with constant level oiler	212
F.2 — Slinger ring installation using a bearing cartridge for ease of installation	213
F.3 — Typical oil mist bearing construction	214
F.4 — Dry-start running times at different shaft speeds when applied to PTFE bearings.	215
F.5 — Conversion example from enclosed line shaft vertical pump (left) to open line shaft (right)	216
G.1 — Head shaft coupling, rigid style, for hollow-shaft motor	220
G.2 — Flanged adjustable coupling, rigid style	221
G.3 — Flanged adjustable spacer coupling, rigid style	221
H.1 — Typical horizontal pump anchor bolt, leveling jack bolt, and grout design	224
H.2 — Grouted baseplate, fabricated steel	226
H.3 — Grouted baseplate, cast iron	227
H.4 — Nongrout baseplate	228
H.5 — Pregrouted baseplate	228
H.6 — Soleplate	229
H.7 — Freestanding baseplate	230
H.8 — Baseplate mounting springs with slide bearing	230
H.9 — ASME B73.1 pump and baseplate	231

H.10 — ISO pump and baseplate	231
H.11 — Formed polymer baseplate.	232
H.12 — Solid (polymer concrete) baseplate	233
H.13 — Pedestal baseplate.	233
H.14 — Oil pipeline skid type baseplate	234
H.15 — Offshore skid type baseplate	235
H.16 — Three-point mount type baseplate	235
H.17 — Underside of the three-point mount baseplate (O, P, and Q show the mounting points)	236
H.18 — Typical vertical pump anchor bolt, leveling jack bolt, and grout design	239
I.1 — Design A, B, C, and D for AC motors.	250
I.2 — Outline of an internal combustion engine.	262
Tables	
14.3.1.3 — Principal symbols	2
14.3.4.5.3 — Guidelines for minimum and maximum liquid temperature for gray iron, ductile iron, carbon steel, chrome steel, austenitic stainless and duplex stainless steel pumps (°C)	44
14.3.4.24.2 — Multistage pump sound pressure reductions	78
14.3.5.4.3.3.1— Distance ratio from the casing wall to the impeller shroud to maximum impeller diameter for various specific speeds.	98
14.3.6.2.1 — Consideration for threaded versus flanged column	120
C.1 — Typical pump materials of construction.	179
E.1 — Rolling element bearing types	198
E.2 — Sleeve bearings materials	200
G.1 — Shaft couplings - functions and parameters for selection.	217
H.1 — Functions of a baseplate and parameters for selection	225
I.1 — Common motor enclosures	245
I.2 — IP classification system	245
I.3 — Definitions of second numeral in the IP classification systems	246
I.4 — Drivers' functions and parameters for selection	249