



**Acoustics — Determination of sound
power levels of noise sources —
Guidelines for the use of basic standards**



AS 5332:2019

This Australian Standard® was prepared by EV-010, Acoustics Community Noise. It was approved on behalf of the Council of Standards Australia on 20 May 2019.

This Standard was published on 6 June 2019.

The following are represented on Committee EV-010:

- Association of Australasian Acoustical Consultants
- Australian Acoustical Society
- Austroads
- Bureau of Steel Manufacturers of Australia
- Department of Defence (Australian Government)
- Engineers Australia
- Master Builders Australia
- University of Sydney

This Standard was issued in draft form for comment as DR AS ISO 3741:2019.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76072 485 6



Acoustics — Determination of sound power levels of noise sources — Guidelines for the use of basic standards

First published as AS 5332:2019.

COPYRIGHT

© ISO 2019 — All rights reserved
© Standards Australia Limited 2019

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Australian members of the Joint Standards Australia/Standards New Zealand Committee EV-010, Acoustics Community Noise.

The objective of this Standard is to specify methods for determining the sound power level or sound energy level of a noise source from sound pressure levels measured in a reverberation test room. The sound power level (or, in the case of noise bursts or transient noise emission, the sound energy level) produced by the noise source, in frequency bands of width one-third-octave with mid-band frequencies from 100 Hz to 10 000 Hz, is calculated using those measurements, including corrections to allow for any differences between the meteorological conditions at the time and place of the test and those corresponding to a reference characteristic impedance. Measurement and calculation procedures are given for both a direct method and a comparison method of determining the sound power level and the sound energy level.

The methods in this Standard are suitable for all types of noise (e.g. steady, non-steady, fluctuating, isolated bursts of sound energy, etc.) as defined in ISO 12001.

This Standard is identical with, and has been reproduced from, ISO 3741:2010, *Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Precision methods for reverberation test rooms*.

As this document has been reproduced from an International Standard, the following applies:

- (a) In the source text “this International Standard” should read “this Australian Standard”.
- (b) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an ‘informative’ appendix or annex is only for information and guidance.

Contents

Preface	ii
Foreword	v
Introduction	vi
1 Scope	1
1.1 General	1
1.2 Types of noise and noise sources	1
1.3 Reverberation test room	1
1.4 Measurement uncertainty	1
2 Normative references	1
3 Terms and definitions	2
4 Reference meteorological conditions	6
5 Reverberation test room	6
5.1 General	6
5.2 Volume and shape of test room	6
5.3 Sound absorption of test room	7
5.4 Criteria for background noise	7
5.4.1 Relative criteria for background noise	7
5.4.2 Absolute criteria for background noise	8
5.4.3 Statement of non-conformity with background noise criteria	8
5.5 Atmospheric temperature, humidity and pressure	9
6 Instrumentation and measurement equipment	10
6.1 General	10
6.2 Calibration	10
7 Definition, location, installation, and operation of noise source under test	10
7.1 General	10
7.2 Auxiliary equipment	11
7.3 Noise source location	11
7.4 Installation and mounting conditions	11
7.5 Operation of source during test	12
8 Measurements in the reverberation test room	12
8.1 General	12
8.2 Initial location of the noise source under test	13
8.3 Microphone positions	13
8.4 Measurement of sound pressure levels	14
8.4.1 General	14
8.4.2 Further evaluation in a test room that is not qualified for the measurement of discrete-frequency components (see Annex D)	14
8.5 Measurement of single event time-integrated sound pressure levels	17
8.5.1 General	17
8.5.2 Further evaluation in a test room that is not qualified for the measurement of discrete-frequency components (see Annex D)	17
8.6 Measurement of sound pressure levels from the reference sound source for the comparison method	18
8.6.1 Location of the reference sound source	18
8.6.2 Sound pressure levels from the reference sound source	18
8.7 Measurement of reverberation time	18
8.8 Measurement of meteorological conditions	18
9 Determination of sound power levels and sound energy levels	18
9.1 Determination of sound power levels	18

9.1.1	Calculation of measured time-averaged sound pressure levels for multiple source positions.....	18
9.1.2	Corrections for background noise.....	19
9.1.3	Calculation of mean time-averaged sound pressure levels in the test room.....	20
9.1.4	Calculation of sound power levels using the equivalent absorption area of the room (direct method).....	21
9.1.5	Calculation of sound power levels using the reference sound source (comparison method).....	23
9.2	Determination of sound energy levels.....	23
9.2.1	Calculation of the mean of the measured single event time-integrated sound pressure levels for multiple sound emission events and for multiple source positions.....	23
9.2.2	Corrections for background noise.....	24
9.2.3	Calculation of mean single event time-integrated sound pressure levels in the test room.....	25
9.2.4	Calculation of sound energy levels using the equivalent absorption area of the room (direct method).....	26
9.2.5	Calculation of sound energy levels using the reference sound source (comparison method).....	26
9.3	A-weighted sound power level and sound energy level.....	27
10	Measurement uncertainty	27
10.1	Methodology.....	27
10.2	Determination of σ_{omc}	28
10.3	Determination of σ_{R0}	28
10.3.1	General.....	28
10.3.2	Round robin test.....	28
10.3.3	Modelling approach for σ_{R0}	29
10.4	Typical upper bound values of σ_{R0}	29
10.5	Total standard deviation σ_{tot} and expanded measurement uncertainty, U	30
11	Information to be recorded	30
11.1	General.....	30
11.2	Noise source under test.....	30
11.3	Test environment.....	31
11.4	Instrumentation.....	31
11.5	Acoustical data.....	31
12	Test report	32
Annex A	(informative) Guidelines for the design of reverberation test rooms	33
Annex B	(informative) Guidelines for the design of rotating diffusing vanes	35
Annex C	(normative) Reverberation test room qualification procedure for the measurement of broad-band sound	36
Annex D	(normative) Reverberation test room qualification procedure for the measurement of discrete-frequency components	38
Annex E	(informative) Extension of frequency range to frequencies below 100 Hz	43
Annex F	(normative) Calculation of octave band sound power levels and sound energy levels, A-weighted sound power levels and A-weighted sound energy levels from one-third-octave band levels	46
Annex G	(informative) Guidelines on the development of information on measurement uncertainty	49
Bibliography	61

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 3741 was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

This fourth edition cancels and replaces the third edition (ISO 3741:1999), which has been technically revised. It also incorporates the Technical Corrigendum ISO 3741:1999/Cor.1:2001.

Introduction

This International Standard is one of the series ISO 3740[2] to ISO 3747[8], which specify various methods for determining the sound power levels and sound energy levels of noise sources including machinery, equipment and their sub-assemblies. The selection of one of the methods from the series for use in a particular application depends on the purpose of the test to determine the sound power level or sound energy level and on the facilities available. General guidelines to assist in the selection are provided in ISO 3740[2]. ISO 3740[2] to ISO 3747[8] give only general principles regarding the operating and mounting conditions of the machinery or equipment for the purposes of the test. It is important that test codes be established for individual kinds of noise source, in order to give detailed requirements for mounting, loading, and operating conditions under which the sound power levels or sound energy levels are to be obtained.

The methods given in this International Standard require the source under test to be mounted in a reverberation test room having specified acoustical characteristics. The methods are then based on the premise that the sound power or sound energy of the source under test is directly proportional to the mean-square sound pressure averaged in space and time, and otherwise depends only on the acoustical and geometric properties of the room and on the physical constants of air.

For a source emitting sound in narrow bands of frequency or at discrete frequencies, a precise determination of the radiated sound power level or sound energy level in a reverberation test room requires greater effort than for a source emitting sound more evenly over a wide range of frequencies, because:

- a) the space- and time-averaged sound pressure along a short microphone path, or as determined with an array of a small number of microphones, is not always a good estimate of the space- or time-averaged mean-square pressure throughout the room;
- b) the sound power or sound energy radiated by the source is more strongly influenced by the normal modes of the room and by the position of the source within the room.

The increased measurement effort in the case of a source emitting narrow bands of sound or discrete tones consists of either the optimization and qualification of the test room or the use of a greater number of source locations and microphone positions (or increased path length for a moving microphone). The addition of low-frequency absorbers or the installation of rotating diffusers in the test room can help to reduce the measurement effort.

The methods specified in this International Standard permit the determination of the sound power level and the sound energy level in one-third-octave frequency bands, from which octave band data, A-weighted frequency data, and total unweighted sound can be computed.

This International Standard describes methods of accuracy grade 1 (precision grade) as defined in ISO 12001. The resulting sound power levels and sound energy levels include corrections to allow for any differences that might exist between the meteorological conditions under which the tests are conducted and reference meteorological conditions. For applications in reverberant environments where reduced accuracy is acceptable, reference can be made to ISO 3743-1[3], ISO 3743-2[4] or ISO 3747[8].

Australian Standard®

Acoustics — Determination of sound power levels of noise sources — Guidelines for the use of basic standards

1 Scope

1.1 General

This International Standard specifies methods for determining the sound power level or sound energy level of a noise source from sound pressure levels measured in a reverberation test room. The sound power level (or, in the case of noise bursts or transient noise emission, the sound energy level) produced by the noise source, in frequency bands of width one-third-octave, is calculated using those measurements, including corrections to allow for any differences between the meteorological conditions at the time and place of the test and those corresponding to a reference characteristic impedance. Measurement and calculation procedures are given for both a direct method and a comparison method of determining the sound power level and the sound energy level.

In general, the frequency range of interest includes the one-third-octave bands with mid-band frequencies from 100 Hz to 10 000 Hz. Guidelines for the application of the specified methods over an extended frequency range in respect to lower frequencies are given in [Annex E](#). This International Standard is not applicable to frequency ranges above the 10 000 Hz one-third-octave band.

NOTE For higher frequencies, the methods specified in ISO 9295 can be used.

1.2 Types of noise and noise sources

The methods specified in this International Standard are suitable for all types of noise (steady, non-steady, fluctuating, isolated bursts of sound energy, etc.) defined in ISO 12001.

The noise source under test can be a device, machine, component or sub-assembly. This International Standard is applicable to noise sources with a volume not greater than 2 % of the volume of the reverberation test room. For a source with a volume greater than 2 % of the volume of the test room, it is possible that the achievement of results as defined in ISO 12001:1996, accuracy grade 1 (precision grade) is not feasible.

NOTE In specific cases, the source volume can be increased to a maximum of 5 % of the room volume. In such cases, the relevant noise test code indicates the possible consequences on the measurement uncertainty.

1.3 Reverberation test room

The test rooms that are applicable for measurements made in accordance with this International Standard are reverberation test rooms meeting specified requirements (see [Clause 5](#)).

1.4 Measurement uncertainty

Information is given on the uncertainty of the sound power levels and sound energy levels determined in accordance with this International Standard, for measurements made in specific frequency bands and for the A-weighted sum of all frequency bands. The uncertainty conforms to ISO 12001:1996, accuracy grade 1 (precision grade).

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies