

IN-LB

Inch-Pound Units

SI

International System of Units

Guide to the Selection and Use of Hydraulic Cements

Reported by ACI Committee 225

ACI 225R-19



American Concrete Institute
Always advancing



Guide to the Selection and Use of Hydraulic Cements

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, through electronic subscription, or reprint, and may be obtained by contacting ACI.

ACI codes, specifications, and practices are made available in the ACI Collection of Concrete Codes, Specifications, and Practices. The online subscription to the ACI Collection is always updated, and includes current and historical versions of ACI's codes and specifications (in both inch-pound and SI units) plus new titles as they are published. The ACI Collection is also available as an eight-volume set of books and a USB drive.

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
Phone: +1.248.848.3700
Fax: +1.248.848.3701

Guide to the Selection and Use of Hydraulic Cements

Reported by ACI Committee 225

Kenneth G. Kazanis, Chair

Mark R. Lukkarila, Secretary

Gregory S. Barger
Glen E. Bollin
Michael M. Chehab
Marwan A. Daye
Jonathan E. Dongell
Michael S. Hammer

Brett A. Harris
Geoffrey Hichborn
R. Doug Hooton
Kimberly E. Kurtis
Kirk L. McDonald
Moncef L. Nehdi

James S. Pierce
Nicholas J. Popoff
Oscar Tavares
Paul D. Tennis
James I. Turici Jr.
Jay E. Whitt

Stephen D. Wilcox
Consulting Members
Larry Rowland
Bryce P. Simons

*The committee acknowledges B. Blair and M. D. A. Thomas for their contributions in the development of this guide.

This guide covers the influence of cement on the properties of concrete, summarizing the composition and availability of commercial hydraulic cements and the factors affecting their performance in concrete. Cement is the most active component of concrete and usually has the greatest unit cost; therefore, its selection and proper use is imperative to attaining the desired balance of properties and cost for a particular concrete mixture. Selection should include consideration of the cement properties in relation to the required performance of the concrete. It includes a discussion of cement types, a brief review of cement chemistry, the influences of chemical admixtures and supplementary cementitious materials, as well as the effects of the environment on cement performance and reviews of the sustainability aspects for the use and manufacture of portland cement. Cement storage, delivery, sampling, and testing of hydraulic cements for conformance to specifications are addressed. Users will learn to recognize when a readily available, general-purpose cement will perform satisfactorily or when conditions require selection of a cement that meets additional requirements.

Keywords: admixture; blended cement; calcium-aluminate cement; cement storage; cement types; chemical analysis; hydraulic cement; physical properties; portland cement; pozzolan; slag cement; supplementary cementitious materials; sustainability.

ACI Committee Reports, Guides, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

CONTENTS

CHAPTER 1—INTRODUCTION AND SCOPE, p. 2

- 1.1—Introduction, p. 2
- 1.2—Scope, p. 2

CHAPTER 2—NOTATION AND DEFINITIONS, p. 3

- 2.1—Notation, p. 3
- 2.2—Definitions, p. 3

CHAPTER 3—CEMENT TYPES, AVAILABILITY, AND SELECTION, p. 3

- 3.1—Portland and blended hydraulic cements, p. 3
- 3.2—Special-purpose cement, p. 4
- 3.3—Research and development, p. 6
- 3.4—Rational approach to selection, p. 6

CHAPTER 4—CEMENT CHEMISTRY, p. 8

- 4.1—Portland cement, p. 8
- 4.2—Blended hydraulic cement, p. 10
- 4.3—Shrinkage-compensating expansive cement, p. 12
- 4.4—Calcium-aluminate cement, p. 13

CHAPTER 5—INFLUENCE OF CHEMICAL ADMIXTURES, POZZOLANS, AND SLAG CEMENTS ON CEMENTITIOUS SYSTEMS, p. 13

- 5.1—Air-entraining admixtures, p. 13
- 5.2—Other chemical admixtures, p. 14
- 5.3—Pozzolans, p. 15
- 5.4—Slag cements, p. 16

ACI 225R-19 supersedes ACI 225R-16 and was adopted and published August 2019.

Copyright © 2019, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

CHAPTER 6—INFLUENCE OF ENVIRONMENTAL CONDITIONS ON THE HYDRATION OF CEMENTS, p. 16

- 6.1—Water requirements, p. 16
- 6.2—Temperature effects, p. 16
- 6.3—Composition, p. 16

CHAPTER 7—INFLUENCE OF CEMENT ON CONCRETE PROPERTIES, p. 16

- 7.1—Thermal cracking, p. 17
- 7.2—Placeability, p. 17
- 7.3—Strength, p. 18
- 7.4—Volume stability, p. 19
- 7.5—Elastic properties, p. 20
- 7.6—Creep, p. 20
- 7.7—Permeability, p. 20
- 7.8—Corrosion of embedded steel, p. 21
- 7.9—Resistance to freezing and thawing, p. 22
- 7.10—Resistance to chemical attack, p. 22
- 7.11—Resistance to high temperatures, p. 22
- 7.12—Aggregate reactions in concrete, p. 22
- 7.13—Color, p. 23

CHAPTER 8—CEMENT STORAGE AND DELIVERY, p. 24

- 8.1—Storage, p. 24
- 8.2—Pack set (sticky cement), p. 24
- 8.3—Delivery, p. 24
- 8.4—Contamination and handling, p. 24
- 8.5—Worker protection, p. 25

CHAPTER 9—SAMPLING AND TESTING HYDRAULIC CEMENTS FOR CONFORMANCE TO SPECIFICATIONS, p. 25

- 9.1—Cement mill test reports, p. 25
- 9.2—Sealed silos, p. 27
- 9.3—Cement certification, p. 27
- 9.4—Quality management, p. 28

CHAPTER 10—SUSTAINABILITY ASPECTS OF HYDRAULIC CEMENTS, p. 29

- 10.1—Hydraulic cements, p. 29
- 10.2—Energy consumption, p. 30
- 10.3—Use of SCMs as replacement for portland cement, p. 30
- 10.4—Use of cement in concrete, p. 30
- 10.5—Recycled raw materials as raw feed in the manufacture of portland cement, p. 30
- 10.6—Alternate fuels, p. 30
- 10.7—Combustion emissions, p. 31
- 10.8—Recent progress and strategy, p. 31

CHAPTER 11—REFERENCES, p. 31

Authored documents, p. 33

APPENDIX A—CALCIUM-ALUMINATE CEMENTS, p. 36

- A.1—Manufacture and properties, p. 36

A.2—Influences of admixtures and supplementary cementitious materials, p. 37

A.3—Influence of environment, p. 37

A.4—Heat of hydration, p. 37

A.5—Setting characteristics, p. 37

A.6—Strength, p. 37

A.7—Resistance to chemical attack, p. 38

A.8—Resistance to high temperatures, p. 38

APPENDIX B—MANUFACTURER'S CERTIFICATION (MILL TEST REPORT), p. 39

CHAPTER 1—INTRODUCTION AND SCOPE

1.1—Introduction

This guide assists specifiers and designers in choosing appropriate cement for specified concrete applications. Although hydraulic cements are only one ingredient of a concrete mixture, they are the active ingredient and, therefore, play a key role in the long-term viability of the structure, floor, or pavement. Cement choice depends on many variables, such as the service conditions for which the concrete is designed, properties of other materials used in the mixture, or the performance characteristics of the concrete required during or shortly after placement.

Cement paste is the binder in concrete or mortar that holds the fine aggregate, coarse aggregate, or other constituents together in a hardened mass. The term “hydraulic” in this guide refers to the basic mechanism by which the hardening of the cement takes place—a chemical reaction between the cement and water. The term also differentiates hydraulic cement from binder systems that are based on other hardening mechanisms, as hydraulic cements can harden underwater.

Concrete properties depend on the quantities and qualities of its constituents. Because cement is the most active component of concrete and usually has the greatest unit cost, its selection and proper use are fundamental in obtaining the most economical balance of properties desired for a particular concrete mixture. Most cements will provide adequate levels of strength and durability for general use. Some provide higher levels of certain properties than are needed in specific applications.

1.2—Scope

This guide summarizes information about the composition, availability, and factors affecting the performance of commercial hydraulic cements. It also provides information regarding:

- a) Cement selection, whether a cement is readily available, and if conditions require a general-purpose cement or a special cement
- b) How the chemical and physical characteristics of a cement can affect certain properties of concrete
- c) How interaction of cements with various additives, admixtures, and mixture designs can affect concrete

This guide deals with hydraulic cements manufactured in conformance with ASTM International, American Association