

DETAIL SPECIFICATION

HOSES, RUBBER, PETROLEUM-BASED FUELS AND WATER SERVICES,
DISCHARGE-ONLY, SMOOTH BORE, LIGHTWEIGHT BUOYANT TYPE

This specification is approved for use by the Naval Sea Systems Command and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers lightweight buoyant type, smooth bore, petroleum-based fuels and discharge-only water service rubber hoses. Water services include both boiler feed water and potable water.

1.2 Classification. Hoses covered by this specification are of the following sizes and types (see 6.2).

1.2.1 Hose size. The hose size (inside diameter) is identified by two digits (see [table I](#)).

TABLE I. Hose size.

Size code number	Inside diameter (inches)
25	2½
40	4
60	6
70	7

1.2.2 Hose type. Hose type is identified by a single capital letter (see [table II](#)).

TABLE II. Hose type.

Type code letter	Type	Sizes
A	Alongside fueling	40, 60, and 70
B	Astern fueling	25 and 60
C	Alongside fueling or water transfer	25

Comments, suggestions, or questions on this document should be addressed to Commander, Naval Sea Systems Command, ATTN: SEA 05S, 1333 Isaac Hull Avenue, SE, Stop 5160, Washington Navy Yard DC 20376-5160 or emailed to CommandStandards@navy.mil, with the subject line "Document Comment". Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at <https://assist.dla.mil>.