



ANSI C18.1M, Part 2-2019

American National
Standard for Portable
Primary Cells and
Batteries with Aqueous
Electrolyte—Safety
Standard



National Electrical Manufacturers Association
1300 North 17th Street, Suite 900 • Rosslyn, VA 22209
www.NEMA.org





ANSI C18.1M, Part 2-2019

*American National Standard for
Portable Primary Cells and Batteries with
Aqueous Electrolyte—Safety Standard*

Secretariat:

National Electrical Manufacturers Association

Approved: May 10, 2019

American National Standards Institute

NOTICE AND DISCLAIMER

The information in this publication was considered technically sound by the consensus of persons engaged in the development and approval of the document at the time it was developed. Consensus does not necessarily mean that there is unanimous agreement among every person participating in the development of this document.

ANSI Standards and guideline publications, of which the document contained herein is one, are developed through a voluntary consensus Standards development process. This process brings together volunteers and/or seeks out the views of persons who have an interest in the topic covered by this publication. While NEMA administers the process to promote fairness in the development of consensus, it does not write the document, and it does not independently test, evaluate, or verify the accuracy or completeness of any information or the soundness of any judgments contained in its Standards and guideline publications.

NEMA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential, or compensatory, directly or indirectly resulting from the publication, use of, application, or reliance on this document. NEMA disclaims and makes no guaranty or warranty, expressed or implied, as to the accuracy or completeness of any information published herein, and disclaims and makes no warranty that the information in this document will fulfill any of your particular purposes or needs. NEMA does not undertake to guarantee the performance of any individual manufacturer or seller's products or services by virtue of this Standard or guide.

In publishing and making this document available, NEMA is not undertaking to render professional or other services for or on behalf of any person or entity, nor is NEMA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances. Information and other Standards on the topic covered by this publication may be available from other sources, which the user may wish to consult for additional views or information not covered by this publication.

NEMA has no power, nor does it undertake to police or enforce compliance with the contents of this document. NEMA does not certify, test, or inspect products, designs, or installations for safety or health purposes. Any certification or other statement of compliance with any health- or safety-related information in this document shall not be attributable to NEMA and is solely the responsibility of the certifier or maker of the statement.

AMERICAN NATIONAL STANDARD

Approval of an American National Standard requires verification by The American National Standards Institute, Inc. (ANSI) that the requirements for due process, consensus, and other criteria for approval have been met by the Standards developer. An American National Standard implies a consensus of those substantially concerned with its scope and provisions. Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly, and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered and that a concerted effort be made toward their resolution.

The existence of an American National Standard does not in any respect preclude anyone, whether s/he has approved the Standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not conforming to the Standards. It is intended as a guide to aid the manufacturer, the consumer, and the general public.

The American National Standards Institute, Inc., does not develop Standards and will in no circumstances give an interpretation of any American National Standard. Moreover, no person shall have the right or authority to issue an interpretation of an American National Standard in the name of the American National Standards Institute, Inc. Requests for interpretations should be addressed to the secretariat or sponsor whose name appears on this title page.

CAUTION NOTICE: This American National Standard may be revised or withdrawn at any time. The procedures of the American National Standards Institute, Inc. require that action be taken periodically to reaffirm, revise, or withdraw this Standard. Purchasers of American National Standards may receive current information on all Standards by calling or writing the American National Standards Institute, Inc.

Published by

National Electrical Manufacturers Association
1300 North 17th Street, Suite 900
Rosslyn, VA 22209

© 2019 National Electrical Manufacturers Association

All rights, including translation into other languages, reserved under the Universal Copyright Convention, the Berne Convention for the Protection of Literary and Artistic Works, and the International and Pan American copyright conventions.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Printed in the United States of America

< This page intentionally left blank. >

CONTENTS

Foreword	v
1 Introduction	1
2 Scope	1
3 Normative References	1
4 Definitions	1
5 Requirements for Safety	3
5.1 Design.....	3
5.1.1 General.....	3
5.1.2 Battery Case.....	3
5.1.3 Venting	3
5.1.4 Temperature/Current management.....	4
5.1.5 Multi-Cell Molded Plastic Battery Enclosure	4
5.1.6 Quality Assurance Plan	4
6 Sampling for Type Approval.....	5
7 Testing and Compliance (Verification)	5
7.1 General	5
7.1.1 Test Temperature	5
7.2 Pretest Dimensions, Voltage, and Insulation Resistance Test Requirements	5
7.2.1 Dimensions.....	5
7.2.2 Open Circuit Voltage	5
7.2.3 Closed Circuit Voltage.....	5
7.2.4 Insulation Resistance Test	5
7.3 Intended Use Simulation Tests.....	6
7.3.1 Test A: Partial Use	6
7.3.2 Test B: Vibration	7
7.3.3 Test C: Thermal Shock.....	8
7.3.4 Test D: Mechanical Shock.....	8
7.4 Reasonably Foreseeable Misuse Tests	9
7.4.1 Test E: Incorrect Installation.....	9
7.4.2 Test F: External Short-Circuit.....	10
7.4.3 Test G: Free Fall (User Drop).....	11
7.4.4 Test H: Over-Discharge.....	12
7.4.5 Test I: Crush	13
7.5 Design Consideration Tests	14
7.5.1 Test J: Thermal Abuse	14
7.5.2 Test K: Mold Stress	15
8 Information for Safety	18
9 Instructions for Use	19
10 Marking.....	19
10.1 General	19
10.2 Small Size Batteries	19

Annex A Guidance for Device Designers	20
Annex B Guidance for Packaging, Handling, and Transportation.....	27
Annex C Compliance checklist.....	29
Annex D Maximum temperature during usage	30
Annex E Bibliography.....	31

Tables

Table 1 Vibration Test Sequence.....	7
Table 2 Shock Pulse	9
Table 3 Tests Required for Single Cell Batteries	16
Table 4 Test References.....	16
Table 5 Tests Required for Multi-Cell Batteries	17
Table A.1 Suggested Minimum Diameters for Coil Spring Wire	26
Table C.1 Compliance Checklist.....	29
Table D.1 Recommended maximum temperatures	30

Figures

Figure 1 Ingestion Gauge.....	3
Figure 2 Circuit Diagram for Test E: Incorrect Installation	10
Figure 3 Circuit Diagram for Test F: External Short-Circuit	11
Figure 4 Circuit Diagram for Test H: Over-Discharge.....	13
Figure 5 Example of Series Connection with One Battery Reversed	20
Figure 6 Positive Contact, Contact Recessed Between Ribs	22
Figure 7 Positive Contact, Recessed Aperture	22
Figure 8 Negative Contact, Contact is “U” Shaped.....	23
Figure 9 Battery Orientation Examples	24
Figure 10A Example of a Short Circuit—A Switch is Piercing the Battery Insulating Jacket.....	24
Figure 10B Example of Insulation to Prevent Short Circuit—Insulating Material Positioned as Shown Prevents the Switch from Damaging the Battery Jacket.....	25
Figure 11 Examples Showing Distorted Springs.....	25
Figure 12 One Example of Protected Insertion Design	26

Foreword (This foreword is not part of American National Standard ANSI C18.1M, Part 2-2019)

In 1912, a committee of the American Electrochemical Society recommended standard methods to be used in testing dry cells. Their recommendations were followed five years later when the National Bureau of Standards (currently the National Institute of Standards and Testing) prepared specifications that included cell sizes, the arrangement of cells within batteries, service tests, and required performance.

The need for continued revision to the specification led to the authorization, by the American Engineering Standards Committee, of a permanent sectional committee on dry cells. This committee, C18, representing battery users, manufacturers, and government agencies, has remained active since that time. Committee C18 prepared ANSI Standard C18.1M, Part 2, upon which this document is originally based under the sponsorship of the National Electrical Manufacturers Association (NEMA).

ANSI Standard C18.1M, Part 2, was created in parallel with the International Electrotechnical Commission (IEC) project to develop a product safety Standard for primary batteries with aqueous electrolyte (IEC Publication 60086-5). This revision was undertaken to provide a new over-discharge test for the 13-25 batteries and revise the criteria in select tests.

Suggestions for the improvement of this Standard are welcome. They should be sent to the National Electrical Manufacturers Association, 1300 N. 17th Street, Suite 900, Rosslyn, VA 22209, Attention: Secretary ANSI ASC C18.

This Standard was processed and approved for submittal to ANSI by the Accredited Standards Committee C18 on Portable Cells and Batteries. Committee approval of the Standard does not necessarily imply that all committee Members voted for its approval. At the time it approved this Standard, the C18 committee had the following Members:

Steven Wicelinski, Chairperson
 Marcus Boolish, Vice Chairperson
 Khaled Masri, Secretary

<u>Organization Represented:</u>	<u>Name of Representative(s):</u>		<u>Voting Status:</u>
Batteries Plus Bulbs	Heather	Peterson	Voting
	Jason	Fladhammer	Alt. Voting
Bureau Veritas Consumer Product Services	David	Grandin	Voting
Consumer Product Integrity Consulting, LLC	Robert	Coughlin	Voting
Duracell, Inc.	Steven	Wicelinski	Voting
	Christopher	Brown	Alt. Voting
Energizer Brands, LLC	Marcus	Boolish	Voting
	Carin	Stuart	Alt. Voting
Fisher-Price	Douglas	Golde	Voting
Intertek	Thomas	O'Hara	Voting
	Rich	Byczek	Alt. Voting
Kimberly-Clark Corporation	Cary	Costello	Voting
Micropower Battery Co.	Jeff	Becker	Voting
Panasonic Corporation of North America	Charles	Monahan	Voting
SGS	Rodney	Grimes	Voting
Spectrum Brands, Inc.	John	Hadley	Voting

UL LLC	Andy	Roszkowski	Alt. Voting
ZPower, LLC	Laurie	Florence	Voting
	Jeff	Ortega	Voting
	Tim	Powers	Alt. Voting

The Members of Subcommittee C18-6 on Safety Standards who contributed to the development of this Standard are:

Carin Stuart, Chairperson
Tom O'Hara, Vice-Chairperson
Khaled Masri, Secretary

Name		Organization
Yasuo	Akai	FDK CORPORATION
Larry	Albert	Stanley Black & Decker
Akinrori	Awano	Battery Association of Japan
Jeff	Becker	Micropower Battery Co.
Zekarias	Bekele	CSA Group
Marcus	Booish	Energizer Brands, LLC
Christopher	Brown	Duracell, Inc.
Rich	Byczek	Intertek
Denis	Carpenter	Spectrum Brands, Inc.
Cary	Costello	Kimberly-Clark Corporation
Robert	Coughlin	Consumer Product Integrity Consulting, LLC
Raju	Desai	Apple Inc.
Sharon	Ensminger	Sy Kessler Sales, Inc.
Melissa	Fensterstock	Landsdowne Labs
Jacqueline	Ferrante	U. S. Consumer Product Safety Commission
Jeff	Fischer	Spectrum Brands, Inc.
Jason	Fladhammer	Batteries Plus Bulbs
Laurie	Florence	UL LLC
Akio	Furukawa	Panasonic Automotive & Industrial Systems Company
Douglas	Golde	Fisher-Price
David	Grandin	Bureau Veritas Consumer Product Services
Rodney	Grimes	SGS North America
John	Hadley	Energizer Brands, LLC
Ray	Iveson	Duracell, Inc.
Judith	Jeevarajan	Underwriters Laboratories Inc.
Henry	Kessler	Sy Kessler Sales, Inc.
Roland	Klinger	RENATA
Jody	Leber	CSA Group
Douglas	Lee	U. S. Consumer Product Safety Commission
Khaled	Masri	NEMA
Charles	Monahan	Panasonic Corporation of North America

Thomas	O'Hara	Intertek
Jeff	Ortega	ZPower, LLC
Heather	Peterson	Batteries Plus Bulbs
Tim	Powers	ZPower, LLC
Andy	Roszkowski	Spectrum Brands, Inc.
John	Rotondo	Duracell, Inc.
Hirotaaka	Shima	Hitachi Maxell, Ltd.
Carin	Stuart	Energizer Brands, LLC
Yoshiki	Terao	Panasonic
Hirohito	Teraoka	FDK CORPORATION
Kelly	Tsudama	Google
Steven	Wicelinski	Duracell, Inc.

1 Introduction

The concept of safety is closely related to safeguarding the integrity of people and property. This Standard defines performance requirements for primary batteries with aqueous electrolyte to ensure their safe operation under normal use and reasonably foreseeable misuse.

Safety is a balance between freedom from risk of harm and other demands to be met by the product. There can be no absolute safety. Even at the highest level of safety, the product can only be relatively safe. In this respect, decision-making is based on risk evaluation and safety judgment.

As safety will pose different problems, it is impossible to provide a set of precise provisions and recommendations that will apply in every case. This may be particularly true for button-type batteries. However, when following a judicious “use when applicable” basis this Standards publication will provide reasonably consistent standards for safety.

2 Scope

This American National Standard specifies tests and requirements for portable primary batteries with aqueous electrolyte and zinc anode (non-lithium) to ensure their safe operation under normal use and reasonably foreseeable misuse. For reference, the chemical systems standardized in ANSI C18.1M, Part 1 are:

- a. Carbon Zinc (Leclanché and Zinc Chloride types);
- b. Alkaline Manganese Dioxide;
- c. Silver Oxide;
- d. Zinc air;
- e. Nickel Oxy-Hydroxide.

3 Normative References

The following Standards contain provisions which, through reference in this text, constitute provisions of this American National Standard. At the time of publication, the editions indicated were valid. All Standards are subject to revision, and parties to agreements based on this American National Standard are encouraged to investigate the possibility of applying the most recent editions of the Standards indicated below.

ANSI C18.1M, Part 1, *American National Standard for Portable Primary Cells and Batteries with Aqueous Electrolyte—General and Specifications*

4 Definitions

For the purposes of this American National Standard, the following definitions apply:

battery: One or more cells, including case, terminals, and marking.

battery, button: Small round battery, where the overall height is less than the diameter.

battery or cell, cylindrical: A round cell or battery in which the overall height is equal to or greater than the diameter.

battery, portable: A battery that is easily hand-carried.

battery, prismatic: A battery with non-round geometry.

cell, primary: A source of electrical energy obtained by the direct conversion of chemical energy that is not designed to be charged by any other electrical source.