

FINAL VERSION

VERSION FINALE

Edison screw lampholders

Douilles à vis edison pour lampes



CONTENTS

FOREWORD	4
INTRODUCTION to Amendment 2	6
1 Scope	7
2 Normative references	8
3 Terms and definitions	9
4 General requirement.....	14
5 General conditions for tests	14
6 Standard ratings	15
7 Classification	16
8 Marking	17
9 Dimensions.....	19
10 Protection against electric shock	22
11 Terminals	24
12 Provision for earthing	28
13 Construction	29
14 Switched lampholders.....	34
15 Moisture resistance, insulation resistance and electric strength	35
16 Mechanical strength	37
17 Screws, current-carrying parts and connections.....	41
18 Creepage distances and clearances	43
19 Normal operation	48
20 General resistance to heat.....	49
21 Resistance to heat, fire and tracking.....	52
22 Resistance to excessive residual stresses (season cracking) and to rusting	54
Annex A (normative) Season cracking/corrosion test	75
Annex B (informative) Guidance for requirements in IEC 61058-1 applicable to switches in lampholders (see 14.2)	77
Annex C (informative) Guidance for special requirements in appliance standards – Household and similar electrical appliances	79
Annex D (informative) Clauses containing new or more stringent requirements with respect to the previous edition	81
Bibliography.....	82
Figure 1a –Nipple thread for lampholders: metric thread. Basic profile and design profile for the nut and for the screw.....	55
Figure 1b –Nipple thread for lampholders: ISO standard pipe thread. Basic profile and design profile for the nut and for the screw	56
Figure 2a – Gauges for metric thread for nipples	57
Figure 2b – Gauges for ISO standard pipe thread for nipples	58
Figure 3 – Gauge for holes for backplate lampholder screws	59
Figure 4 – Normal operation test apparatus	60
Figure 5 – Test caps for the test of Clause 18.....	61
Figure 6 – Torque apparatus.....	62

Figure 7 – Tumbling barrel	63
Figure 8 – Impact-test apparatus	64
Figure 9 – Pressure apparatus	65
Figure 10 – Ball-pressure test apparatus.....	65
Figure 11 – Test cap for the tests of 15.4 and 20.3	66
Figure 12 – Bending apparatus	67
Figure 13 – Test cap A and test cap B for lampholders E14 (2 of 2)	69
Figure 14 – Test cap for lampholders E27	70
Figure 15 – Test cap for lampholders E40.....	71
Figure 16 – Standard test finger (according to IEC 60529).....	72
Figure 17 – Clarification of some definitions.....	73
Figure 18 – Preparation of specimens for the needle-flame test of 21.4	74
Table 1 – Thickness of screw shells and contacts	20
Table 2 – Minimum effective screw lengths	21
Table 3 – Dimensions of threaded entries and set screws	22
Table 4 – Minimum dimensions of pillar-type terminals	26
Table 5 – Minimum dimensions of screw-type terminals	26
Table 6 – Pull and torque values	32
Table 7 – Insertion torque	34
Table 8 – Minimum and maximum removal torques	34
Table 9 – Test cap dimensions	38
Table 10 – Heights of fall	39
Table 11 – Maximum deformation values	41
Table 12 – Torque values	42
Table 13a – Minimum distances for AC sinusoidal voltages up to 30 kHz – Impulse withstand category II.....	45
Table 13b – Minimum distances for AC sinusoidal voltages up to 30 kHz – Impulse withstand category III.....	46
Table 14 – Minimum distances for ignition pulse voltages or equivalent peak voltages Up	48
Table 15 – Heating cabinet temperatures.....	51
Table A.1 – pH adjustment.....	75

INTERNATIONAL ELECTROTECHNICAL COMMISSION

EDISON SCREW LAMPHOLDERS**FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

DISCLAIMER

This Consolidated version is not an official IEC Standard and has been prepared for user convenience. Only the current versions of the standard and its amendment(s) are to be considered the official documents.

This Consolidated version of IEC 60238 bears the edition number 9.1. It consists of the ninth edition (2016-07) [documents 34B/1852/FDIS and 34B/1860/RVD], and its amendment 1 (2017-01) [documents 34B/1887/FDIS and 34B/1892/RVD] and its corrigendum (2018-01), and its amendment 2 (2020-01) [documents 34B/2029/CDV and 34B/2040A/RVC]. The technical content is identical to the base edition and its amendments.

This Final version does not show where the technical content is modified by amendments 1 and 2. A separate Redline version with all changes highlighted is available in this publication.

International Standard IEC 60238 has been prepared by subcommittee 34B: Lamp caps and holders, of IEC technical committee 34: Lamps and related equipment.

This ninth edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) Addition of a pull test for certain E5 and E10 lampholders.
- b) Annex D listing amended requirements/clauses which require products to be retested.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

In this standard, the following print types are used:

– *compliance statements: in italic type.*

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION to Amendment 2

Some changes and corrections needed for IEC 60238 became obvious during the work relating to the consolidated Edition 9.1 of IEC 60238.

Change 1:

Actual lamp holder safety standards require a ball pressure test in line with IEC 60695-10-2 in sections "Resistance to heat, fire and tracking". Within this test there is an alternative depth indentation method described for the calculation of the indentation diameter.

This alternative calculation option was removed from the latest edition of IEC 60695-10-2 dated 2014 and during its meeting held in Sydney in 2018, SC 34B/WG1 agreed to delete the alternative method as well from IEC 60238.

Change 2:

Based on IEC 60664-1:2007, 4.8.1.5 "Non tracking materials":

"For glass, ceramics or other inorganic insulating materials which do not track, creepage distances need not be greater than their associated clearance for the purpose of insulation coordination. The dimensions of Table F.2 for inhomogeneous field conditions are appropriate."

This is not completely reflected in TC 34 standards as revised recently. For applications with ELV it is of high importance whether the creepage distance shall be 0,6 mm or may be 0,2 mm in the case where inorganic insulating material is used.

Correction

In Amendment 1 to IEC 60238 Edition 9, a complete paragraph was deleted by accident. This was corrected with the publication of a corrigendum to Amendment 1, however an editorial correction needs to be made to the references to previous items, changed to table footnotes "a" and "d", as the referenced text was included in Tables 13a and 13b.

EDISON SCREW LAMPHOLDERS

1 Scope

This International Standard applies to lampholders with Edison thread E14, E27 and E40, designed for connection to the supply of lamps and semi-luminaires¹ only.

It also applies to switched-lampholders for use in AC circuits only, where the working voltage does not exceed 250 V r.m.s.

This standard also applies to lampholders with Edison thread E5 designed for connection to the supply mains of series connected lamps, with a working voltage not exceeding 25 V, to be used indoors, and to lampholders with Edison thread E10 designed for connection to the supply mains of series connected lamps, with a working voltage not exceeding 60 V, to be used indoors or outdoors. It also applies to lampholders E10 for building-in, for the connection of single lamps to the supply. These lampholders are not intended for retail sale.

As far as it reasonably applies, this standard also covers lampholders other than lampholders with Edison thread designed for connection of series-connected lamps to the supply.

NOTE This type of lampholder is for example used in Christmas tree lighting chains.

As far as it reasonably applies, this standard also covers adapters.

This standard also covers lampholders which are, wholly or partly, integral with a luminaire or intended to be built into appliances. It covers the requirements for the lampholder only. For all other requirements, such as protection against electric shock in the area of the terminals or of the lamp cap, the requirements of the relevant appliance standard are observed and tested after building into the appropriate equipment, when that equipment is tested according to its own standard. Such lampholders as well as lampholders provided with a snap-on outer shell, for use by luminaire manufacturers only, are not for retail sale.

This standard applies to lampholders to be used indoors or outdoors in residential as well as in industrial lighting installations. It also applies to candle lampholders. In locations where special conditions prevail, as for street lighting, on board ships, in vehicles and in hazardous locations, for example where explosions are liable to occur, special constructions may be required.

This standard does not apply to three-light lampholders E26d.

This standard is based on the following data relative to lamps for general lighting service:

- caps E14 are used for lamps with a current not exceeding 2 A;
- caps E27 are used for lamps with a current not exceeding 4 A;
- caps E40 are used for lamps with a current not exceeding 16 A, or 32 A if the nominal voltage of the supply does not exceed 130 V (see 5.5 and 6.3).

Where lampholders are used in luminaires, their maximum operating temperatures are specified in IEC 60598.

¹ Requirements for lampholders suitable for semi-luminaires are under consideration.