

Table of Contents

Chapter 1: Principles of Transmission

Metallic Media	1-1
Electrical Conductors	1-2
American Wire Gauge (AWG)	1-6
Insulation	1-6
Balanced Twisted-Pair Cables	1-9
Environmental Considerations	1-10
Cable Shielding	1-13
Drain Wires	1-16
Analog Signals	1-17
Telephony	1-23
Digital Signals	1-29
Types of Transmission Circuits	1-39
Asynchronous and Synchronous Transmission	1-40
Digital Hierarchy	1-41
Video Transmission	1-46
Transmission Line Concepts	1-48
Balanced Twisted-Pair Performance	1-57
Balanced Twisted-Pair Channel Performance	1-58
Balanced Twisted-Pair Permanent Link Performance	1-62
Balanced Twisted-Pair Applications	1-63
Optical Fiber	1-78
Optical Fiber Transmitters	1-79
Optical Fiber Receivers	1-88
Optical Fiber Medium	1-89
Bandwidth	1-91
Optical Fiber Applications Support Information	1-103
Verifying Optical Fiber Performance and Electronics Compatibility	1-105
Selecting an Optical Fiber Core Size to Application or Original Equipment Manufacturer (OEM) Specifications	1-116
Synchronous Optical Network (SONET) and Synchronous Digital Hierarchy (SDH) Concepts	1-116
Appendix	1-121

Chapter 2: Electromagnetic Compatibility

Electromagnetic Compatibility (EMC) 2-1
Electromagnetic Spectrum 2-2
Electromagnetics 2-6
Measuring Electromagnetic Compatibility (EMC) 2-9
Electromagnetic Interference (EMI)—A Problem 2-12
Electromagnetic Compatibility (EMC)—The Solution. 2-15
Electromagnetic Interference (EMI) and Cabling 2-18
Electromagnetic Qualification Parameters. 2-19
Unwanted Signals 2-24
Grounding (Earthing). 2-27
Minimizing Electromagnetic Interference (EMI). 2-35
Considerations for Electromagnetic Compatibility (EMC) in Cabling Systems. 2-36
Interference Reduction in Shielded Rooms 2-42
Telecommunications Cabling within Joint-Use Tunnel 2-44

Chapter 3: Telecommunications Spaces

Telecommunications Spaces 3-1
Telecommunications Spaces Considerations 3-1
Telecommunications Rooms (TRs) and Telecommunications Enclosures (TEs). 3-18
Telecommunications Room (TR) and Telecommunications Enclosure (TE)
Applications 3-19
Telecommunications Room (TR) Design 3-21
General Requirements for All Telecommunications Enclosures (TEs) 3-26
Equipment Rooms (ERs) 3-28
Equipment Room (ER) Design. 3-30
Locating the Equipment Room (ER). 3-32
Space Allocation and Layout. 3-37
Cable Installation and Pathways 3-42
Electrical Power 3-45
Heating, Ventilation, and Air-Conditioning (HVAC) Environmental Control 3-48
Miscellaneous Considerations 3-50
Design Approval, Buildout, and Final Inspection 3-50
Entrance Facilities (EFs). 3-52

Chapter 4: Backbone Distribution Systems

Backbone Distribution Systems	4-1
Cabling Topologies	4-3
Hierarchical Star Campus Backbone Designs	4-24
Telecommunications Rooms (TRs) and Telecommunications Enclosures (TEs)	4-31
Building Backbones	4-32
Choosing Media	4-38
Backbone Building Pathways (Internal)	4-41
Miscellaneous Support Facilities	4-47
Bonding and Grounding (Earthing)	4-49
Backbone Planning	4-49
Indoor Hardware	4-51
Ethernet in the First Mile (EFM)	4-53

Chapter 5: Horizontal Distribution Systems

Horizontal Distribution Systems	5-1
---	-----

SECTION 1: HORIZONTAL CABLING SYSTEMS

Horizontal Cabling Systems	5-5
Horizontal Cabling Media	5-17
Work Areas and Open Office Cabling	5-20
Simultaneous Data and Power Transmission within Horizontal Cabling	5-37
Centralized Optical Fiber Cabling	5-44
Fiber-To-The-Outlet (FTTO)	5-48
Horizontal Pathways for Fiber to the Office (FTTO) Systems	5-53
Passive Optical Networks (PONs)	5-56

SECTION 2: HORIZONTAL PATHWAYS

Horizontal Pathways	5-65
Types of Horizontal Pathways	5-70
Ceiling Distribution Systems	5-93
Other Horizontal Pathways	5-110

SECTION 3: ADA REQUIREMENTS

Americans with Disabilities Act (ADA) Requirements	5-117
Appendix: Disabled Access and the Americans with Disabilities Act (ADA)	5-125

Chapter 6: ICT Cables and Connecting Hardware

ICT Cables and Connecting Hardware 6-1
Balanced Twisted-Pair Cables 6-3
Optical Fiber Cables. 6-14
Coaxial Cables 6-24
Balanced Twisted-Pair Connectors 6-33
Balanced Twisted-Pair Connecting Hardware. 6-55
Balanced Twisted-Pair Connecting Blocks 6-61
Optical Fiber Connectors 6-77
Optical Fiber Connecting Hardware 6-89
Coaxial Connectors 6-95
Coaxial Connecting Hardware 6-103

Chapter 7: Firestop Systems

Firestop Systems 7-1
Firestop and Disaster Avoidance 7-3
Fire-Resistance Rated Construction 7-6
Firestop Considerations 7-8
Testing and Guidelines for Firestops 7-11
Types of Firestop Systems 7-19
Firestop for Brick, Concrete Block, and Concrete Walls 7-32
Firestop for Framed Wall Assemblies 7-36
Firestop for Lath and Plaster Walls 7-42
Firestop for Combination Walls 7-42
Firestop for Floor Assemblies 7-43
Firestop for Floor/Ceiling Assemblies 7-44
Structural Steel Floor Units with Concrete Floor Fill without Suspended
Ceiling Membranes 7-47
Firestop for Roof/Ceiling Assemblies 7-47
Fire-Rated Vertical Shafts. 7-48
Firestop for Curtain Wall Floor/Ceiling Seals 7-49
General Firestop Considerations 7-52
Appendix A: Approved Firestop Methods 7-54
Appendix B: Testing and Guidelines for Firestops 7-108

Chapter 8: Bonding and Grounding (Earthing)

Bonding and Grounding (Earthing) 8-1
Alternating Current (ac) Grounding (Earthing) Electrode System 8-5
Equipment Grounding (Earthing) System 8-8
Telecommunications Bonding Infrastructure 8-12
Lightning Exposure 8-26

Chapter 9: Power Distribution

Power Distribution	9-1
Alternating Current (ac) Power	9-2
American Wire Gauge (AWG)	9-15
Alternating Current (ac) Voltage Quality Problems	9-18
Power Distribution for Information Technology Equipment (ITE) Spaces	9-25
Electrical Safety	9-28
Power System Redundancy	9-31
Power Conditioning/Power Protection	9-36
Direct Current (dc) Power	9-52
Installation of Direct Current (dc) Systems	9-61
Batteries	9-63
Power System Alarms	9-72
Power System Monitoring and Control	9-75
Conductor Identification	9-77

Chapter 10: Telecommunications Administration

Telecommunications Administration	10-1
Identification Methods	10-12
Identification Systems	10-23
Labeling and Recordkeeping	10-31
Administration of Large Telecommunications Spaces	10-39

Chapter 11: Field Testing of Structured Cabling

Field Testing of Structured Cabling	11-1
Balanced Twisted-Pair Cabling Tests	11-2
Balanced Twisted-Pair Cabling Acceptance Tests	11-11
Coaxial Cabling Testing	11-18
Optical Fiber Cabling Tests	11-19
Optical Fiber Cabling Acceptance Tests	11-22
Optical Fiber Cabling Field Testing	11-24
Maintenance and Troubleshooting for Optical Fiber Cabling	11-27
Additional Optical Fiber Troubleshooting Tools and Equipment	11-28

Chapter 12: Outside Plant

Outside Plant	12-1
Telecommunications Service Entrances	12-6
Underground Entrances	12-6
Buried Entrances	12-9
Aerial Entrances	12-10
Other Telecommunications Service Entrance Considerations	12-15
Terminating Space for Telecommunications Entrance Facilities	12-20

Table of Contents

Terminating Conduit Inside a Building	12-22
Network Interface (NI) Locations	12-23
Outside Building Terminals (Pedestals and Cabinets) Pedestal Hardware Mounted on Outside Walls	12-25
Direct-Buried Pathways	12-26
Trenches	12-28
Underground Pathways	12-32
Conduit Guidelines	12-33
Terminating Conduit at a Designated Property Line	12-38
Maintenance Hole Guidelines	12-39
Aerial Plant Pathways	12-46

Chapter 13: Audiovisual Systems

Audiovisual (AV) Systems	13-1
Fundamentals.	13-2
Types of Signals	13-10
Environmental Considerations.	13-30
Visual Display Systems	13-38
Program Audio and Speech Reinforcement Systems	13-43
Signal Distribution Systems	13-52
Audioconferencing Systems	13-54
Videoconferencing Systems	13-70
Control Systems	13-79
Overhead Paging Systems	13-82
Sound Masking Systems	13-92
Digital Signage Systems	13-96
Cable Television Distribution Systems	13-100

Chapter 14: Building Automation Systems

Building Automation Systems (BAS)	14-1
Building Automation Systems (BAS) Interfaces with Other Systems	14-6
Building Automation Systems (BAS) Communications Networks	14-17
Building Automation Systems (BAS) Electrical Characteristics.	14-23
Planning Building Automation Systems (BAS) Distribution Cabling	14-25

Chapter 15: Data Networks

Data Networks	15-1
Open Systems Interconnection (OSI) Reference Model	15-4
Network Hardware	15-8
Network Software	15-14
Network Supported Systems	15-15
Network Design	15-19
Computer Rooms	15-21
Campus and Multisite Network Design	15-33

Chapter 16: Wireless Networks

Wireless Networks.	16-1
Services and Applications.	16-2
Frequency and Wavelength	16-6
Electromagnetic Spectrum	16-14
Wireless System Design.	16-22
Selection of Technology	16-25
Components of a Wireless System	16-28
Distributed Antenna Systems (DAS)	16-38
Personal Area Networks (PANs)	16-65
Wireless LAN (WLAN) Technology	16-67
Wireless LAN (WLAN) Components	16-69

Chapter 17: Electronic Safety and Security

Electronic Safety and Security (ESS)	17-1
Electronic and Electrical Door Hardware.	17-8
Video Surveillance.	17-21
Intrusion Detection	17-28
Fire Detection and Alarm Systems (FDAS)	17-31
Fire Alarm (FA) Notification	17-36
Fire Alarm Control Panels (FACP)	17-39
Digital Alarm Communicator System (DACS)	17-49
Area of Refuge and Rescue Two-Way Communication Systems	17-56
Mass Notification and Emergency Communications (MNEC) Systems.	17-59

Chapter 18: Data Centers

Data Centers 18-1
Data Center Redundancy and Availability 18-4
Structured Cabling Hierarchy for Data Centers 18-9
Guidelines for Telecommunications Cabling, Cable Containment, Equipment
Racks, and Cabinets 18-16
Data Center Security 18-24
Operation, Ownership Costs, Environmental Impact, and Efficiency. 18-30
Data Center Planning Considerations. 18-30

Chapter 19: Health Care

Health Care 19-1
Space and Pathway Requirements and Considerations. 19-2
Nurse Call Systems 19-10
Code Call Systems 19-20
Hospital Security. 19-21
Wireless Networks. 19-24
Audiovisual (AV) Systems 19-26
Picture Archiving and Communication System (PACS) 19-28
Patient Monitoring. 19-28
Radio Frequency Identification (RFID)–Based Systems 19-30
Interactive Patient Entertainment and Education Systems 19-33
Wayfinding and Signage. 19-37
Regulatory Bodies and Organizations. 19-38

Chapter 20: Residential Cabling

Residential Cabling 20-1
Components. 20-4
Planning the Cabling System 20-19
Rough-In Cabling 20-20
Finish Cabling. 20-22

Chapter 21: Project Administration and Execution

SECTION 1: PROFESSIONAL DEVELOPMENT

Professional Development 21-1

SECTION 2: PROJECT MANAGEMENT

Project Management 21-5

SECTION 3: DISASTER RECOVERY PLANNING AND RISK MANAGEMENT

Disaster Recovery Planning and Risk Management	21-63
The Disaster Recovery Plan	21-67

Chapter 22: Special Design Considerations

Special Occupancies	22-1
-------------------------------	------

SECTION 1: MICE CONSIDERATIONS

MICE Considerations	22-5
-------------------------------	------

Appendix A: Codes, Standards, Regulations, and Organizations

Codes, Standards, Regulations, and Organizations	A-1
International Codes and Standards	A-6
Regional Codes and Standards	A-30
National Codes and Standards	A-42
Enforcement of United States (U.S.) Building Codes, Standards, and Regulations	A-74
Wireless Transmission Standards	A-77
Approval of Electrical Products and Equipment	A-81
Regulations and Standards for Emissions and Immunity	A-86
Commercial Products Marketed in the United States (U.S.)	A-86
Radiation Limits for Class A and Class B.	A-87
Emission Limits for Class A and Class B	A-88
Commercial Products Marketed Outside the United States (U.S.)	A-88
Electrostatic Discharge (ESD)	A-93
Network Interfaces and Demarcation Points in the United States (U.S.)	A-93
Definitions	A-94
Classifications.	A-94
Groups	A-94
Types	A-95
Analog Voice Connectors	A-96
Analog Data Connectors.	A-116
Network Channel Equipment Connectors	A-134

Appendix B: Legal Considerations

Legal Aspects of Information and Communications Technology (ICT) Design	B-1
---	-----

Glossary**Bibliography****Index**

Figures

Chapter 1: Principles of Transmission

Figure 1.1	Calculated attenuation values for cables insulated with FEP, ECTFE, and PVC from 1 MHz to 135 MHz at 22 °C (72 °F).	1-11
Figure 1.2	Calculated and measured attenuation values for cables insulated with FEP, ECTFE, and PVC from 1 MHz to 135 MHz at 40 °C (104 °F) . . .	1-12
Figure 1.3	Calculated and measured attenuation values for cables insulated with FEP, ECTFE, and PVC from 1 MHz to 135 MHz at 60 °C (140 °F) . . .	1-12
Figure 1.4	Example 1 of a sinusoidal signal	1-17
Figure 1.5	Example 2 of a sinusoidal signal	1-19
Figure 1.6	IP telephony architecture	1-27
Figure 1.7	DS1 frame format	1-31
Figure 1.8	E1 frame format	1-32
Figure 1.9	Polar non-return-to-zero level.	1-36
Figure 1.10	Bipolar AMI	1-36
Figure 1.11	Biphase Manchester	1-36
Figure 1.12	Two binary bits encoded into one quaternary (2B1Q)	1-36
Figure 1.13	MLT-3, also referred to as NRZI-3	1-37
Figure 1.14	Composite video	1-46
Figure 1.15	Two-conductor transmission line	1-48
Figure 1.16	Resistive model.	1-49
Figure 1.17	Capacitance model	1-49
Figure 1.18	Inductive model	1-50
Figure 1.19	Primary transmission line parameters	1-51
Figure 1.20	General transmission model	1-52
Figure 1.21	Example of a channel test configuration.	1-58
Figure 1.22	Permanent link test configuration	1-62
Figure 1.23	Typical configuration of endspan and midspan power source equipment	1-77
Figure 1.24	Spectral profile comparison of laser and LED	1-80
Figure 1.25	Spectral width of an LED source showing full width half maximum	1-81
Figure 1.26	Numerical aperture	1-82
Figure 1.27	System bandwidth versus distance example.	1-91
Figure 1.28	Pulse distortion because of rise time and data rate	1-93
Figure 1.29	Link bandwidth at 1300 nm using 62.5/125 micrometer multimode optical fiber	1-97
Figure 1.30	Core and coating.	1-100
Figure 1.31	DSX optical multiplexing design	1-118
Figure 1.32	SONET multiplexing design	1-119
Figure 1.33	WDM	1-120

Chapter 2: Electromagnetic Compatibility

Figure 2.1	Electromagnetic spectrum	2-3
Figure 2.2	Dependence of the safe distance to EMI source on its power	2-10
Figure 2.3	Model T for a short wire channel	2-21
Figure 2.4	Surge test voltage waveform sample	2-23
Figure 2.5	CM versus DM.	2-25
Figure 2.6	Ground loops in shielded cabling systems	2-28
Figure 2.7	Ground loop because of stray capacitance at high frequencies	2-29
Figure 2.8	Common impedance coupling interference	2-30
Figure 2.9	Field-to-cable and ground loop	2-31
Figure 2.10	Coupling reduction as function of grounding (earthing) practice	2-32
Figure 2.11	Higher frequency twist decrease	2-33
Figure 2.12	Typical power line filter	2-39
Figure 2.13	Isolation transformer scheme	2-40
Figure 2.14	Samples of ferrite toroids, beads, and sleeves	2-41
Figure 2.15	Balance concept	2-43
Figure 2.16	EMI susceptibility of circuits and systems connected through unshielded cables	2-45
Figure 2.17	Ground loop and EMI immunity.	2-47

Chapter 3: Telecommunications Spaces

Figure 3.1	Typical cabinet and rack mounting hole spacing arrangements	3-15
Figure 3.2	Rack unit	3-15
Figure 3.3	Space considerations when sizing a telecommunications space.	3-17
Figure 3.4	Typical TR layout.	3-23
Figure 3.5	Typical sleeve/conduit	3-24
Figure 3.6	Typical shallow room layout	3-25
Figure 3.7	Typical AP ER	3-34
Figure 3.8	Typical ER layout.	3-38

Chapter 4: Backbone Distribution Systems

Figure 4.1	Star topology	4-5
Figure 4.2	Hierarchical star topology.	4-6
Figure 4.3	Ring topology (simplified)	4-8
Figure 4.4	Buildings connected by a physical ring topology	4-9
Figure 4.5	Main backbone ring and redundant backbone star combined	4-10
Figure 4.6	Physical star/logical ring topology	4-11
Figure 4.7	Clustered star topology with physical star/logical ring	4-12
Figure 4.8	Bus topology	4-13
Figure 4.9	Tree and branch topology.	4-14
Figure 4.10	Fully connected mesh topology.	4-15

Table of Contents

Figure 4.11	Partially connected mesh topology	4-17
Figure 4.12	Point-to-multipoint optical topology.	4-18
Figure 4.13	PTP optical fiber	4-19
Figure 4.14	PTP balanced twisted-pair topology.	4-22
Figure 4.15	Typical backbone hierarchical star topology for multiple buildings on a campus (inside and outside distribution).	4-24
Figure 4.16	Example of multiple hierarchical level campus backbone design	4-26
Figure 4.17	Levels of cross-connections	4-27
Figure 4.18	Logical bus topology	4-28
Figure 4.19	Logical ring topology implemented using a physical star topology.	4-29
Figure 4.20	Logical tree topology implemented using a hierarchical star topology	4-29
Figure 4.21	Star building backbone	4-33
Figure 4.22	Hierarchical star building backbone.	4-34
Figure 4.23	Redundant routing for building backbone (HCs [FDs] not linked)	4-35
Figure 4.24	Example of combined optical fiber/balanced twisted-pair backbone supporting voice and data traffic.	4-36
Figure 4.25	ERs and AP cabling system interface cabling	4-37
Figure 4.26	Typical office building pathway layout	4-44
Figure 4.27	Typical sleeve and slot installations	4-45
Figure 4.28	EFM network boundaries	4-53

Chapter 5: Horizontal Distribution Systems

Figure 5.1	Typical horizontal cabling system elements	5-2
Figure 5.2	Horizontal cabling system channel	5-7
Figure 5.3	Horizontal cabling system channel model with four connection points	5-8
Figure 5.4	Horizontal cabling system channel model with three connection points	5-9
Figure 5.5	Horizontal cabling system permanent link model with three connection points	5-10
Figure 5.6	Example of connection by means of cross-connection	5-12
Figure 5.7	Example of connection by means of interconnection	5-13
Figure 5.8	Example of connection by means of cross-connection and interconnection.	5-14
Figure 5.9	Example of connection by means of double cross-connection	5-15
Figure 5.10	Total cable length in the horizontal cabling system channel	5-18
Figure 5.11	Pin/pair assignments.	5-21
Figure 5.12	Typical dimensions for furniture opening for telecommunications faceplate	5-24
Figure 5.13	Example of MUTOA application	5-26
Figure 5.14	CPs used in a combined furniture system and private office work area environment	5-30
Figure 5.15	CPs located on all columns.	5-33
Figure 5.16	CPs located in a space between the columns	5-34
Figure 5.17	CPs located in checkerboard order	5-35

Figure 5.18	CPs located on columns close to the building core	5-36
Figure 5.19	Temperature versus wattage for category cable types	5-38
Figure 5.20	Insertion loss versus temperature for category cable types	5-39
Figure 5.21	Centralized optical fiber cabling	5-45
Figure 5.22	Traditional structured cabling LAN design compared with FTTO LAN . . .	5-49
Figure 5.23	Traditional active Ethernet design compared with PON-based architecture	5-56
Figure 5.24	Underfloor conduit extended to individual telecommunications outlet boxes	5-70
Figure 5.25	Typical underfloor conduit system	5-71
Figure 5.26	Conduit bodies recommended for telecommunications cables	5-72
Figure 5.27	Recommended pull box configurations	5-82
Figure 5.28	Stringered access floor system	5-86
Figure 5.29	Recommended clearance for access floor spaces	5-88
Figure 5.30	Typical zoned ceiling (plan view)	5-96
Figure 5.31	Conduit-based ceiling zone (elevation view)	5-97
Figure 5.32	Rules of installation for discrete cable support facilities	5-99
Figure 5.33	Raceways and fittings	5-101
Figure 5.34	Attaching various utility columns	5-103
Figure 5.35	Perimeter raceway	5-112
Figure 5.36	Molding raceway	5-113
Figure 5.37	Side-reach telephones	5-121
Figure 5.38	Forward-reach telephones	5-122
Figure 5.39	International teletypewriter/text telephone symbol and volume control telephone symbol	5-124

Chapter 6: ICT Cables and Connecting Hardware

Figure 6.1	Balanced twisted-pair cable construction types	6-6
Figure 6.2	Examples of balanced twisted-pair cables	6-7
Figure 6.3	Multimode optical fiber	6-16
Figure 6.4	Singlemode optical fiber	6-17
Figure 6.5	Side view of a loose-tube optical fiber cable	6-19
Figure 6.6	Loose-tube furcating harness	6-19
Figure 6.7	Loose-tube optical fiber cable	6-20
Figure 6.8	Tight-buffered optical fiber cable, distribution construction	6-21
Figure 6.9	Tight-buffered optical fiber cable, breakout construction	6-22
Figure 6.10	Series-6 quad shield (screen) coaxial cable	6-24
Figure 6.11	Classification of cables and wires according to the <i>NEC</i>	6-30
Figure 6.12	110-style IDC connector design	6-34
Figure 6.13	Examples of 66-style connector designs	6-37
Figure 6.14	BIX-style IDC connector design	6-40
Figure 6.15	Examples of LSA-style connector designs	6-42

Table of Contents

Figure 6.16	8P8C unkeyed modular plug	6-45
Figure 6.17	8P8C modular plugs for stranded and solid conductors	6-46
Figure 6.18	8P8C modular jack	6-48
Figure 6.19	Modular jack design	6-48
Figure 6.20	Eight-position jack pin/pair assignments (front view)	6-49
Figure 6.21	50-position miniature ribbon connector	6-51
Figure 6.22	50-position miniature ribbon connector design	6-52
Figure 6.23	Telecommunications outlet/connectors.	6-55
Figure 6.24	Examples of work area telecommunications outlet designs.	6-56
Figure 6.25	Rack-mount \approx 483 mm (19 in) modular patch panel	6-57
Figure 6.26	Modular patch panel with cable management bar installed in an \approx 483 mm (19 in) equipment rack.	6-59
Figure 6.27	66-style block, 89-style mounting brackets, and a distribution frame with installed 66-style blocks	6-61
Figure 6.28	110-style wiring blocks	6-63
Figure 6.29	BIX-style connecting blocks mounted in a distribution frame	6-66
Figure 6.30	25-pair BIX-style connecting strip	6-67
Figure 6.31	LSA-style connecting blocks	6-68
Figure 6.32	10-pair LSA-style connecting block	6-69
Figure 6.33	Hybrid equipment cord assembly or hybrid patch cord assembly.	6-71
Figure 6.34	Example of MS2 and Type 710 IDC connector splicing contacts.	6-73
Figure 6.35	Example of single-pair splice connectors and modules	6-74
Figure 6.36	Example of multipair splice connectors and modules	6-75
Figure 6.37	LC-style optical fiber adapters and connectors	6-80
Figure 6.38	SC-style optical fiber adapters and connectors	6-81
Figure 6.39	ST-style optical fiber connector.	6-83
Figure 6.40	Array-style optical fiber connector and adapter (example of Type-A MPO configuration)	6-84
Figure 6.41	Array-style optical fiber connector and adapter (example of Type-B MPO configuration)	6-84
Figure 6.42	Fusion splicer	6-85
Figure 6.43	Mechanical splice open position	6-86
Figure 6.44	Optical fiber pigtail splicing	6-87
Figure 6.45	Cross-connection of optical fiber cabling segments (first- and second-level backbone)	6-90
Figure 6.46	Interconnection of equipment to backbone cabling	6-91
Figure 6.47	Hybrid optical fiber patch cord assembly	6-92
Figure 6.48	BNC-style connector	6-95
Figure 6.49	BNC-style connector components	6-96
Figure 6.50	BNC-style connector plug and jack	6-96
Figure 6.51	50-ohm and 75-ohm bayonet BNC-style connectors	6-97

Figure 6.52	One-piece crimp-style F-style connector	6-99
Figure 6.53	N-style coaxial connector	6-101
Figure 6.54	Standard wall-mount multimedia and modular furniture multimedia outlets featuring F-style coaxial connectors	6-103
Figure 6.55	BNC-style bracket mount and F-style ≈483 mm (19 in) rack-mount coaxial patch panels	6-105

Chapter 7: Firestop Systems

Figure 7.1	Standard time/temperature curves up to three hours	7-10
Figure 7.2	Elastomeric modules (within frames).	7-20
Figure 7.3	Mechanical firestop system	7-21
Figure 7.4	Example of fire-rated pathway device	7-22
Figure 7.5	Typical plastic pipe device	7-24
Figure 7.6	Typical cast-in-place firestop device	7-25
Figure 7.7	Examples of poke-thru.	7-26
Figure 7.8	Continuous conduit penetration through concrete	7-32
Figure 7.9	Cable penetration in concrete wall or floor	7-33
Figure 7.10	PVC innerduct penetration in concrete wall.	7-33
Figure 7.11	PVC innerduct penetration in concrete floor	7-34
Figure 7.12	Qualified cable tray seal system in concrete wall.	7-35
Figure 7.13	Qualified steel pipe system in framed wall	7-36
Figure 7.14	Telecommunications cable seal system for framed wall	7-37
Figure 7.15	Non-metallic innerduct penetration of framed wall	7-38
Figure 7.16	Sleeve systems for retrofit over existing cables	7-39
Figure 7.17	Sleeve system with cable tray	7-40
Figure 7.18	Sleeve system with cable support	7-40
Figure 7.19	Expansion joint or slot in a floor	7-49
Figure 7.20	Expansion joint or slot in a wall	7-50
Figure 7.21	Perimeter gap.	7-50
Figure 7.22	Seal system in a curtain wall	7-51
Figure 7.23	Typical label for all firestops	7-53
Figure 7.24	Concrete floor or wall	7-55
Figure 7.25	Typical framed wall penetration.	7-56
Figure 7.26	Typical concrete wall penetration	7-57
Figure 7.27	Concrete wall or floor (metallic pipes)	7-58
Figure 7.28	Concrete wall or floor (no penetrating item).	7-59
Figure 7.29	Concrete wall or floor (electrical power, telecommunications, and building signaling cables).	7-60
Figure 7.30	Concrete floor (electrical power and telecommunications cables)	7-61
Figure 7.31	Framed wall (steel pipes or conduit)	7-62
Figure 7.32	Framed wall (cable).	7-63

Table of Contents

Figure 7.33	Framed wall (steel or aluminum cable trays)	7-64
Figure 7.34	Concrete wall (cable).	7-65
Figure 7.35	Concrete floor or wall (bus duct).	7-66
Figure 7.36	Concrete floor or wall (steel pipe)	7-67
Figure 7.37	Framed wall (cables)	7-68
Figure 7.38	Framed wall (PVC pipe [closed or vented]).	7-69
Figure 7.39	Floor or wall (PVC, CPVC, or PB pipe [closed or vented] or RNC).	7-70
Figure 7.40	Wood joist floor (steel or copper pipe)	7-72
Figure 7.41	Concrete floor or wall (electrical power, building signaling, control, and telecommunications cables)	7-73
Figure 7.42	Concrete floor or wall (steel or aluminum cable tray).	7-74
Figure 7.43	Framed wall (steel or aluminum cable tray)	7-75
Figure 7.44	Floor or wall (steel or aluminum cable tray)	7-76
Figure 7.45	Floor or wall (pipes and cable tray)	7-77
Figure 7.46	Head of wall joint (framed wall or concrete, fluted deck)	7-78
Figure 7.47	Head of wall joint (concrete wall or concrete fluted deck).	7-79
Figure 7.48	Concrete floor or wall (telecommunications cable)	7-80
Figure 7.49	Framed wall (telecommunications cable)	7-81
Figure 7.50	Framed wall (telecommunications cable with sleeve).	7-82
Figure 7.51	Framed wall (telecommunications cable with firestop wrap strip)	7-83
Figure 7.52	Concrete floor or wall (telecommunications cable with sleeve)	7-84
Figure 7.53	Concrete floor or wall (telecommunications cable with firestop collar)	7-85
Figure 7.54	Framed wall stud cavity (electrical outlet box)	7-86
Figure 7.55	Concrete floor or wall (no penetrating item).	7-87
Figure 7.56	Concrete floor or wall (PVC innerduct or ENT with optical fiber cables and firestop wrap strip)	7-88
Figure 7.57	Concrete floor or wall (PVC innerduct or ENT with optical fiber cables and firestop sealant)	7-89
Figure 7.58	Framed wall (non-metallic conduit)	7-90
Figure 7.59	Framed wall (electrical power, building signaling, control, or telecommunications cable steel sleeve system)	7-91
Figure 7.60	Framed wall (electrical power, building signaling, control, or telecommunications cable split sleeve system)	7-93
Figure 7.61	Plenum-rated wrap system for combustibile pipe	7-95
Figure 7.62	Intumescent blocks	7-96
Figure 7.63	Framed wall (electrical power, building signaling, control, or telecommunications cable steel sleeve system)	7-97
Figure 7.64	Concrete floor or wall (electrical power, building signaling, control, or telecommunications cable steel sleeve system).	7-98
Figure 7.65	Framed wall (power, building signaling, control, or telecommunications split cable pathway system)	7-99
Figure 7.66	Framed wall (power, building signaling, control, or telecommunications cable sleeve device system)	7-100

Figure 7.67	Concrete floor (power, building signaling, control, or telecommunications cable sleeve system)	7-101
Figure 7.68	Framed wall (telecommunications cable steel sleeve membrane penetration system)	7-102
Figure 7.69	Framed wall (telecommunications cable firestop grommet membrane penetration system)	7-103
Figure 7.70	Framed wall (telecommunications cable firestop grommet penetration system)	7-104
Figure 7.71	Typical perimeter fire barrier system exterior insulation glass panel curtain wall	7-105
Figure 7.72	Typical framed wall HVAC duct	7-106
Figure 7.73	Concrete floor (power, building signaling, control, or telecommunications cable pathway system).	7-107

Chapter 8: Bonding and Grounding (Earthing)

Figure 8.1	Typical supplementary bonding grid	8-11
Figure 8.2	Small systems	8-14
Figure 8.3	Recommended large system arrangement	8-16
Figure 8.4	Typical PBB	8-17
Figure 8.5	Typical SBB	8-18
Figure 8.6	Equipment rack bonding and grounding (earthing)	8-24
Figure 8.7	Zone of protection.	8-27
Figure 8.8	Cone of protection.	8-27
Figure 8.9	Extending zone of protection	8-28

Chapter 9: Power Distribution

Figure 9.1	Measuring amplitude	9-2
Figure 9.2	Measuring phase difference in a three-phase system.	9-3
Figure 9.3	Delta configuration	9-4
Figure 9.4	Wye configuration	9-5
Figure 9.5	Center-tapped single-phase configuration	9-5
Figure 9.6	Typical electrical power system 1	9-6
Figure 9.7	Typical electrical power system 2	9-6
Figure 9.8	Calculation chart.	9-7
Figure 9.9	Voltage and current in phase (resistive load)	9-9
Figure 9.10	Current lags voltage (inductive circuit)	9-9
Figure 9.11	Current leads voltage (capacitive load)	9-10
Figure 9.12	Panelboard connection to equipment.	9-26
Figure 9.13	PDU connection to equipment.	9-27
Figure 9.14	Sample Class 1 electrical system topology	9-32
Figure 9.15	Sample Class 2 electrical system topology	9-33
Figure 9.16	Sample Class 3 electrical system topology	9-34

Table of Contents

Figure 9.17	Sample Class 4 electrical system topology	9-35
Figure 9.18	UPS module with maintenance bypass	9-42
Figure 9.19	UPS system	9-43
Figure 9.20	Parallel redundant UPS system	9-44
Figure 9.21	Isolated redundant UPS system	9-45
Figure 9.22	Distributed redundant UPS system	9-46
Figure 9.23	Communications link UPS system	9-47
Figure 9.24	Series configured rotary UPS system	9-48
Figure 9.25	Elevation of modular UPS system	9-50
Figure 9.26	Typical dc power system	9-52
Figure 9.27	Identification by color, letter, or marking	9-78

Chapter 10: Telecommunications Administration

Figure 10.1	Telecommunications administration systems	10-1
Figure 10.2	Numbering TRs	10-13
Figure 10.3	Numbering cable trays	10-15
Figure 10.4	Patch panel labeling within a rack	10-18
Figure 10.5	Twisted-pair patch panel labeling with six-port groupings and near- and far-end panel and port identifiers	10-19
Figure 10.6	Pair patch panel labeling example where available label space is limited	10-19
Figure 10.7	Optical fiber patch panel labeling using sequential port numbering identifiers	10-20
Figure 10.8	Optical fiber patch panel labeling with subpanel cassette identifiers	10-20
Figure 10.9	Optical fiber patch panel labeling with HDA identifiers	10-21
Figure 10.10	Labeling example	10-27
Figure 10.11	Recordkeeping system example	10-35
Figure 10.12	Room grid coordinate example	10-39
Figure 10.13	Sample rack and cabinet non-grid identifiers	10-41

Chapter 11: Field Testing of Structured Cabling

Figure 11.1	Wire map testing	11-2
Figure 11.2	Pair electrical lengths	11-4
Figure 11.3	Propagation delay/delay skew	11-4
Figure 11.4	Return loss	11-5
Figure 11.5	NEXT	11-6
Figure 11.6	ACR-F	11-7
Figure 11.7	PSNEXT	11-7
Figure 11.8	Coaxial TDR test	11-10
Figure 11.9	Typical work area three-connector channel	11-11
Figure 11.10	Typical work area four-connector channel	11-11
Figure 11.11	Typical data center four-connector channel	11-12

Figure 11.12 Work area three-connector permanent link	11-12
Figure 11.13 Work area four-connector permanent link	11-13
Figure 11.14 Data center four-connector permanent link	11-14
Figure 11.15 MPTL	11-15
Figure 11.16 OTDR display	11-21

Chapter 12: Outside Plant

Figure 12.1 Underground pathway plan	12-2
Figure 12.2 Direct-buried pathway plan	12-4
Figure 12.3 Installing underground entrances	12-8
Figure 12.4 Examples of building attachment	12-11
Figure 12.5 Vertical conduit mast.	12-12
Figure 12.6 Cable entrance sleeve through a wall	12-14
Figure 12.7 Typical joint trenching dimensions (section view through trench)	12-29
Figure 12.8 Positioning conduit on poles	12-37
Figure 12.9 Typical cable MH	12-39
Figure 12.10 Basic MH configurations	12-40
Figure 12.11 MH Elements	12-41
Figure 12.12 Typical MH diagram	12-43
Figure 12.13 Typical MH on private property	12-44

Chapter 13: Audiovisual Systems

Figure 13.1 Measuring wavelength	13-2
Figure 13.2 Different amplitudes of equal frequency sine waves	13-3
Figure 13.3 Equal amplitudes of different frequency sine waves.	13-3
Figure 13.4 Two waves offset by 180 degrees	13-4
Figure 13.5 Frequency	13-5
Figure 13.6 Complex waveform	13-6
Figure 13.7 Building complex waveforms	13-7
Figure 13.8 Electromagnetic spectrum	13-7
Figure 13.9 Sample rate the size of the signal frequency	13-12
Figure 13.10 Sample rate double the size of the signal frequency	13-13
Figure 13.11 Video signal building blocks	13-16
Figure 13.12 Video signal bandwidth	13-17
Figure 13.13 Analog video signals	13-20
Figure 13.14 RF signal	13-21
Figure 13.15 Examples of DVI connectors.	13-22
Figure 13.16 Example of HDMI connector	13-23
Figure 13.17 Example of a DisplayPort connector.	13-24
Figure 13.18 Optimum and acceptable viewing areas	13-32
Figure 13.19 Sightlines.	13-33

Table of Contents

Figure 13.20 Flat floor—seats aligned	13-34
Figure 13.21 Tiered floor—seats staggered	13-35
Figure 13.22 Chain of typical audio components	13-43
Figure 13.23 Example of horn installation	13-45
Figure 13.24 Potential versus needed acoustic gain measurements	13-47
Figure 13.25 Loudspeaker dispersion polar plot	13-49
Figure 13.26 Loudspeaker coverage formula	13-50
Figure 13.27 Typical audioconferencing system	13-55
Figure 13.28 Conference room microphone pickup pattern	13-58
Figure 13.29 Two connected rooms and their acoustic echo cancellers	13-61
Figure 13.30 Telephone hybrid	13-63
Figure 13.31 Line echo canceller	13-64
Figure 13.32 Loudspeaker coverage angle	13-66
Figure 13.33 Microphone pickup and loudspeaker coverage patterns	13-68
Figure 13.34 FOV	13-73
Figure 13.35 Camera bright-to-dark ranges	13-74
Figure 13.36 Videoconference light setup	13-75
Figure 13.37 Hexagonal loudspeaker pattern.	13-85
Figure 13.38 Square loudspeaker pattern	13-86
Figure 13.39 70 V loudspeaker line loss	13-89
Figure 13.40 Distributed amplifier system.	13-91
Figure 13.41 Collaboration of component technology	13-97
Figure 13.42 Home run network design	13-103
Figure 13.43 Trunk and tap design.	13-104
Figure 13.44 Video over balanced twisted-pair cabling	13-104
Figure 13.45 Video over optical fiber cabling	13-105
Figure 13.46 Dividing the optical signal	13-106
Figure 13.47 Signal tilt for ≈ 12.7 mm (0.50 in) hardline.	13-107

Chapter 14: Building Automation Systems

Figure 14.1 Building system changes	14-3
Figure 14.2 Example of fire alarm, security, and access control interfaces with BAS .	14-6
Figure 14.3 HVAC system in a small commercial building	14-9
Figure 14.4 Hierarchical configuration of processor and controller levels.	14-18
Figure 14.5 Cabling system elements and channel.	14-30
Figure 14.6 Single-point and chained branch devices	14-31
Figure 14.7 Cabling system topologies for BAS	14-37
Figure 14.8 Devices bridged at HC (FD) or HCP	14-38
Figure 14.9 Devices chained at the HC (FD) or HCP	14-39
Figure 14.10 BAS equipment cabling	14-42

Figure 14.11 Traditional distributed BAS with multiple horizontal pathways	14-43
Figure 14.12 Integrated distributed BAS with single horizontal pathway	14-44
Figure 14.13 Separate and consolidated cabling systems	14-46
Figure 14.14 Reducing quantity and costs of BAS controllers.	14-48

Chapter 15: Data Networks

Figure 15.1 Example of a LAN	15-2
Figure 15.2 Example of a WAN	15-3
Figure 15.3 OSI Reference Model	15-5
Figure 15.4 Message transfer described using the OSI Reference Model	15-7
Figure 15.5 Multiple routers in an internetwork	15-11
Figure 15.6 Integrated VoIP infrastructure	15-16
Figure 15.7 Types of network video communications	15-17
Figure 15.8 Functional (top-down) design	15-19
Figure 15.9 Physical (bottom-up) design.	15-20
Figure 15.10 Class 1 telecommunications infrastructure	15-22
Figure 15.11 Class 2 telecommunications infrastructure	15-22
Figure 15.12 Class 3 telecommunications infrastructure	15-23
Figure 15.13 Class 4 telecommunications infrastructure	15-24
Figure 15.14 Server-to-switch connections	15-25
Figure 15.15 Redundant server-to-switch connections	15-26
Figure 15.16 Server-to-storage director connections	15-27
Figure 15.17 Redundant server-to-storage director connections	15-28
Figure 15.18 Example of Class 3 and Class 4 network and storage infrastructure. . .	15-29
Figure 15.19 Centralized data center topology.	15-30
Figure 15.20 End-of-row data center topology.	15-31
Figure 15.21 Top-of-rack data center topology	15-32
Figure 15.22 Example of campus network.	15-33
Figure 15.23 Links from customer site to SP	15-35
Figure 15.24 Example of a centralized WAN design	15-37
Figure 15.25 Example of a partial mesh WAN design	15-38
Figure 15.26 Partial mesh WAN after a link failure	15-39
Figure 15.27 Example of a full mesh WAN design	15-40

Chapter 16: Wireless Networks

Figure 16.1 Frequency, amplitude, and wavelength	16-6
Figure 16.2 Propagation velocity through free space.	16-7
Figure 16.3 Fresnel zone.	16-8
Figure 16.4 Ground and sky waves.	16-11
Figure 16.5 Isotropic gain	16-12
Figure 16.6 Amplitude modulation	16-14

Table of Contents

Figure 16.7	Frequency modulation	16-15
Figure 16.8	Phase modulation	16-16
Figure 16.9	Pulse modulation techniques	16-17
Figure 16.10	Harmonic distortion.	16-19
Figure 16.11	Power injector with tower-mounted preamplifier	16-35
Figure 16.12	Power injector for WLAN AP	16-36
Figure 16.13	Typical DAS environments	16-40
Figure 16.14	Omnidirectional antennas.	16-42
Figure 16.15	Directional antennas	16-43
Figure 16.16	Radiating cable standoff mount.	16-46
Figure 16.17	Headend and backend	16-50
Figure 16.18	Optical to RF coupling power relationship.	16-52
Figure 16.19	ESS using a wireless distribution system	16-70
Figure 16.20	ESS using a cable distribution system	16-71
Figure 16.21	PTP bridging.	16-74
Figure 16.22	Point-to-multipoint bridging	16-75
Figure 16.23	Repeating bridge.	16-76

Chapter 17: Electronic Safety and Security

Figure 17.1	Elements of a security program	17-2
Figure 17.2	Threat, risk, and vulnerability assessments	17-3
Figure 17.3	Security quandary.	17-4
Figure 17.4	MPTL with one CP	17-12
Figure 17.5	Electric strikes	17-15
Figure 17.6	Magnetic locks	17-17
Figure 17.7	Electric locksets	17-18
Figure 17.8	Electric latch and mechanical operation	17-19
Figure 17.9	Electrified exit hardware	17-20
Figure 17.10	Grid display layouts.	17-25
Figure 17.11	Typical fire alarm pull station	17-34
Figure 17.12	Example of a Class N pathway	17-42
Figure 17.13	Redundant cables in Class N pathways	17-43
Figure 17.14	Additional pathway between Switch 1 and 2.	17-44
Figure 17.15	Endpoint servicing more than one device	17-44
Figure 17.16	Enhanced annunciator panel.	17-54

Chapter 18: Data Centers

Figure 18.1	Relationship of spaces in a data center	18-2
Figure 18.2	Hierarchical structure of a data center from CENELEC EN 50173-5 and ISO/IEC 11801-5	18-14
Figure 18.3	Example of TIA-942-B data center topology	18-15
Figure 18.4	Cabling cross-sectional area comparison	18-16
Figure 18.5	Example of equipment cabling using overhead infrastructure	18-19
Figure 18.6	Example of overhead communications cabling with power and bonding conductors beneath raised access floor	18-21
Figure 18.7	Example of communications, power, and earth conductors installed in raised access floor	18-22
Figure 18.8	Layering.	18-26

Chapter 19: Health Care

Figure 19.1	TDR.	19-5
Figure 19.2	Redundancy option 1.	19-6
Figure 19.3	Redundancy option 2.	19-7
Figure 19.4	Redundancy option 3.	19-8
Figure 19.5	Redundancy option 4.	19-9
Figure 19.6	Typical nurse call staff emergency station	19-12
Figure 19.7	Typical nurse call bedside station	19-13
Figure 19.8	Typical nurse call code call station.	19-14
Figure 19.9	Typical nurse call staff station.	19-15
Figure 19.10	Nurse call system traditional one-line diagram	19-18
Figure 19.11	Typical physiological monitor remote wiring diagram	19-29
Figure 19.12	Typical RFID tag	19-31
Figure 19.13	Typical IPTS	19-36

Chapter 20: Residential Cabling

Figure 20.1	Residential cabling layout.	20-4
Figure 20.2	Media room with one balanced twisted-pair and three coaxial cable runs to a telecommunications outlet	20-9
Figure 20.3	Example of a residential premises cabling system.	20-10
Figure 20.4	Multi-dwelling unit cabling layout	20-12
Figure 20.5	Telecommunications backbone and distribution cabling layout for an apartment building with a central backbone	20-13
Figure 20.6	Telecommunications backbone and distribution cabling layout for an apartment building with multiple backbones.	20-14
Figure 20.7	Example of conduit distribution for a seven-unit townhouse.	20-15
Figure 20.8	Cabling distribution for a side-by-side duplex residence.	20-16
Figure 20.9	Example of cable distribution for frame apartment projects	20-17
Figure 20.10	Example of an apartment complex with backbone cable	20-18
Figure 20.11	Telecommunications outlets/connectors	20-23

Chapter 21: Project Administration and Execution

Figure 21.1 Simple OBS 21-17

Figure 21.2 PERT or network logic diagram using the precedence diagram method 21-21

Figure 21.3 Milestone chart 21-21

Figure 21.4 Gantt chart 21-22

Figure 21.5 Calendar of schedule 21-22

Figure 21.6 Example of budgeted cost of work schedules 21-25

Figure 21.7 Example of plotted BCWP, BCWS, and ACWP 21-25

Figure 21.8 Client/supplier model 21-27

Figure 21.9 United States National CAD Standard® layer name format 21-53

Chapter 22: Special Design Considerations

Figure 22.1 Industrial floor area described by MICE classification 1, 2, or 3 22-6

Appendix A: Codes, Standards, Regulations, and Organizations

Figure A.1 Conformité européenne mark A-85

Figure A.2 Emission limits at 10 m (≈33 ft) A-89

Figure A.3 IEC CISPR 22 conducted disturbance limits (main ports) A-89

Figure A.4 IEC CISPR 22 conducted disturbance limits (telecommunications ports) A-90

Figure A.5 RJ11C/RJ11W connector configuration A-97

Figure A.6 RJ15C connector configuration A-98

Figure A.7 RJ16X connector configuration A-99

Figure A.8 RJ17C connector configuration A-101

Figure A.9 RJ18C, RJ18W connector configuration A-102

Figure A.10 RJ31X connector configuration A-103

Figure A.11 RJ14C/RJ14W connector configuration A-104

Figure A.12 RJ14X connector configuration A-105

Figure A.13 RJ25C connector configuration A-106

Figure A.14 RJ61X connector configuration A-107

Figure A.15 RJ2DX connector configuration A-108

Figure A.16 RJ2EX connector configuration A-109

Figure A.17 RJ2FX connector configuration A-110

Figure A.18 RJ2GX connector configuration A-111

Figure A.19 RJ2HX connector configuration A-112

Figure A.20 RJ21X connector configuration A-113

Figure A.21 RJ2MB connector configuration A-114

Figure A.22 RJ71C connector configuration A-115

Figure A.23 RJ41S single-line data connection A-117

Figure A.24 RJ45S single-line data connection A-118

Figure A.25 RJ4MB single-line data connection. A-119

Figure A.26 RJ41M single-line data connection. A-121

Figure A.27 RJ45M single-line data connection. A-123

Figure A.28 RJ26X single-line data connection A-124

Figure A.29 RJ27X single-line data connection A-125

Figure A.30 RJ48S connector configuration A-126

Figure A.31 RJ48T connector configuration A-127

Figure A.32 RJ48C connector configuration A-128

Figure A.33 RJ48M connector configuration A-129

Figure A.34 RJ48X connector configuration A-130

Figure A.35 RJ48H connector configuration A-131

Tables

Chapter 1: Principles of Transmission

Table 1.1	Conductor descriptions	1-3
Table 1.2	Solid conductor properties	1-4
Table 1.3	Electrical characteristics of common insulation types	1-7
Table 1.4	Explanations of insulation electrical characteristics	1-8
Table 1.5	Types of cable shields	1-15
Table 1.6	Common units of frequency measurement	1-18
Table 1.7	Spectrums of standard frequency bands	1-20
Table 1.8	Power ratios from 0 to 60 dB	1-21
Table 1.9	Transmission data rates	1-29
Table 1.10	Coding methods	1-35
Table 1.11	ADSL standards	1-43
Table 1.12	ADSL performance	1-44
Table 1.13	VDSL data rate and target range	1-44
Table 1.14	Propagation delay/delay skew	1-55
Table 1.15	Balanced twisted-pair cabling channel performance	1-64
Table 1.16	Applications supported using 100-ohm balanced twisted-pair cabling	1-65
Table 1.17	Media selection	1-67
Table 1.18	Transmission, speed, distance, and pair requirements	1-69
Table 1.19	IEEE 802.3 PoE classes	1-76
Table 1.20	Characteristics of typical LED sources	1-83
Table 1.21	Characteristics of typical short wavelength laser	1-84
Table 1.22	Characteristics of typical VCSELs	1-85
Table 1.23	Characteristics of typical LD sources	1-86
Table 1.24	Comparison of transmitters	1-87
Table 1.25	Optical fiber cable performance by type	1-90
Table 1.26	Summarized comparison of core sizes of multimode and singlemode optical fiber cable	1-98
Table 1.27	Typical characteristics of multimode optical fiber	1-99
Table 1.28	Characteristics of 50/125 μm multimode optical fiber	1-100
Table 1.29	Characteristics of 62.5/125 μm multimode optical fiber	1-101
Table 1.30	Typical characteristics of singlemode optical fiber	1-102
Table 1.31	Maximum cable attenuation coefficient	1-104
Table 1.32	Mismatch of core size and power loss	1-106
Table 1.33	Calculating optical fiber performance	1-108
Table 1.34	System gain, power penalties, and link loss budget calculations	1-111

Table 1.35	Calculating losses	1-112
Table 1.36	Splice loss values in decibels	1-113
Table 1.37	Minimum system loss	1-114
Table 1.38	Common SONET and SDH transmission rates	1-117
Table 1.39	Levels of multiplexing and carrier transmission in North America	1-123
Table 1.40	Levels of multiplexing and carrier transmission in Europe	1-125

Chapter 2: Electromagnetic Compatibility

Table 2.1	Factors that can affect EMI in telecommunications equipment	2-12
Table 2.2	Factors that can affect EMI in sites	2-13
Table 2.3	Four levels of immunity	2-19
Table 2.4	ESD susceptibility ranges	2-20
Table 2.5	Mutual capacitance ranges for telecommunications cables	2-21
Table 2.6	Minimum separation distances from possible sources of EMI exceeding 5 kVA	2-38
Table 2.7	Separation requirements between metallic cabling and specific EMI sources	2-38

Chapter 3: Telecommunications Spaces

Table 3.1	Size guidelines	3-11
Table 3.2	Smaller buildings	3-11
Table 3.3	Allocating termination space.	3-12
Table 3.4	Layout considerations	3-22

Chapter 4: Backbone Distribution Systems

Table 4.1	Backbone distribution system components.	4-1
Table 4.2	EFM installed singlemode optical fiber	4-20
Table 4.3	Common conduit sizes with vernacular	4-41
Table 4.4	Summary of EFM physical layer signaling systems	4-54

Chapter 5: Horizontal Distribution Systems

Table 5.1	Maximum allowable cable lengths with the use of multiuser telecommunications outlet assemblies.	5-28
Table 5.2	Comparison of CP locations	5-32
Table 5.3	PoE and HDBaseT current specifications.	5-37
Table 5.4	Primary PON variations and their source standards.	5-57
Table 5.5	Maximum channel attenuation and supported distance for PON versions.	5-60
Table 5.6	EMT 40 percent conduit fill rate	5-74
Table 5.7	Typical EMT conduit fill rate for varying cable diameters.	5-75
Table 5.8	Conduit fill with 1 bend	5-76

Table of Contents

Table 5.9	Conduit fill with 2 bends	5-77
Table 5.10	Bend radii guidelines	5-80
Table 5.11	Adapting designs	5-81
Table 5.12	Typical space requirements for pull boxes having conduit enter at opposite ends of the box	5-83
Table 5.13	Slip sleeves and gutters	5-84
Table 5.14	Coverings.	5-90
Table 5.15	Load capacity	5-90
Table 5.16	Guidelines for recommending ceiling panels	5-94
Table 5.17	Common types of cable trays	5-105
Table 5.18	Common cable tray dimensions	5-107
Table 5.19	ADA height requirements	5-120

Chapter 6: ICT Cables and Connecting Hardware

Table 6.1	Comparison of the terms class and category within ISO/IEC and TIA standards.	6-3
Table 6.2	Balanced twisted-pair cabling channel performance.	6-4
Table 6.3	Balanced twisted-pair cable designations	6-4
Table 6.4	Balanced cable designs	6-5
Table 6.5	Optical fiber cable transmission performance parameters.	6-15
Table 6.6	Typical distances supported by optical fiber cabling.	6-18
Table 6.7	Examples of regional fire safety standards	6-27
Table 6.8	Communications cable types	6-28
Table 6.9	Optical fiber cable types.	6-29
Table 6.10	Interclass relativity of <i>NEC</i> and IEC fire safety specifications	6-31
Table 6.11	Comparison between <i>NEC</i> CM ratings and CSA FT requirements	6-32
Table 6.12	Connecting hardware transmission performance categories for 110-style connector-based connecting hardware.	6-35
Table 6.13	Connecting hardware transmission performance categories	6-38
Table 6.14	Connecting hardware transmission performance categories for BIX-style connectors	6-40
Table 6.15	Connecting hardware transmission performance categories for LSA-style connector-based connecting hardware.	6-43
Table 6.16	Modular plug transmission performance categories	6-47
Table 6.17	Modular jack transmission performance categories	6-50
Table 6.18	50-position miniature ribbon connector transmission performance categories	6-53
Table 6.19	Optical fiber link transmission performance calculations worksheet.	6-78
Table 6.20	Splice insertion loss guidelines and objectives	6-86

Chapter 7: Firestop Systems

Table 7.1	Barrier standards	7-6
Table 7.2	European test standards	7-12
Table 7.3	Rating classifications, standards, and definitions.	7-13
Table 7.4	Limiting temperature for each test standard.	7-16
Table 7.5	Pipes, conduits, sleeve systems, innerducts, cable trays, and cable penetration firestop methods (in ceilings)	7-44
Table 7.6	Electrical apparatus, boxes, and access panels firestop methods (in ceilings)	7-45
Table 7.7	Pipes, conduits, sleeve systems, innerducts, cable trays, and cable penetration firestop methods (in floors/ceilings)	7-45
Table 7.8	Underfloor pipe, conduit, sleeve system, and innerduct firestop methods (in floors)	7-46
Table 7.9	Pipe sizes and fire ratings	7-71
Table 7.10	Sizes of pipe chokes, wrap strip layers, and fire ratings	7-91
Table 7.11	United States firestop standards	7-109
Table 7.12	Canadian firestop standards	7-111
Table 7.13	International firestop standards	7-112

Chapter 8: Bonding and Grounding (Earthing)

Table 8.1	Telecommunications bonding component terms cross-reference	8-2
Table 8.2	Basic guide to calculating bonding conductor resistance values.	8-21

Chapter 9: Power Distribution

Table 9.1	Electrical formulas.	9-14
Table 9.2	Circular mils of standard AWG conductors	9-16
Table 9.3	Voltage and current fluctuations	9-18
Table 9.4	K-rating based on load makeup	9-22
Table 9.5	Calculating maximum input current.	9-58
Table 9.6	Calculating voltage	9-60
Table 9.7	Major alarms (dc)	9-72
Table 9.8	Minor alarms (dc)	9-73
Table 9.9	Major alarms (UPS).	9-73
Table 9.10	Color code for conductors in the United States	9-77
Table 9.11	Color code for conductors in the United Kingdom and Ireland.	9-79

Chapter 10: Telecommunications Administration

Table 10.1	Required identifiers by class.	10-6
Table 10.2	Minimum and optional administration system elements	10-8
Table 10.3	Color codes	10-22
Table 10.4	Identifying pathways.	10-32
Table 10.5	Required records by class.	10-37

Chapter 11: Field Testing of Structured Cabling

Table 11.1 Determining worst-case attenuation coefficient. 11-23

Chapter 12: Outside Plant

Table 12.1 Service diversity 12-17
 Table 12.2 Terminating space 12-20
 Table 12.3 Vertical/horizontal separations 12-28
 Table 12.4 Metallic conduit types and sizes used in telecommunications 12-33
 Table 12.5 Direct-bury PVC conduit types and sizes used in telecommunications 12-34
 Table 12.6 Non-metallic conduit types and sizes used in telecommunications. 12-35

Chapter 13: Audiovisual Systems

Table 13.1 Color temperature ranges 13-9
 Table 13.2 Typical audio signal units of measurement 13-11
 Table 13.3 Common bit resolutions 13-14
 Table 13.4 Supported video formats 13-24
 Table 13.5 SDTV versus HDTV 13-26
 Table 13.6 Front and rear projection advantages and disadvantages. 13-41
 Table 13.7 Area covered by horns. 13-87
 Table 13.8 AI speech intelligibility. 13-95
 Table 13.9 Example of loss values per ≈ 30.5 m (100 ft) of the coaxial cable for the lowest and highest channels in a 60-channel system 13-107

Chapter 14: Building Automation Systems

Table 14.1 Typical work and BAS coverage area sizes 14-33

Chapter 16: Wireless Networks

Table 16.1 Balanced twisted-pair cabling channel performance. 16-21
 Table 16.2 Transceiver types and application 16-28

Chapter 18: Data Centers

Table 18.1 Comparison of the standards 18-10

Chapter 20: Residential Cabling

Table 20.1 Recognized tenant area residential cabling by grade 20-3
 Table 20.2 Guidance in planning the wall space allocated for DD and associated equipment 20-7
 Table 20.3 Telecommunications outlets/connectors for residences 20-9
 Table 20.4 Minimum space for a multi-dwelling unit CTR 20-11

Chapter 21: Project Administration and Execution

Table 21.1 *MasterFormat*[®] 2018 numbering 21-44

Chapter 22: Special Design Considerations

Table 22.1	List of applicable IEC test procedures	22-8
Table 22.2	IP codes.	22-10
Table 22.3	Enclosure ratings and IP codes	22-11
Table 22.4	Comparison of specific applications of enclosures for indoor non-hazardous locations	22-12

Appendix A: Codes, Standards, Regulations, and Organizations

Table A.1	Schematic of the relationships between standards	A-25
Table A.2	Key elements of the legal and regulatory framework of telecommunications sectors in select countries.	A-32
Table A.3	Schematic of the relationships between CENELEC standards	A-34
Table A.4	Sections of the <i>Canadian Electrical Code (CEC)</i>	A-46
Table A.5	Federal Communications Commission (FCC) documents.	A-58
Table A.6	<i>National Electrical Safety Code® (NESC®)</i> parts, sections, and rules applicable to telecommunications distribution requirements.	A-60
Table A.7	<i>National Electrical Code® (NEC®)</i> articles and sections that impact telecommunications installation	A-66
Table A.8	Federal Communications Commission (FCC) regulations	A-79
Table A.9	Class A radiation limits	A-87
Table A.10	Class B radiation limits	A-87
Table A.11	EN 61000-6-1 and EN 61000-6-2 generic standards	A-91
Table A.12	RJ11C/RJ11W connector configuration.	A-96
Table A.13	RJ15C connector configuration	A-98
Table A.14	RJ16X connector configuration	A-99
Table A.15	RJ17C connector configuration	A-100
Table A.16	RJ18C, RJ18W connector configuration	A-102
Table A.17	RJ31X connector configuration	A-103
Table A.18	RJ14C/RJ14W connector configuration.	A-104
Table A.19	RJ14X connector configuration	A-105
Table A.20	RJ25C connector configuration	A-106
Table A.21	RJ61X connector configuration	A-107
Table A.22	RJ2DX connector configuration	A-108
Table A.23	RJ2EX connector configuration	A-109
Table A.24	RJ2FX connector configuration	A-110
Table A.25	RJ2GX connector configuration	A-111
Table A.26	RJ2HX connector configuration	A-112
Table A.27	RJ21X connector configuration	A-113
Table A.28	RJ2MB connector configuration	A-114
Table A.29	RJ71C connector configuration	A-115
Table A.30	RJ41S single-line data connection	A-116

Table of Contents

Table A.31	RJ45S single-line data connection	A-118
Table A.32	RJ4MB single-line data connection.	A-119
Table A.33	RJ41M single-line data connection.	A-120
Table A.34	RJ45M single-line data connection.	A-122
Table A.35	RJ26X single-line data connection	A-124
Table A.36	RJ27X single-line data connection	A-125
Table A.37	RJ48S connector configuration	A-126
Table A.38	RJ48T connector configuration	A-127
Table A.39	RJ48C connector configuration	A-128
Table A.40	RJ48M connector configuration	A-129
Table A.41	RJ48X connector configuration	A-130
Table A.42	RJ48H connector configuration	A-131
Table A.43	Intermixable services at network-provided standard connectors	A-132
Table A.44	Facility interface code translator	A-135

Examples

Chapter 1: Principles of Transmission

Example 1.1	Optical fiber performance calculations example	1-109
-------------	--	-------

Chapter 14: Building Automation Systems

Example 14.1	SoW checklist.	14-26
--------------	------------------------	-------

Chapter 21: Project Administration and Execution

Example 21.1	WBS	21-19
Example 21.2	WBS in a text outline format.	21-20