



Guide to the installation, maintenance, testing and replacement of secondary batteries in buildings

Part 2: Sealed cells



AS 2676.2:2020

This Australian Standard® was prepared by EL-005, Secondary Batteries. It was approved on behalf of the Council of Standards Australia on 6 April 2020.

This Standard was published on 17 April 2020.

The following are represented on Committee EL-005:

- Australasian Fire and Emergency Service Authorities Council
- Australian Industry Group
- Clean Energy Council
- Communications, Electrical and Plumbing Union — Electrical Division
- Consumers Federation of Australia
- CSIRO
- Electrical Compliance Testing Association of Australia
- Electrical Regulatory Authorities Council
- Energy Networks Australia
- Energy Storage Council
- Engineers Australia
- International Copper Association Australia
- Joint Accreditation System of Australia & New Zealand
- Master Electricians Australia

This Standard was issued in draft form for comment as DR AS 2676.2:2018.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76072 813 7



Guide to the installation, maintenance, testing and replacement of secondary batteries in buildings

Part 2: Sealed cells

First published as AS 2676.2—1992.
This edition 2020.

COPYRIGHT

© Standards Australia Limited 2020

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Standards Australia Committee EL-005, Secondary batteries to supersede AS 2676.2—1992, *Guide to the installation, maintenance, testing and replacement of secondary batteries in building, Part 2: Sealed cells*.

The objective of this Standard is to set out minimum requirements and provide guidance for the installation, maintenance, testing and replacement of sealed secondary batteries (either valve-regulated or gastight) permanently installed in buildings, structures or premises.

It also provides guidance to determine when batteries should be replaced.

This Standard covers secondary batteries with a nominal voltage of 24 V or greater, and a capacity exceeding 10 A.h at the 1 h rate. It includes batteries comprising sealed lead-acid cells and alkaline cells (such as nickel-cadmium cells).

This Standard covers requirements for components of the d.c. system of which the battery is a part, where these components comprise an essential part of the d.c. system.

This Standard covers sealed cells only. The installation and maintenance of vented cells are covered by AS 3011.1 and AS 2676.1.

The major changes in this edition are as follows:

- (a) Scope aligned to complement AS/NZS 5139.
- (b) Important requirements established in text.
- (c) Battery terminal connection requirements aligned with AS 3011.2.
- (d) Battery protection requirements aligned with AS 3011.2.
- (e) Layout, location and ventilation requirements aligned with AS 3011.2.
- (f) Cell voltage test added to commissioning checks.
- (g) Requirement for safety signs for open flames and smoking removed.
- (h) Requirement for undefined emergency related signs removed.

The terms “normative” and “informative” are used in Standards to define the application of the appendices to which they apply. A “normative” appendix is an integral part of a Standard, whereas an “informative” appendix is only for information and guidance.

Contents

Preface	ii
Introduction	vi
1 Scope and general	1
1.1 Scope	1
1.2 Application	1
1.3 Normative references	1
1.4 Terms and definitions	1
2 Design considerations for direct current systems using batteries	5
2.1 General	5
2.2 Battery size and type (nominal voltage and rated capacity)	5
2.3 Method of connection	5
2.4 Operating conditions	6
2.5 Battery short-circuit current	6
2.6 Voltage drop	7
2.7 Connection between battery and direct current switchboard	7
2.7.1 General	7
2.7.2 Cables	7
2.7.3 Busbars	7
2.7.4 Busways	7
2.8 Direct current switchboards	8
2.9 Terminals and connectors	8
2.10 Direct current systems — earthing and earth-fault detection	8
2.11 Earth-fault location	9
2.12 Protection of batteries and direct current circuits	9
2.13 Alarms	9
2.14 Dual battery system	10
3 Battery accommodation	10
3.1 General	10
3.2 Layout and location	10
3.3 Ventilation	10
3.3.1 General	10
3.3.2 Rate of ventilation	10
3.3.3 Charging rate	11
3.3.4 Method of ventilation	11
3.4 Access	12
3.4.1 General	12
3.4.2 Battery rooms or areas restricted to authorized personnel	12
3.4.3 Battery enclosures	13
3.5 Floor loadings	13
3.6 Battery enclosure construction	13
3.7 Lighting and power	13
3.8 Safety signs	13
3.9 Arrangement of cells or monobloc	13
3.10 Battery stands	14
4 Charging	14
4.1 General	14
4.2 Charging parameters	14
4.3 Charging time	14
5 Installation and commissioning	14
5.1 Receipt inspection	14
5.2 Unpacking	15
5.3 Storage	15

5.4	Mounting and connection	15
5.5	Commissioning.....	16
5.5.1	Initial charge.....	16
5.5.2	Inter-cell voltage.....	16
5.5.3	Performance test.....	16
5.5.4	Cell voltage test.....	16
5.6	Records.....	16
6	Inspection and maintenance	16
6.1	Inspection.....	16
6.1.1	General.....	16
6.1.2	Test equipment.....	16
6.1.3	Inspection schedule.....	17
6.1.4	Performance tests.....	17
6.1.5	Abnormal conditions.....	18
6.2	Records.....	18
6.3	Pilot cells.....	18
6.4	Maintenance.....	18
6.4.1	Routine maintenance.....	18
6.4.2	Level of float voltage.....	18
6.4.3	Cell voltage.....	19
6.4.4	Cycling of nickel-cadmium batteries.....	19
7	Testing.....	19
7.1	General.....	19
7.2	Capacity test schedule.....	19
7.2.1	Performance.....	19
7.2.2	Service.....	19
7.3	Design considerations for a capacity tester.....	20
7.4	Procedure for battery capacity tests.....	20
7.4.1	Type of test.....	20
7.4.2	Initial conditions.....	20
7.4.3	Test duration.....	20
7.4.4	Performance test.....	20
7.4.5	Service test.....	20
7.5	Battery replacement criteria.....	21
8	Safety.....	21
8.1	General.....	21
8.2	Protective equipment.....	22
8.3	Safety signs.....	22
8.4	Precautions.....	22
8.4.1	General.....	22
8.4.2	During installation.....	22
8.4.3	During maintenance.....	23
8.5	Firefighting equipment.....	23
Appendix A (informative) A method of determining internal resistance		24
Appendix B (informative) Typical direct current system earthing.....		26
Appendix C (informative) Typical battery stands.....		28
Appendix D (informative) Typical direct current system using two batteries.....		30
Appendix E (normative) Initial charging and commissioning of sealed lead-acid batteries.....		31
Appendix F (normative) Initial charging and commissioning of sealed nickel-cadmium batteries.....		32
Appendix G (informative) Typical battery report sheet.....		34
Appendix H (normative) Performance test.....		36

Bibliography.....**39**

Introduction

Both the ampere-hour capacity and voltage of battery installations have increased to the point where some voltages now border on the medium and high voltage range. Even in extra-low voltage installations, the low internal resistances of batteries under short-circuit conditions can cause severe injuries to staff working on a battery or cell, or cause fire and explosion.

Tests have shown that batteries of 24 V d.c. and above may present problems in breaking fault currents and that additional precautions need to be taken to reduce the possibility of accidental short-circuits.

In preparing this Standard, the Committee considered the requirements of both sealed lead-acid cells and sealed alkaline cells.

Australian Standard®

Guide to the installation, maintenance, testing and replacement of secondary batteries in buildings

Part 2: Sealed cells

1 Scope and general

1.1 Scope

This Standard sets out requirements and provides guidance for the installation, maintenance, testing and replacement of sealed secondary batteries (either valve-regulated or gastight) permanently installed in buildings, structures or premises.

This Standard covers secondary batteries with a nominal voltage of 24 V or greater, and a capacity exceeding 10 A.h at the 1 h rate. It includes batteries comprising lead-acid cells and alkaline cells (such as nickel-cadmium cells).

This Standard covers requirements for components of the d.c. system of which the battery is a part, where these components comprise an essential part of the d.c. system.

This Standard covers sealed cells only. The installation and maintenance of vented cells are covered by AS 3011.1 and AS 2676.1.

NOTE 1 Requirements specifically applicable to the design and installation of extra-low voltage power supplies that are used by telecommunications carriers in the provision of public telecommunications networks are given in AS/NZS 3015.

NOTE 2 General installation and safety requirements for battery energy storage systems (BESSs) are given in AS/NZS 5139.

1.2 Application

This Standard is to be read in conjunction with AS 3011.2.

1.3 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document.

NOTE Documents for informative purposes are listed in the Bibliography.

AS 1170.4, *Minimum design loads on structures, Part 4 — Earthquake load*

AS 1319, *Safety signs for the occupational environment*

AS 3011.2, *Electrical installations — Secondary batteries installed in buildings, Part 2: Sealed cells*

AS/NZS 3000, *Electrical installations (known as the Australian/New Zealand Wiring Rules)*

AS/NZS 61439.1, *Low-voltage switchgear and controlgear assemblies, Part 1: General rules (IEC 61439-1, Ed. 2.0 (2011), MOD)*

1.4 Terms and definitions

For the purpose of this document, the following terms and definitions apply.