

Australian/New Zealand Standard™

**Mathematical expressions for reliability,
availability, maintainability and
maintenance support terms**



AS/NZS IEC 61703:2020

This Joint Australian/New Zealand Standard™ was prepared by Joint Technical Committee QR-005, Dependability. It was approved on behalf of the Council of Standards Australia on 22 April 2020 and by the New Zealand Standards Approval Board on 5 February 2020.

This Standard was published on 1 May 2020.

The following are represented on Committee QR-005:

- Asset Management Council (Australia)
- Australian Industry Group
- Department of Defence (Australian Government)
- Engineering New Zealand
- Engineers Australia
- Human Factors and Ergonomics Society of New Zealand
- Institution of Occupational Safety and Health
- National Rail Safety Regulator (Australia)
- National Road Carriers Association (New Zealand)
- New Zealand Institute of Safety Management
- Professionals Australia
- Risk Engineering Society (Australia)
- Risk Management Institute of Australasia
- RiskNZ
- University of New South Wales
- University of Western Australia
- University of Wollongong

This Standard was issued in draft form for comment as DR AS/NZS IEC 61703:2019.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

www.standards.govt.nz

ISBN 978 1 76072 831 1

Australian/New Zealand Standard™

**Mathematical expressions for reliability,
availability, maintainability and
maintenance support terms**

First published as AS/NZS IEC 61703:2020.

COPYRIGHT

© IEC 2020 — All rights reserved

© Standards Australia Limited/the Crown in right of New Zealand, administered by the New Zealand Standards Executive 2020

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth) or the Copyright Act 1994 (New Zealand).

Preface

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee QR-005, Dependability.

The objective of this Standard is to provide mathematical expressions for selected reliability, availability, maintainability and maintenance support measures defined in IEC 60050-192:2015. In addition, it introduces some terms not covered in IEC 60050-192:2015. They are related to aspects of the system of item classes (see hereafter).

According to IEC 60050-192:2015, dependability [192-01-22] is the ability of an item to perform as and when required and an item [192-01-01] can be an individual part, component, device, functional unit, equipment, subsystem, or system.

To account for mathematical constraints, this Standard splits the items between the individual items considered as a whole (e.g. individual components) and the systems made of several individual items. It provides general considerations for the mathematical expressions for systems as well as individual items but the individual items which are easier to model are analysed in more detail with regards to their repair aspects.

The following item classes are considered separately:

- (a) Systems;
- (b) Individual items —
 - (i) non-repairable [192-01-12];
 - (ii) repairable [192-01-11] —
 - (A) with zero (or negligible) time to restoration;
 - (B) with non-zero time to restoration.

In order to explain the dependability concepts which can be difficult to understand, keep the Standard self-contained and the mathematical formulae as simple as possible, the following basic mathematical models are used in this standard to quantify dependability measures:

- (i) Systems —
 - (A) state-transition models;
 - (B) Markovian models.
- (ii) Individual items —
 - (A) random variable (time to failure) for non-repairable items;
 - (B) simple (ordinary) renewal process for repairable items with zero time to restoration;
 - (C) simple (ordinary) alternating renewal process for repairable items with non-zero time to restoration.

The application of each dependability measure is illustrated by means of simple examples.

This Standard is mainly applicable to hardware dependability, but many terms and their definitions may be applied to items containing software.

This Standard is identical with, and has been reproduced from, IEC 61703:2016, *Mathematical expressions for reliability, availability, maintainability and maintenance support terms*.

As this document has been reproduced from an International Standard, the following applies:

- (A) In the source text “this International Standard” should read “this Australian/New Zealand Standard”.
- (B) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

CONTENTS

FOREWORD.....	6
INTRODUCTION.....	8
1 Scope.....	9
2 Normative references.....	10
3 Terms and definitions	10
4 Glossary of symbols and abbreviations	13
4.1 General.....	13
4.2 Acronyms used in this standard	13
4.3 Symbols used in this standard	15
5 General models and assumptions	18
5.1 Constituents of up and down times	18
5.2 Introduction to models and assumptions	19
5.3 State-transition approach	20
5.4 Model and assumptions for non-repairable individual items	22
5.5 Assumptions and model for repairable individual items.....	23
5.5.1 Assumption for repairable individual items	23
5.5.2 Instantaneous repair	24
5.5.3 Non-instantaneous repair	25
5.6 Continuously operating items (COI) versus intermittently operating individual items (IOI).....	26
6 Mathematical models and expressions	27
6.1 Systems.....	27
6.1.1 General	27
6.1.2 Availability related expressions	29
6.1.3 Reliability related expressions	36
6.1.4 Mean operating time between failures [192-05-13] and mean time between failures.....	40
6.1.5 Instantaneous failure rate [192-05-06] and conditional failure intensity (Vesely failure rate).....	41
6.1.6 Failure density and unconditional failure intensity [192-05-08].....	44
6.1.7 Comparison of $\lambda(t)$, $\lambda_V(t)$, $z(t)$ and $f(t)$ for high and small MTTRs	47
6.1.8 Restoration related expressions	47
6.2 Non-repairable individual items.....	49
6.2.1 General	49
6.2.2 Instantaneous availability [192-08-01].....	50
6.2.3 Reliability [192-05-05]	50
6.2.4 Instantaneous failure rate [192-05-06]	51
6.2.5 Mean failure rate [192-05-07]	52
6.2.6 Mean operating time to failure [192-05-11].....	53
6.3 Repairable individual items with zero time to restoration	54
6.3.1 General	54
6.3.2 Reliability [192-05-05].....	54
6.3.3 Instantaneous failure intensity [192-05-08].....	56
6.3.4 Asymptotic failure intensity [192-05-10]	58
6.3.5 Mean failure intensity [192-05-09].....	59
6.3.6 Mean time between failures (see 3.3)	60

6.3.7	Mean operating time to failure [192-05-11].....	60
6.3.8	Mean operating time between failures [192-05-13]	61
6.3.9	Instantaneous availability [192-08-01], mean availability [192-08-05] and asymptotic availability [192-08-07]	61
6.3.10	Mean up time [192-08-09]	61
6.4	Repairable individual items with non-zero time to restoration.....	62
6.4.1	General	62
6.4.2	Reliability [192-05-05]	62
6.4.3	Instantaneous failure intensity [192-05-08].....	64
6.4.4	Asymptotic failure intensity [192-05-10]	67
6.4.5	Mean failure intensity [192-05-09].....	68
6.4.6	Mean operating time to failure [192-05-11].....	69
6.4.7	Mean time between failures (see 3.3)	70
6.4.8	Mean operating time between failures [192-05-13]	71
6.4.9	Instantaneous availability [192-08-01].....	71
6.4.10	Instantaneous unavailability [192-08-04].....	73
6.4.11	Mean availability [192-08-05].....	74
6.4.12	Mean unavailability [192-08-06].....	76
6.4.13	Asymptotic availability [192-08-07]	78
6.4.14	Asymptotic unavailability [192-08-08].....	78
6.4.15	Mean up time [192-08-09]	79
6.4.16	Mean down time [192-08-10]	81
6.4.17	Maintainability [192-07-01]	82
6.4.18	Instantaneous repair rate [192-07-20].....	84
6.4.19	Mean repair time [192-07-21]	86
6.4.20	Mean active corrective maintenance time [192-07-22].....	87
6.4.21	Mean time to restoration [192-07-23]	88
6.4.22	Mean administrative delay [192-07-26]	89
6.4.23	Mean logistic delay [192-07-27].....	90
Annex A (informative)	Performance aspects and descriptors	91
Annex B (informative)	Summary of measures related to time to failure	92
Annex C (informative)	Comparison of some dependability measures for continuously operating items.....	95
Bibliography	97
Figure 1	– Constituents of up time	18
Figure 2	– Constituents of down time.....	19
Figure 3	– Acronyms related to failure times	19
Figure 4	– Simple state-transition diagram.....	21
Figure 5	– Sample realization (chronogram) related to the system in Figure 4	22
Figure 6	– State-transition diagram of a non-repairable individual item	22
Figure 7	– Sample realization of a non-repairable individual item	23
Figure 8	– State-transition diagram of an instantaneously repairable individual item	24
Figure 9	– Sample realization of a repairable individual item with zero time to restoration	25
Figure 10	– State-transition diagram of a repairable individual item.....	25

Figure 11 – Sample realization of a repairable individual item with non-zero time to restoration26

Figure 12 – Comparison of an enabled time for a COI and an IOI.....26

Figure 13 – Equivalent operating time for IOI items.....27

Figure 14 – State-transition graph for a simple redundant system27

Figure 15 – Markov graph for a simple redundant system28

Figure 16 – Evolution of the state probabilities related to the Markov model in Figure 1528

Figure 17 – Evolution of $A(t)$ and $U(t)$ related to the Markov model in Figure 15.....29

Figure 18 – Evolution of the $Ast_i(0, t)$ related to the Markov model in Figure 1531

Figure 19 – Instantaneous availability and mean availability of a periodically tested item33

Figure 20 – Example of a simple production system.....34

Figure 21 – Evolution of $A(t)$ and $K(t)$ 35

Figure 22 – Illustration of a system reliable behaviour over $[0, t]$ 36

Figure 23 – Illustration of a system reliable behaviour over time interval $[t_1, t_2]$37

Figure 24 – State-transition and Markov graphs for reliability calculations37

Figure 25 – Evolution of the state probabilities related to the Markov model in Figure 2438

Figure 26 – Evolution of $R(t)$ and $F(t)$ related to the Markov model in Figure 2439

Figure 27 – Evolution of $Ast_i(0, t)$ related to the Markov model in Figure 24.....40

Figure 28 – Time between failures versus operating time between failures40

Figure 29 – Comparison between $\lambda(t)$ and $\lambda_V(t)$ related to the model in Figure 2443

Figure 30 – Comparison between $z(t)$ and $f(t)$ 46

Figure 31 – Comparison of $\lambda(t)$, $\lambda_V(t)$, $z(t)$ and $f(t)$ for high and small values of MTTRs.....47

Figure 32 – Illustration of reliable behaviour over $[t_1, t_2]$ for a zero time to restoration individual item55

Figure 33 – Sample of possible number of failures at the renewal time t56

Figure 34 – Illustration of reliable behaviour over $[t_1, t_2]$ for a non-zero time to restoration individual item62

Figure 35 – Evolution of $R(t, t + 1/4)$ 64

Figure 36 – Sample of possible number of failures at the renewal time t64

Figure 37 – Evolution of the failure intensity $z(t)$ 66

Figure 38 – Evolution of the mean failure intensity $z(t, t + 1/4)$69

Figure 39 – Illustration of available behaviour at time t for a non-zero time to restoration individual item71

Figure 40 – Evolution of the instantaneous availability $A(t)$73

Figure 41 – Illustration of unavailable behaviour at time t for a non-zero time to restoration individual item73

Figure 42 – Evolution of the instantaneous unavailability $U(t)$74

Figure 43 – Evolution of the mean availability $\bar{A}(t, t + 1/4)$ 76

Figure 44 – Evolution of the mean unavailability $\bar{U}(t, t + 1/4)$ 77

Figure 45 – Sample realization of the individual item state80

Figure 46 – Plot of the up-time hazard rate function $\lambda_U(t)$ 80

Figure 47 – Evolution of the maintainability $M(t, t + 16h)$84

Figure 48 – Evolution of the lognormal repair rate $\mu(t)$ 86

Figure A.1 – Performance aspects and descriptors	91
Table B.1 – Relations among measures related to time to failure of continuously operating items	92
Table B.2 – Summary of characteristics for some continuous probability distributions of time to failure of continuously operating items	93
Table B.3 – Summary of characteristics for some probability distributions of repair time	94
Table C.1 – Comparison of some dependability measures of continuously operating items with constant failure rate λ and restoration rate μ_R	95

INTERNATIONAL ELECTROTECHNICAL COMMISSION

MATHEMATICAL EXPRESSIONS FOR RELIABILITY, AVAILABILITY, MAINTAINABILITY AND MAINTENANCE SUPPORT TERMS

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61703 has been prepared by IEC technical committee 56: Dependability.

This second edition cancels and replaces the first edition published in 2001. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- a) standard made as self containing as possible;
- b) item split between individual items and systems;
- c) generalization of the dependability concepts for systems made of several components;
 - introduction of the conditional failure intensity (Vesely failure rate);
 - introduction of the state-transition and the Markovian models;

- generalization of the availability to production availability;
- d) introduction of curves to illustrate the various concepts.

The text of this standard is based on the following documents:

FDIS	Report on voting
56/1682/FDIS	56/1693/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

This International Standard is to be used in conjunction with IEC 60050-192:2015.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

IEC 60050-192 provides definitions for dependability and its influencing factors, reliability, availability, maintainability and maintenance support, together with definitions of other related terms commonly used in this field. Some of these terms are measures of specific dependability characteristics, which can be expressed mathematically.

It is important for the users to understand the mathematical meaning of those expressions and how they are established. This is the purpose of the present International Standard which, used in conjunction with IEC 60050-192, provides practical guidance essential for the quantification of those measures. For those requiring further information, for example on detailed statistical methods, reference should be made to the IEC 60605 series [23]¹.

Annex A provides a diagrammatic explanation of the relationships between some basic dependability terms, related random variables, probabilistic descriptors and modifiers.

Annex B provides a summary of measures related to time to failure.

Annex C compares some dependability measures for continuously operating items.

The bibliography gives references for the mathematical basis of this standard, in particular, the mathematical material is based on references [2], [6], [8], [9], [13], [14] and [18]; the renewal theory (renewal and alternating renewal processes) can be found in [6], [8], [9], [10], [11], [13], [15], and [17]; and more advanced treatment of renewal theory can be found in references [1], [3], [12], [16], [19] and [20]. More information on the theory and applications of Markov processes can be found in references [3], [9], [10], [15], [16], [17] and [19].

¹ Numbers in brackets refer to the Bibliography.

MATHEMATICAL EXPRESSIONS FOR RELIABILITY, AVAILABILITY, MAINTAINABILITY AND MAINTENANCE SUPPORT TERMS

1 Scope

This International Standard provides mathematical expressions for selected reliability, availability, maintainability and maintenance support measures defined in IEC 60050-192:2015. In addition, it introduces some terms not covered in IEC 60050-192:2015. They are related to aspects of the system of item classes (see hereafter).

According to IEC 60050-192:2015, dependability [192-01-22] is the ability of an item to perform as and when required and an item [192-01-01] can be an individual part, component, device, functional unit, equipment, subsystem, or system.

To account for mathematical constraints, this standard splits the items between the individual items considered as a whole (e.g. individual components) and the systems made of several individual items. It provides general considerations for the mathematical expressions for systems as well as individual items but the individual items which are easier to model are analysed in more detail with regards to their repair aspects.

The following item classes are considered separately:

- Systems;
- Individual items:
 - non-repairable [192-01-12];
 - repairable [192-01-11]:
 - i) with zero (or negligible) time to restoration;
 - ii) with non-zero time to restoration.

In order to explain the dependability concepts which can be difficult to understand, keep the standard self-contained and the mathematical formulae as simple as possible, the following basic mathematical models are used in this standard to quantify dependability measures:

- Systems:
 - state-transition models;
 - Markovian models.
- Individual items:
 - random variable (time to failure) for non-repairable items;
 - simple (ordinary) renewal process for repairable items with zero time to restoration;
 - simple (ordinary) alternating renewal process for repairable items with non-zero time to restoration.

The application of each dependability measure is illustrated by means of simple examples.

This standard is mainly applicable to hardware dependability, but many terms and their definitions may be applied to items containing software.