

ACI 549.4R-20

IN-LB

Inch-Pound Units

SI

International System of Units

Guide to Design and Construction of Externally Bonded Fabric-Reinforced Cementitious Matrix and Steel-Reinforced Grout Systems for Repair and Strengthening of Concrete Structures

Reported by ACI Committee 549



American Concrete Institute
Always advancing



Guide to Design and Construction of Externally Bonded Fabric-Reinforced Cementitious Matrix and Steel-Reinforced Grout Systems for Repair and Strengthening of Concrete Structures

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised the ACI Collection of Concrete Codes, Specifications, and Practices.

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
Phone: +1.248.848.3700
Fax: +1.248.848.3701

www.concrete.org

Guide to Design and Construction of Externally Bonded Fabric-Reinforced Cementitious Matrix and Steel-Reinforced Grout Systems for Repair and Strengthening of Concrete Structures

Reported by ACI Committee 549

Antonio Nanni, Chair

Corina-Maria Aldea, Secretary

Nemkumar Banthia
Christian Carloni
Paolo Casadei
Gianmarco de Felice
Michael E. Driver

Ashish Dubey
Usama A. Ebead
Mahmut Ekenel
Brad L. Erickson
Garth J. Fallis

Houman Akbari Hadad
Barzin Mobasher
Hani H. Nassif
Bekir Yilmaz Pekmezci
Alva Peled

Larry Rowland
Surendra P. Shah
Yixin Shao
Lesley H. Sneed
J. Gustavo Tumialan

Consulting Members

Gordon B. Batson
James I. Daniel

John Jones
Antoine E. Naaman

Paul Nedwell
P. Paramasivam

Parviz Soroushian

Fabric-reinforced cementitious matrix (FRCM) and steel-reinforced grout (SRG) systems for rehabilitation and strengthening concrete structures is an alternative to traditional techniques such as fiber-reinforced polymers (FRPs), steel plate bonding, section enlargement, and external post-tensioning. An FRCM/SRG is a composite material consisting of one or more layers of inorganic matrix reinforced with dry fibers in the form of open mesh or fabric. The inorganic matrixes are typically cement-based, lime-based, or geopolymer. When adhered to concrete structural members, they form an FRCM/SRG system that acts as supplemental, externally bonded reinforcement. This guide addresses the history and use of FRCM and SRG systems rehabilitation and strengthening, their unique material properties, and recommendations on their design, construction, and inspection. Guidelines are based on experimental research, analytical work, and field applications.

Keywords: cyclic loading; deflection; earthquake-resistant; fabric-reinforced cementitious matrix fatigue systems; fiber-reinforced polymer systems; lap splices; meshes; substrate repair; rehabilitation; surface preparation.

CONTENTS

CHAPTER 1—INTRODUCTION AND SCOPE, p. 2

- 1.1—Introduction, p. 2
- 1.2—Scope, p. 2

CHAPTER 2—NOTATION AND DEFINITIONS, p. 2

- 2.1—Notation, p. 2
- 2.2—Definitions, p. 3

CHAPTER 3—BACKGROUND, p. 4

- 3.1—FRCM and SRG systems features, p. 4
- 3.2—Background, p. 4
- 3.3—Commercially available FRCM/SRG systems, p. 12

CHAPTER 4—FIELD APPLICATION EXAMPLES, p. 12

- 4.1—Concrete repair applications, p. 13

ACI Committee Reports, Guides, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

ACI 549.4R-20 supersedes ACI 549.4R-13 and was adopted and published April 2020.

Copyright © 2020, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

CHAPTER 5—FRCM AND SRG CONSTITUENT MATERIALS AND SYSTEM QUALIFICATIONS, p. 16

- 5.1—Constituent materials, p. 16
- 5.2—FRCM and SRG system qualifications, p. 17
- 5.3—Physical and mechanical properties of FRCM/SRG, p. 17
- 5.4—Durability, p. 18

CHAPTER 6—SHIPPING, STORAGE, AND HANDLING, p. 18

- 6.1—Shipping, p. 18
- 6.2—Storage, p. 18
- 6.3—Handling, p. 18

CHAPTER 7—INSTALLATION, p. 19

- 7.1—Contractor qualifications, p. 19
- 7.2—Environmental considerations, p. 19
- 7.3—Equipment, p. 19
- 7.4—Substrate repair and surface preparation, p. 19
- 7.5—Mixing of mortar matrix, p. 20
- 7.6—Application of FRCM/SRG systems, p. 20
- 7.7—Alignment of FRCM/SRG reinforcement, p. 20
- 7.8—Multiple fabrics and lap splices, p. 20
- 7.9—Curing of mortar matrix, p. 20
- 7.10—Temporary protection, p. 20

CHAPTER 8—INSPECTION, EVALUATION, AND ACCEPTANCE, p. 20

- 8.1—Inspection, p. 20
- 8.2—Evaluation and acceptance, p. 21

CHAPTER 9—MAINTENANCE AND REPAIR, p. 22

- 9.1—General, p. 22
- 9.2—Inspection and assessment, p. 22
- 9.3—Repair of strengthening system, p. 22
- 9.4—Repair of surface coating, p. 22

CHAPTER 10—GENERAL DESIGN CONSIDERATIONS FOR REINFORCED CONCRETE STRENGTHENED WITH FRCM/SRG, p. 22

- 10.1—Design philosophy, p. 22
- 10.2—Strengthening limits, p. 22
- 10.3—Selection of FRCM/SRG system, p. 22
- 10.4—Design properties, p. 22

CHAPTER 11—FRCM/SRG REINFORCEMENT DETAILS, p. 22

- 11.1—Bond and delamination, p. 23

CHAPTER 12—STRENGTHENING OF REINFORCED CONCRETE MEMBERS WITH FRCM/SRG, p. 23

- 12.1—FRCM/SRG flexural strengthening, p. 23
- 12.2—Shear strengthening, p. 24
- 12.3—Strengthening for axial force, p. 25
- 12.4—Design axial strength, p. 27
- 12.5—Engineering requirements, p. 27
- 12.6—Drawings and specifications, p. 27

- 12.7—Submittals, p. 27

CHAPTER 13—REFERENCES, p. 27

- Authored documents, p. 28

APPENDIX A—CONSTITUENT MATERIALS PROPERTIES OF COMMERCIALY AVAILABLE FRCM SYSTEMS, p. 34**APPENDIX B—DESIGN LIMITATIONS, p. 36****CHAPTER 1—INTRODUCTION AND SCOPE****1.1—Introduction**

Fabric-reinforced cementitious matrix (FRCM) and steel-reinforced grout (SRG) composites have recently emerged as a viable technology for rehabilitation and strengthening concrete structures. The strengthening and rehabilitation of existing concrete structures has traditionally been accomplished using new and conventional materials and construction techniques, including externally bonded fiber-reinforced polymer (FRP) systems, steel plates, reinforced concrete (RC) overlays, and post-tensioning.

The primary reasons for considering FRCM/SRG as a suitable strengthening material system are from the inorganic matrix that shows properties of:

- a) Inherent heat resistance
- b) Compatibility with the substrate (that is, allows vapor permeability and application on a wet surface)
- c) Long-term durability

FRCM and SRG are systems where all constituents are developed and tested as a unique combination and should not be created by randomly selecting and mixing products available in the marketplace.

AC434 establishes guidelines for the manufacturers for necessary tests and calculations required to receive a product research report from ICC-ES. Once received, the evaluated system can be accepted by code officials under Section 104.11.1 of the International Building Code (IBC 2018). Section 104.11.1 allows research reports to be used as a source of information to show building code compliance of alternative materials.

1.2—Scope

This guide covers fabric-reinforced cementitious matrix (FRCM) and steel-reinforced grout (SRG) composite systems used to strengthen or rehabilitate existing concrete structures, providing background information and field applications; composite material properties; axial, flexural, and shear capacities of the FRCM/SRG-strengthened structures; and structural design procedures.

CHAPTER 2—NOTATION AND DEFINITIONS**2.1—Notation**

A_c = net cross-sectional area of compression member, in.² (mm²)

A_e = area of effectively confined concrete, in.² (mm²)