

AS/NZS CISPR 16.1.4:2020



Australian/New Zealand Standard™

Specification for radio disturbance and immunity measuring apparatus and methods

**Part 1.4: Radio disturbance and immunity measuring apparatus —
Antennas and test sites for radiated disturbance measurements (CISPR
16-1-4:2019 (ED 4.0) MOD)**



AS/NZS CISPR 16.1.4:2020

This Joint Australian/New Zealand Standard™ was prepared by Joint Technical Committee TE-003, Electromagnetic Compatibility. It was approved on behalf of the Council of Standards Australia on 30 July 2020 and by the New Zealand Standards Approval Board on 2 September 2020.

This Standard was published on 25 September 2020.

The following are represented on Committee TE-003:

- Australian Broadcasting Corporation
- Australian Communications and Media Authority
- Australian Industry Group
- Australian Information Industry Association
- Consumer Electronics Suppliers Association
- Department of Defence (Australian Government)
- Electrical Compliance Testing Association of Australia
- EMC Society of Australia
- Energy Networks Australia
- Engineers Australia
- Free TV Australia
- Lighting Council New Zealand
- Ministry of Business, Innovation and Employment (NZ)
- National Measurement Institute
- Wireless Institute Australia

This Standard was issued in draft form for comment as DR AS/NZS CISPR 16.1.4:2020.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

www.standards.govt.nz

ISBN 978 1 76072 982 0

Australian/New Zealand Standard™

Specification for radio disturbance and immunity measuring apparatus and methods

**Part 1.4: Radio disturbance and immunity
measuring apparatus — Antennas and test sites
for radiated disturbance measurements (CISPR
16-1-4:2019 (ED 4.0) MOD)**

Originated as AS/NZS CISPR 16.1.4:2004.
Previous edition AS/NZS CISPR 16.1.4:2013.
Fifth edition 2020.



© IEC 2020 — All rights reserved

© Standards Australia Limited/the Crown in right of New Zealand, administered by the New Zealand Standards Executive 2020

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of either the IEC or the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth). If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please see the contact details on the back cover or the contact us page of the website for further information.

Preface

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee TE-003, Electromagnetic Compatibility, to supersede AS/NZS CISPR 16.1.4:2013, *Specification for radio disturbance and immunity measuring apparatus and methods, Part 1.4: Radio disturbance and immunity measuring apparatus — Antennas and test sites for radiated disturbance measurements*.

The objective of this document is to specify the characteristics and performance of equipment for the measurement of radiated disturbances in the frequency range 9 kHz to 18 GHz. Specifications for antennas and test sites are included.

The requirements of this document apply at all frequencies and for all levels of radiated disturbances within the CISPR indicating range of the measuring equipment.

Methods of measurement are covered in AS/NZS CISPR 16.2.3, further information on radio disturbance is given in AS/NZS CISPR 16.3, and uncertainties, statistics and limit modelling are covered in sub-parts of AS/NZS CISPR 16.4.

This document is an adoption with national modifications, and has been reproduced from, CISPR 16-1-4:2019, *Specification for radio disturbance and immunity measuring apparatus and methods — Part 1-4: Radio disturbance and immunity measuring apparatus — Antennas and test sites for radiated disturbance measurements*. The modifications are additional requirements and are set out in Appendix ZZ, which has been added at the end of the source text.

Appendix ZZ lists the variations to the normative references list for the application of this Standard in Australia and New Zealand.

This document is structured as follows:

- (a) Preface.
- (b) CISPR 16-1-4:2019 (unedited from the contents page to the final clause of the source document).
- (c) Appendix ZZ—Australian/New Zealand variations to the source document.

As this document has been reproduced from an International Standard, the following applies:

- (i) In the source text “this part of CISPR 16” should read “this document”.
- (ii) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

NOTES

CONTENTS

FOREWORD.....	8
1 Scope.....	10
2 Normative references.....	10
3 Terms, definitions and abbreviated terms.....	11
3.1 Terms and definitions.....	11
3.2 Abbreviated terms.....	15
4 Antennas for measurement of radiated radio disturbance.....	16
4.1 General.....	16
4.2 Physical parameter (measurand) for radiated disturbance measurements.....	16
4.3 Antennas for the frequency range 9 kHz to 150 kHz.....	17
4.3.1 General.....	17
4.3.2 Magnetic field antenna.....	17
4.3.3 Shielding of loop antenna.....	17
4.4 Antennas for the frequency range 150 kHz to 30 MHz.....	17
4.4.1 Electric field antenna.....	17
4.4.2 Magnetic field antenna.....	18
4.4.3 Balance and electric field discrimination of antennas.....	18
4.5 Antennas for the frequency range 30 MHz to 1 000 MHz.....	18
4.5.1 General.....	18
4.5.2 Low-uncertainty antenna for use if there is an alleged non-compliance to the electric disturbance field strength limit.....	18
4.5.3 Antenna characteristics.....	18
4.5.4 Balance of antenna.....	20
4.5.5 Cross-polar response of antenna.....	22
4.6 Antennas for the frequency range 1 GHz to 18 GHz.....	23
4.6.1 General.....	23
4.6.2 Receive antenna.....	23
4.7 Special antenna arrangements – large-loop antenna system.....	25
5 Test sites for measurement of radio disturbance field strength for the frequency range of 9 kHz to 30 MHz.....	25
6 Test sites for measurement of radio disturbance field strength for the frequency range of 30 MHz to 1 000 MHz.....	26
6.1 General.....	26
6.2 OATS.....	26
6.2.1 General.....	26
6.2.2 Weather-protection enclosure.....	26
6.2.3 Obstruction-free area.....	26
6.2.4 Radio-frequency ambient environment of a test site.....	27
6.2.5 Ground plane.....	28
6.3 Suitability of other test sites.....	28
6.3.1 Other ground-plane test sites.....	28
6.3.2 Test sites without ground plane (FAR).....	28
6.4 Test site validations.....	29
6.4.1 General.....	29
6.4.2 Overview of test site validations.....	30
6.5 Basic parameters of the NSA method for OATS and SAC.....	30
6.5.1 General equation and table of theoretical NSA values.....	30

6.5.2	Antenna calibration	34
6.6	Reference site method for OATS and SAC	34
6.6.1	General.....	34
6.6.2	Antennas not permitted for RSM measurements	35
6.6.3	Determination of the antenna pair reference site attenuation on a REFTS.....	35
6.6.4	Determination of the antenna pair reference site attenuation using an averaging technique on a large OATS	36
6.7	Validation of an OATS by the NSA method	39
6.7.1	Discrete frequency method.....	39
6.7.2	Swept frequency method	40
6.8	Validation of a weather-protection-enclosed OATS or a SAC.....	41
6.9	Possible causes for exceeding site acceptability limits	43
6.10	Site validation for FARs	44
6.10.1	General.....	44
6.10.2	RSM for FAR sites	48
6.10.3	NSA method for FAR sites.....	50
6.10.4	Site validation criteria for FAR sites	52
6.11	Evaluation of set-up table and antenna tower.....	52
6.11.1	General.....	52
6.11.2	Evaluation procedure for set-up table influences.....	53
7	Test sites for measurement of radio disturbance field strength for the frequency range 1 GHz to 18 GHz.....	54
7.1	General.....	54
7.2	Reference test site	55
7.3	Test site validation	55
7.3.1	General.....	55
7.3.2	Acceptance criterion for site validation.....	56
7.4	Antenna requirements for S_{VSWR} standard test procedure.....	56
7.4.1	General.....	56
7.4.2	Transmit antenna	57
7.4.3	Antennas and test equipment for the S_{VSWR} reciprocal test procedure	59
7.5	Required positions for site validation testing	60
7.5.1	General.....	60
7.5.2	Descriptions of S_{VSWR} measurement positions in a horizontal plane (Figure 23).....	60
7.5.3	Descriptions of S_{VSWR} additional measurement positions (Figure 24).....	61
7.5.4	Summary of S_{VSWR} measurement positions	62
7.6	S_{VSWR} site validation – standard test procedure.....	65
7.7	S_{VSWR} site validation – reciprocal test procedure using an isotropic field probe	66
7.8	S_{VSWR} conditional measurement position requirements.....	67
7.9	S_{VSWR} site validation test report	68
7.10	Limitations of the S_{VSWR} site validation method	68
7.11	Alternative test sites.....	69
8	Common mode absorption devices.....	69
8.1	General.....	69
8.2	CMAD S -parameter measurements.....	69
8.3	CMAD test jig.....	69
8.4	Measurement method using the TRL calibration.....	70

8.5	Specification of ferrite clamp-type CMAD	72
8.6	CMAD performance (degradation) check using spectrum analyzer and tracking generator	73
9	Reverberating chamber for total radiated power measurement	75
9.1	General.....	75
9.2	Chamber.....	75
9.2.1	Chamber size and shape.....	75
9.2.2	Door, openings in walls, and mounting brackets	75
9.2.3	Stirrers.....	76
9.2.4	Test for the efficiency of the stirrers	76
9.2.5	Coupling attenuation	77
10	TEM cells for immunity to radiated disturbance measurement.....	78
Annex A (normative)	Parameters of antennas.....	79
A.1	General.....	79
A.2	Preferred antennas	79
A.2.1	General.....	79
A.2.2	Calculable antenna.....	79
A.2.3	Low-uncertainty antennas.....	79
A.3	Simple dipole antennas	80
A.3.1	General.....	80
A.3.2	Tuned dipole	81
A.3.3	Shortened dipole	81
A.4	Broadband antenna parameters.....	82
A.4.1	General.....	82
A.4.2	Antenna type.....	83
A.4.3	Specification of the antenna	83
A.4.4	Antenna calibration	84
A.4.5	Antenna user information	84
Annex B (XXX)	(Void).....	85
Annex C (normative)	Large-loop antenna system for magnetic field induced-current measurements in the frequency range of 9 kHz to 30 MHz.....	86
C.1	General.....	86
C.2	Construction of an LLAS.....	86
C.3	Construction of a large-loop antenna (LLA).....	86
C.4	Validation of an LLA	91
C.5	Construction of the LLAS verification dipole antenna.....	92
C.6	Conversion factors	93
Annex D (normative)	Construction details for open area test sites in the frequency range of 30 MHz to 1 000 MHz (see Clause 6).....	96
D.1	General.....	96
D.2	Ground plane construction.....	96
D.2.1	Material.....	96
D.2.2	Roughness.....	96
D.3	Services to EUT	97
D.4	Weather-protection enclosure construction	97
D.4.1	Materials and fasteners	97
D.4.2	Internal arrangements	98
D.4.3	Size	98
D.4.4	Uniformity with time and weather	98

D.5	Turntable and set-up table.....	98
D.6	Receive antenna mast installation	99
Annex E (xxx)	(Void)	100
Annex F (informative)	Basis for ± 4 dB site acceptability criterion (see Clause 6)	101
F.1	General.....	101
F.2	Error analysis.....	101
Annex G (informative)	Examples of uncertainty budgets for site validation of a COMTS using RSM with a calibrated antenna pair (see 6.6).....	103
G.1	Quantities to be considered for antenna pair reference site attenuation calibration using the averaging technique	103
G.2	Quantities to be considered for antenna pair reference site attenuation calibration using a REFTS	104
G.3	Quantities to be considered for COMTS validation using an antenna pair reference site attenuation	105
Bibliography	106

Figure 1	– Schematic of radiation from EUT reaching an LPDA antenna directly and via ground reflections at a 3 m site, showing the beamwidth half-angle, φ , at the reflected ray.....	19
Figure 2	– RX antenna E-plane radiation pattern example, with limit area shaded for 3 m distance and 2 m EUT width	24
Figure 3	– Determination of maximum useable EUT width using half-power beamwidth.....	24
Figure 4	– Determination of maximum useable EUT height using half-power beamwidth	25
Figure 5	– Obstruction-free area of a test site with a turntable (see 6.2.3).....	27
Figure 6	– Obstruction-free area with stationary EUT (see 6.2.3)	27
Figure 7	– Test point locations for 3 m and 10 m test distances	36
Figure 8	– Paired test point locations for all test distances	38
Figure 9	– Example of paired test point selection for a test distance of 10 m	38
Figure 10	– Illustration of an investigation of influence of antenna mast on A_{APR}	39
Figure 11	– Typical antenna positions for a weather-protected OATS or a SAC – vertical polarization validation measurements	42
Figure 12	– Typical antenna positions for a weather-protected OATS or a SAC – horizontal polarization validation measurements	42
Figure 13	– Typical antenna positions for a weather-protected OATS or a SAC – vertical polarization validation measurements for a smaller EUT	43
Figure 14	– Typical antenna positions for a weather-protected OATS or a SAC – horizontal polarization validation measurements for a smaller EUT	43
Figure 15	– Measurement positions for FAR site validation	46
Figure 16	– Example of one measurement position and antenna tilt for FAR site validation	48
Figure 17	– Typical quasi free-space test site reference SA measurement set-up.....	50
Figure 18	– Theoretical free-space NSA as a function of frequency for different measurement distances [see Equation (16)]	52
Figure 19	– Position of the antenna relative to the edge above a rectangle set-up table (top view).....	54
Figure 20	– Antenna position above the set-up table (side view)	54
Figure 21	– Transmit antenna E-plane radiation pattern example (this example is for informative purposes only)	58
Figure 22	– Transmit antenna H-plane radiation pattern (this example is for informative purposes only)	59

Figure 23 – S_{VSWR} measurement positions in a horizontal plane (see 7.5.2 for description)	60
Figure 24 – S_{VSWR} positions (height requirements)	62
Figure 25 – S_{VSWR} conditional measurement position requirements	68
Figure 26 – Definition of the reference planes inside the test jig	70
Figure 27 – The four configurations for the TRL calibration	72
Figure 28 – Limits for the magnitude of S_{11} , measured according to the provisions of 8.1 to 8.3	73
Figure 29 – Example of a 50Ω adaptor construction in the vertical flange of the jig	74
Figure 30 – Example of a matching adaptor with balun or transformer	74
Figure 31 – Example of a matching adaptor with resistive matching network	75
Figure 32 – Example of a typical paddle stirrer	76
Figure 33 – Range of coupling attenuation as a function of frequency for a chamber using the stirrer shown in Figure 16	77
Figure A.1 – Short dipole antenna factors for $R_L = 50 \Omega$	82
Figure C.1 – The LLAS, consisting of three mutually perpendicular large-loop antennas	88
Figure C.2 – An LLA containing two opposite slits, positioned symmetrically with respect to the current probe C	89
Figure C.3 – Construction of an LLA slit	89
Figure C.4 – Example of an LLA slit construction using a strap of printed circuit board to obtain a rigid construction	90
Figure C.5 – Construction of the metal box containing the current probe	90
Figure C.6 – Example showing the routing of several cables from an EUT to minimize capacitive coupling from the leads to the LLAS	91
Figure C.7 – The eight positions of the LLAS verification dipole during validation of an LLA ...	92
Figure C.8 – Validation factor for an LLA of 2 m diameter	92
Figure C.9 – Construction of the LLAS verification dipole antenna	93
Figure C.10 – Conversion factors C_{dA} [for conversion into $\text{dB}(\mu\text{A}/\text{m})$] and C_{dV} [for conversion into $\text{dB}(\mu\text{V}/\text{m})$] for two standard measuring distances d	95
Figure C.11 – Sensitivity S_D of a large-loop antenna with diameter D relative to a large-loop antenna having a diameter of 2 m	95
Figure D.1 – The Rayleigh criterion for roughness in the ground plane	97
Table 1 – Site validation methods applicable for OATS, OATS-based, SAC, and FAR site types	29
Table 2 – Theoretical normalized site attenuation, A_N – recommended geometries for broadband antennas	32
Table 3 – Example template for A_{APR} data sets	35
Table 4 – RSM frequency steps	35
Table 5 – Maximum dimensions of test volume versus test distance	44
Table 6 – Frequency ranges and step sizes for FAR site validation	48
Table 7 – S_{VSWR} measurement position designations	63
Table 8 – S_{VSWR} reporting requirements	68
Table D.1 – Maximum roughness for 3 m, 10 m and 30 m measurement distances	97
Table F.1 – Error budget	101

Table G.1 – Antenna pair reference site attenuation calibration using the large-OATS averaging technique 103

Table G.2 – Antenna pair reference site attenuation calibration using REFTS 104

Table G.3 – COMTS validation using an antenna pair reference site attenuation 105

INTERNATIONAL ELECTROTECHNICAL COMMISSION
INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE

**SPECIFICATION FOR RADIO DISTURBANCE AND
IMMUNITY MEASURING APPARATUS AND METHODS –**

**Part 1-4: Radio disturbance and immunity measuring apparatus –
Antennas and test sites for radiated disturbance measurements**

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights

This fourth edition cancels and replaces the third edition published in 2010, Amendment 1:2012 and Amendment 2:2017. This edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- provisions are added to address test site validation in the frequency range from 30 MHz to 1000 MHz using the reference site method, to take into account the receive antenna radiation pattern in the frequency range from 1 GHz to 18 GHz, and further details on test site validation using the NSA method with broadband antennas in the frequency range from 30 MHz to 1 000 MHz.

International Standard CISPR 16-1-4 has been prepared by CISPR subcommittee A: Radio-interference measurements and statistical methods.

It has the status of a basic EMC publication in accordance with IEC Guide 107, *Electromagnetic compatibility – Guide to the drafting of electromagnetic compatibility publications*.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
CIS/A/1262/FDIS	CIS/A/1275/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts of CISPR 16 series, under the general title *Specification for radio disturbance and immunity measuring apparatus and methods*, can be found on the IEC website.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

SPECIFICATION FOR RADIO DISTURBANCE AND IMMUNITY MEASURING APPARATUS AND METHODS –

Part 1-4: Radio disturbance and immunity measuring apparatus – Antennas and test sites for radiated disturbance measurements

1 Scope

This part of CISPR 16 specifies the characteristics and performance of equipment for the measurement of radiated disturbances in the frequency range 9 kHz to 18 GHz. Specifications for antennas and test sites are included.

NOTE In accordance with IEC Guide 107, CISPR 16-1-4 is a basic EMC publication for use by product committees of the IEC. As stated in Guide 107, product committees are responsible for determining the applicability of the EMC standard. CISPR and its sub-committees are prepared to cooperate with product committees in the evaluation of the value of particular EMC tests for specific products.

The requirements of this publication apply at all frequencies and for all levels of radiated disturbances within the CISPR indicating range of the measuring equipment.

Methods of measurement are covered in Part 2-3, further information on radio disturbance is given in Part 3, and uncertainties, statistics and limit modelling are covered in Part 4 of CISPR 16.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CISPR 16-1-1, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus*

CISPR 16-1-5:2014, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-5: Radio disturbance and immunity measuring apparatus – Antenna calibration sites and reference test sites for 5 MHz to 18 GHz*
CISPR 16-1-5:2014/AMD1:2016

CISPR 16-1-6:2014, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-6: Radio disturbance and immunity measuring apparatus – EMC antenna calibration*
CISPR 16-1-6:2014/AMD1:2017

CISPR 16-2-3:2016, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 2-3: Methods of measurement of disturbances and immunity – Radiated disturbance measurements*

CISPR TR 16-3, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 3: CISPR technical reports*