

AS 2419.4:2021



Fire hydrant installations

Part 4: Storz fittings for firefighting purposes



AS 2419.4:2021

This Australian Standard® was prepared by FP-009, Fire Hydrant Installations. It was approved on behalf of the Council of Standards Australia on 31 March 2021.

This Standard was published on 9 April 2021.

The following are represented on Committee FP-009:

- Association of Accredited Certification Bodies
- Association of Hydraulic Services Consultants Australia
- Australasian Fire and Emergency Service Authorities Council
- Australian Building Codes Board
- Australian Fire Safety Practitioners Accreditation Board
- Australian Industry Group
- Australian Institute of Building Surveyors
- Australian Stainless Steel Development Association
- Engineers Australia
- Facility Management Association of Australia
- Fire Protection Association Australia
- Hydraulic Consultants Association Australasia
- Insurance Council of Australia
- International Copper Association Australia
- Master Plumbers Australia
- National Fire Industry Association
- Plastics Industry Pipe Association of Australia
- Water Services Association of Australia

This Standard was issued in draft form for comment as DR AS 2419.4:2020.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76113 288 9

Fire hydrant installations

Part 4: Storz fittings for firefighting purposes

First published as AS 2419.4:2021.

© Standards Australia Limited 2021

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Standards Australia Committee FP-009, Fire Hydrant Installations.

The objective of this Standard is to specify minimum requirements for the design, manufacture, performance and testing of Storz (i.e. quarter turn internal lug two-way) pressure and suction fittings suitable for firefighting purposes.

This Standard is part of a series on fire hydrant installation, which comprises the following parts:

- (a) AS 2419.1, *Fire hydrant installations, Part 1: System design, installation and commissioning*
- (b) AS 2419.2, *Fire hydrant installations, Part 2: Fire hydrant valves*
- (c) AS 2419.3, *Fire hydrant installations, Part 3: Fire brigade booster connections*
- (d) AS 2419.4, *Fire hydrant installations, Part 4: Storz fittings for firefighting purposes*
(this Standard)

This Standard is to be read in conjunction with AS 2419.1.

The terms “normative” and “informative” are used in Standards to define the application of the appendix to which they apply. A “normative” appendix is an integral part of a Standard, whereas an “informative” appendix is only for information and guidance.

Contents

Preface	ii
Introduction	v
1 Scope and general	1
1.1 Scope	1
1.2 Application	1
1.3 Normative references	1
1.4 Terms and definitions	3
1.5 Product conformity	6
1.6 Alternative designs	6
1.7 New designs and innovations	6
2 Storz assemblies	7
2.1 Hose coupling	7
2.2 Adaptor — Internal thread	8
2.3 Adaptor — External thread	9
2.4 Fire hydrant adaptor and anti-tamper plug	10
2.5 Blank cap	11
2.6 Dust cap	12
2.7 Reducer	13
3 Components and dimensions	14
3.1 Coupling cam ring	14
3.2 Hose tail	20
3.3 Retaining ring	24
3.4 Suction gasket	25
3.5 Delivery gasket	26
3.6 Flat gasket	26
3.7 Adaptor cam ring — Internal thread	28
3.8 Adaptor cam ring — External thread	35
3.9 Hydrant adaptor cam ring	41
3.10 Anti-tamper plug	44
3.11 Blank cap	45
3.12 Dust cap	49
3.13 Reducer adaptor transition piece	51
3.14 S-Hook and tether	54
4 Manufacture	54
4.1 Sizes	54
4.2 Dimensions	54
4.3 Materials	55
4.3.1 Cam ring	55
4.3.2 Hose tail	55
4.3.3 Blank cap	55
4.3.4 Retaining ring	55
4.3.5 Suction, delivery and 25 mm gaskets	55
4.3.6 Flat gaskets	55
4.3.7 Dust cap	55
4.3.8 Tether	56
4.4 Alternative materials	56
4.4.1 Brass	56
4.4.2 Stainless steel	56
4.5 Coatings and treatments	56
4.5.1 Anodizing	56
4.5.2 Powder coating	56
4.6 Tolerances	56
4.7 Markings	57

5 Performance requirements	57
5.1 Pressures	57
5.2 Interconnection torque	58
Appendix A (normative) Product conformity	59
Appendix B (informative) Purchasing guidelines	61
Appendix C (normative) Equivalent International Standards	62
Bibliography	63

Introduction

Australian fire brigade hose couplings evolved independently in each state and territory according to local needs. The various regional connections are subsequently referenced in the appendices of the AS 2419 suite of standards. To facilitate better interagency cooperation, the Australasian Fire and Emergency Services Authorities Council designated the Storz type connection as one of the common Australia-wide fittings for firefighting hoses, equipment, vehicles and fire hydrant installations.

Carl August Guido Storz first patented a quarter turn internal lug two-way hose coupling in Germany in 1881. German fire brigades adopted Storz after a single fire destroyed 203 homes in 1933. The German Institute for Standardization (DIN) describes 25, 52, 75 and 110 mm Storz fittings. The Netherlands Standardization Institute (NEN) also describes 65 mm Storz fittings. Other diameters of Storz connection are variously described by the National Fire Protection Association (USA) and the Standards Council of Canada.

Storz fittings that do not conform to established Standards are not fully compatible with fire brigade equipment and operations. Cast aluminium fittings which are specifically prohibited for firefighting purposes in Australia by AS 2419.2 and AS 2419.3 have been used in place of forged aluminium fittings and have failed. Non-conforming Storz fittings are a safety risk to firefighters and building occupants, especially if connection failure occurs during firefighting and emergency response operations.

To address poor conformance and facilitate reliability, this Standard consolidates and specifies the requirements for the standard sizes of Storz fittings used for firefighting purposes in Australia.

NOTES

Australian Standard®

Fire hydrant installations

Part 4: Storz fittings for firefighting purposes

1 Scope and general

1.1 Scope

This Standard applies to Storz fittings intended for firefighting purposes in Australia and specifies the design, manufacture, performance and testing of Storz fittings used for:

- (a) connections to valves, hydrant and sprinkler boosters, pipe fittings, and branch pipes etc;
- (b) hose couplings;
- (c) reducing connection sizes; and
- (d) capping connections.

NOTE For guidelines on the information to be supplied at the time of an enquiry or order, see [Appendix B](#).

1.2 Application

This Standard shall be read in conjunction with AS 2419.1.

1.3 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document.

NOTE Documents referenced for informative purposes are listed in the Bibliography.

AS 2419.1, *Fire hydrant installations, Part 1: System design, installation and commissioning*

AS 2419.2, *Fire hydrant installations, Part 2: Fire hydrant valves*

AS 2419.3, *Fire hydrant installations, Part 3: Fire brigade booster connections*

AS 2700, *Colour Standards for General Purposes*

DIN 405, *General purpose knuckle threads*

DIN 5686, *Double loop chains without quality requirements*

DIN 14301, *Aluminium alloy delivery and suction coupling type D; nominal pressure 16*

DIN 14302, *Aluminium alloy delivery coupling type C; nominal pressure 16*

DIN 14303, *Aluminium alloy delivery coupling type B with nominal pressure PN 16*

DIN 14306, *Aluminium alloy solid coupling type D for pressure and suction purposes; nominal pressure 16*

DIN 14307-1, *Aluminium alloy solid coupling type C, with sealing ring for pressure purposes; nominal pressure 16*

DIN 14307-2, *Aluminium alloy solid coupling type C with sealing ring for suction purposes; nominal pressure 16*

DIN 14308-1, *Aluminium alloy solid coupling type B, with sealing ring for pressure purposes; nominal pressure 16*