

IN-LB

Inch-Pound Units

SI

International System of Units

Strut-and-Tie Method Guidelines for ACI 318-19— Guide

Reported by Joint ACI-ASCE Committee 445

ACI PRC-445.2-21



American Concrete Institute
Always advancing



Strut-and-Tie Method Guidelines for ACI 318-19—Guide

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised the ACI Collection of Concrete Codes, Specifications, and Practices.

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
Phone: +1.248.848.3700
Fax: +1.248.848.3701

www.concrete.org

Strut-and-Tie Method Guidelines for ACI 318-19—Guide

Reported by Joint ACI-ASCE Committee 445

Abdeldjelil Belarbi*, Chair

Adam S. Lubell*, Secretary

Neal S. Anderson
Robert B. Anderson*
Robert W. Barnes*
Oguzhan Bayrak*
Zdenek P. Bazant
Evan C. Bentz
John F. Bonacci
Hakim Bouadi*
Mikael W. Braestrup
Michael D. Brown*
Michael P. Collins
David Darwin

Catherine E French
Gary G. Greene, Jr.
Neil M. Hawkins
Thomas T. C. Hsu
Gary J. Klein*
Daniel A. Kuchma*
Z. John Ma*
Adolfo B. Matamoros
Denis Mitchell*
Yi-Lung Mo
Daniel T. Mullins*
Lawrence C. Novak*

Carlos E. Ospina
Stavroula J. Pantazopoulou
Maria A. Polak
Santiago Pujol
Julio A. Ramirez*
Karl-Heinz Reineck*
David H. Sanders*†
Lesley H. Sneed
Robin G. Tuchscherer*
James K. Wight

Consulting Members
Viviane Adam
Perry Adebar
Gerhard Breitschaft
Antoni Gladera
Daniel Dunkelberg
Marc O. Eberhard
Biroł Fitik
Josef Hegger
Patrick Huber
Karin Reissen
Udo Wiens
Konrad Zilch

*Subcommittee 445-A Members who Developed this Guide

†Chair of Subcommittee 445-A

Additional Subcommittee 445-A Members not noted above:

Sergio Brena
I-Kuang Fang
Katrin Habel

Matthew Huizinga
Carin Roberts-Wollmann
Rafael Alves de Souza

Bozidar Stojadinovic
Nancy Larson Verney
Fernando Yanez

Joint ACI-ASCE Committee 445 would like to thank Andrew Stam for his contribution to this guide.

Strut-and-tie models (STMs) were first used at the end of the nineteenth century as a concrete design method. The method was added to ACI 318 in 2002 as Appendix A. In 2014, STM provisions were moved into the main body of the code as Chapter 23, Strut-and-Tie Method. This document focuses on the ACI 318-19 implementation of strut-and-tie modeling. The main objectives of this document are to: 1) explain the intent and application of ACI 318 STM provisions; 2) provide additional design guidance for the STM based on other design codes, specifications, and committee documents; and 3) present design recommendations from recent research publications. This document provides practical guidance to the structural design community.

Keywords: D-regions; design; disturbed regions; model; node; strut; tie.

ACI Committee Reports, Guides, and Commentaries are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

CONTENTS**CHAPTER 1—INTRODUCTION, p. 2**

1.1—Background, p. 2

1.2—Objectives, p. 2

CHAPTER 2—NOTATION AND DEFINITIONS, p. 2

2.1—Notation, p. 2

2.2—Definitions, p. 4

CHAPTER 3—OVERVIEW OF THE STRUT-AND-TIE MODEL DESIGN PROCEDURE, p. 5

3.1—Introduction, p. 5

3.2—Overview of the strut-and-tie method, p. 5

3.3—Conceptual example, p. 6

3.4—Historical development of the strut-and-tie method, p. 9

ACI PRC-445.2-21 was adopted and published August 2021.

Copyright © 2021, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

CHAPTER 4—DESIGN STRENGTH OF STRUTS, TIES, AND NODES, p. 10

- 4.1—Overview, p. 10
- 4.2—Strut and node types and factors influencing strength, p. 11
- 4.3—STM strength requirements, p. 14
- 4.4—Strength and requirements for struts, p. 14
- 4.5—Strength and requirements for ties, p. 17
- 4.6—Strength and requirements for nodes, p. 19

CHAPTER 5—MODELING AND DESIGN CONSIDERATIONS, p. 23

- 5.1—Introduction, p. 23
- 5.2—Influence of model topology on performance of complex D-regions, p. 23
- 5.3—Guidance to selection of STM shapes, p. 25
- 5.4—Calculating member forces and stresses in complex D-regions, p. 28
- 5.5—Comparison of sectional and STM design of transverse reinforcement in a B-region, p. 30
- 5.6—Refined models for cracking of struts and the size effect, p. 31
- 5.7—States of stress in nodes, p. 32
- 5.8—Maximum shear stress limits in beams, p. 34
- 5.9—Member dimensions and constitutive relationships, p. 36
- 5.10—Reinforcement arrangement in relation to tie orientation, p. 37
- 5.11—Consideration of prestressing, p. 37
- 5.12—Capacity evaluation of existing structures, p. 39
- 5.13—Computer-based design aids, p. 40

CHAPTER 6—SERVICEABILITY CONSIDERATIONS, p. 41

- 6.1—Introduction, p. 41
- 6.2—Cracking at service limit states, p. 41
- 6.3—Determination of required distributed reinforcement, p. 42
- 6.4—Distributed reinforcement placement and detailing, p. 42
- 6.5—Deflections, p. 43

CHAPTER 7—IMPLEMENTATION OF STM DESIGN AND CONSTRUCTION DETAILS, p. 44

- 7.1—Introduction, p. 44
- 7.2—Deep beams, p. 44
- 7.3—Frame corners and beam-column joints, p. 46
- 7.4—Corbels, p. 48
- 7.5 Dapped-end beams, p. 50
- 7.6—Beams supporting beams (indirect supports), p. 53
- 7.7—Inverted T-beams, p. 56
- 7.8—Walls and beams with openings, p. 58
- 7.9—Coupling beams, p. 60
- 7.10—Footings, p. 62
- 7.11—Pile caps, p. 62
- 7.12—Post-tensioned anchorage zones, p. 64

CHAPTER 8—OTHER STM DESIGN SPECIFICATIONS, CODES, AND GUIDE DOCUMENTS, p. 66

- 8.1—Introduction, p. 66
- 8.2—Strut-and-tie design requirements in CSA A23.3-19, p. 66
- 8.3 American Association of State Highway and Transportation Officials (AASHTO), p. 69
- 8.4—FIP Recommendations (FIP 1999), p. 71
- 8.5—Eurocode 2, p. 74
- 8.6—*fib* Model Code for Concrete Structures 2010 (*fib* 2013), p. 75

CHAPTER 9—REFERENCES, p. 75

- 9.1—Referenced standards and reports, p. 76
- 9.2—Authored references, p. 76

CHAPTER 1—INTRODUCTION

1.1—Background

While the origins of strut-and-tie models date back to the end of the nineteenth century (Ritter 1899; Considère 1900; Mörsch 1909), the strut-and-tie design method was not formally introduced into ACI 318 until 2002. Up until the 2014 version of ACI 318, strut-and-tie model (STM) provisions were included in Appendix A of ACI 318. With the reorganization of ACI 318 in 2014, STM provisions were moved into the main body of the code as Chapter 23, in part to recognize the importance of this method in structural design practice. Subsequently, significant changes to the STM provisions occurred in ACI 318-19. Chapter 23 was renamed to “Strut-and-Tie Method.” The abbreviation of STM only stands for strut-and-tie model.

In an effort to provide information on the use of strut-and-tie models in structural design, explanatory notes are included with the ACI 318 provisions. Additionally, two ACI special publications—ACI SP-208 and ACI SP-273—were developed by Subcommittee A, Strut & Tie, of Joint ACI-ASCE Committee 445, Shear and Torsion, in which the application of STM was illustrated through various design examples. Nevertheless, there is a need to provide additional guidance on the use of STM techniques.

1.2—Objectives

This document focuses on the ACI 318-19 implementation of strut-and-tie modeling. The main objectives of this document are to: 1) explain the intent and application of ACI 318 STM provisions; 2) provide additional design guidance for the STM based on other design codes, specifications, and committee documents; and 3) present design recommendations from recent research publications. This document is intended to provide practical guidance to the structural design community.

CHAPTER 2—NOTATION AND DEFINITIONS

2.1—Notation

This section defines notations used in this guide.