

# IPC-2591-Version 1.4

2021 - December

**Connected Factory  
Exchange (CFX)**

Supersedes IPC-2591, Version 1.3  
February 2021

*An international standard developed by IPC*



**BUILD ELECTRONICS BETTER**

---

## The Principles of Standardization

In May 1995 the IPC's Technical Activities Executive Committee (TAEC) adopted Principles of Standardization as a guiding principle of IPC's standardization efforts.

### Standards Should:

- Show relationship to Design for Manufacturability (DFM) and Design for the Environment (DFE)
- Minimize time to market
- Contain simple (simplified) language
- Just include spec information
- Focus on end product performance
- Include a feedback system on use and problems for future improvement

### Standards Should Not:

- Inhibit innovation
- Increase time-to-market
- Keep people out
- Increase cycle time
- Tell you how to make something
- Contain anything that cannot be defended with data

## Notice

IPC Standards and Publications are designed to serve the public interest through eliminating misunderstandings between manufacturers and purchasers, facilitating interchangeability and improvement of products, and assisting the purchaser in selecting and obtaining with minimum delay the proper product for his particular need. Existence of such Standards and Publications shall not in any respect preclude any member or nonmember of IPC from manufacturing or selling products not conforming to such Standards and Publication, nor shall the existence of such Standards and Publications preclude their voluntary use by those other than IPC members, whether the standard is to be used either domestically or internationally.

Recommended Standards and Publications are adopted by IPC without regard to whether their adoption may involve patents on articles, materials, or processes. By such action, IPC does not assume any liability to any patent owner, nor do they assume any obligation whatever to parties adopting the Recommended Standard or Publication. Users are also wholly responsible for protecting themselves against all claims of liabilities for patent infringement.

## IPC Position Statement on Specification Revision Change

It is the position of IPC's Technical Activities Executive Committee that the use and implementation of IPC publications is voluntary and is part of a relationship entered into by customer and supplier. When an IPC publication is updated and a new revision is published, it is the opinion of the TAEC that the use of the new revision as part of an existing relationship is not automatic unless required by the contract. The TAEC recommends the use of the latest revision. Adopted October 6, 1998

## Why is there a charge for this document?

Your purchase of this document contributes to the ongoing development of new and updated industry standards and publications. Standards allow manufacturers, customers, and suppliers to understand one another better. Standards allow manufacturers greater efficiencies when they can set up their processes to meet industry standards, allowing them to offer their customers lower costs.

IPC spends hundreds of thousands of dollars annually to support IPC's volunteers in the standards and publications development process. There are many rounds of drafts sent out for review and the committees spend hundreds of hours in review and development. IPC's staff attends and participates in committee activities, typesets and circulates document drafts, and follows all necessary procedures to qualify for ANSI approval.

IPC's membership dues have been kept low to allow as many companies as possible to participate. Therefore, the standards and publications revenue is necessary to complement dues revenue. The price schedule offers a 50% discount to IPC members. If your company buys IPC standards and publications, why not take advantage of this and the many other benefits of IPC membership as well? For more information on membership in IPC, please visit [www.ipc.org](http://www.ipc.org) or call 847/597-2872.

Thank you for your continued support.



**IPC-2591-Version 1.4**

# **Connected Factory Exchange (CFX)**

Developed by the Connected Factory Initiative Subcommittee (2-17)  
of the Electronic Product Data Description Committee (2-10) of IPC

***Supersedes:***

IPC-2591-Version 1.3 -

February 2021

IPC-2591-Version 1.2 -

September 2020

IPC-2591-Version 1.1 -

January 2020

IPC-2591 - March 2019

Users of this publication are encouraged to participate in the  
development of future revisions.

Contact:

IPC  
3000 Lakeside Drive, Suite 105N  
Bannockburn, Illinois  
60015-1249  
Tel 847 615.7100  
Fax 847 615.7105

This Page Intentionally Left Blank

## Acknowledgment

Any document involving a complex technology draws material from a vast number of sources across many continents. While the principal members of the Connected Factory Initiative Subcommittee (2-17) of the Electronic Product Data Description Committee (2-10) are shown below, it is not possible to include all of those who assisted in the evolution of this standard. To each of them, the members of IPC extend their gratitude.

---

### (2-10) Electronic Product Data Description Committee

Chair  
Michael Ford  
Aegis Software

### (2-17) Connected Factory Initiative Subcommittee

Co-Chairs  
Jason Spera  
Aegis Software  
  
Thomas Marktscheffel  
ASM Assembly Systems  
  
Jarrod Webb  
Lockheed Martin Missiles  
& Fire Control

### Technical Liaison of the IPC Board of Directors

Bob Neves  
Microtek (Changzhou) Laboratories

---

### Connected Factory Initiative Subcommittee

Ivan Aduna  
Koh Young Technology

Paul Austen  
ECD

Tanner Avery  
Keysight Technologies

Ifeanyi Azolibe  
SigmaPoint Technologies Inc.

Jaeyoung Bae  
Yamaha Motor Europe N.V.

Jennifer Bennett  
IBM Corporation

Greg Benoit  
Cogiscan Inc.

Praveen Bhat  
Accord Software &  
Systems Private Ltd

Mike Bixenman  
Kyzen Corporation

Ruffin Blackard  
CBH Solutions, LLC

Lim Boon Hong  
ViTrox Technologies

Frederic Bourdat  
MBtech

James Brand  
Innovative Creations Ltd

Tim Burke  
Arch Systems

Javier Caraccioli  
Lockheed Martin Missiles  
& Fire Control

Michael Ceraso  
University of New Orleans

Pierre Chatain  
Europlacer

Zhiman Chen  
ZHUZHOU CRRC TIMES  
ELECTRIC CO., LTD

Peter Chiang  
MSI Computer (Shenzhen) Co., Ltd.

Chris Chiang  
Compal Electronics

Sean Clancy  
HZO Inc

Chris Clapper  
Imperative Solutions, LLC

Thomas Clark  
Lockheed Martin Missiles  
& Fire Control

Marie Cole  
IBM Corporation

Michael Collier  
Teledyne Advanced Electronic  
Solutions

Grayson Cook  
Lockheed Martin Missiles  
& Fire Control

Nick Dajda  
Nordson DAGE X-ray Systems

Karim Dehkordi  
Acculogic

Ghassen Dhaouadi  
Azitech ApS

Radu Diaconescu  
Swissmic

Michael Durkan  
Mentor Graphics Corporation

Uri Elhav  
Cybord

Benoit Fillastre  
MBtech

Brent Fischthal  
Koh Young Technology

Ron Folkeringa  
Nortech Systems Inc.

Michael Ford  
Aegis Software

Thomas Forsythe  
Kyzen Corporation

Alexis Fouquet  
Europlacer

Nicolas Francheteau  
Europlacer

Symon Franklin  
Custom Interconnect Ltd

Ricardo Gallardo  
Sanmina Corporation

Ryan Gamble  
Intraratio Corporation

Stephen Golemme JITX Inc.	Wes Karpiak Celestica	Carlos Ospina BotFactory, Inc.
Constantino Gonzalez ACME Training & Consulting	Ryoji Kashiwagi Saki Corporation	Cengiz Oztunc DNZ Ltd.
Josh Goolsby Lockheed Martin Missiles & Fire Control	Jai Kasinathan CloudVidia	HyungGun Park Hanwha International Corporation
Jay Gorajia Siemens Digital Industries Software	Noriyuki Kato Omron Manufacturing	Marc Peo Heller Industries Inc.
Geoff Goring Goring Engineering Consultancy Ltd	Timothy Keener Timothy A Keener	Brad Perkins Nordson Matrix
David Graham 4IR.UK British Systems	Jason Keeping Celestica International L.P.	Sylvain Perron Cogiscan Inc.
Curtis Grosskopf IBM Corporation	Michael Kimpton Fuji America Corporation	Colas Peyrelier LACROIX Electronics
Shahar Gur-ari FLEX Israel	Robert Kinyanjui John Deere Electronic Solutions	Mee Pha AbelConn, LLC
Frank Hart Precision Valve & Automation, Inc.	Yusaku Kono Japan Unix Co., Ltd.	Mussie Pietros GE Aviation
Shreenivasa Hd Unknown Address	Meredith LaBeau Calumet Electronics Corp.	Ray Prasad Ray Prasad Consultancy Group
Andreas Hemmie Acculogic Inc.	Vincent Levannier SYNEO, LLC	Michael Rauter Flextronics International GmbH
Aaron Hennhoefer Digitaltest Inc.	Wilson Loh CyberOptics Corporation	Henry Rekers Schneider Electric
Richard Ho Cisco Systems	Todd MacFadden Bose Corporation	Maxwell Rich BAE Systems
Happy Holden Holden Consulting-Gentex	Thomas Marktscheffel ASM Assembly Systems	Jens Rick iTAC Software AG
Mark Hooper iBASEt	Karen McConnell Northrop Grumman Corporation	Florian Ritter ASYS Automatisierungssysteme GmbH
Ken Horkey AGI Suretrack	Mark McMeen STI Electronics, Inc.	Luis Rivera Rodriguez Luis I Rivera Rodriguez
Khoo Hua ViTroX Technologies Sdn. Bhd.	James Monarchio TTM Technologies	Charles Robinson Teradyne Inc.
Robert Hudjakov IPTE LLC	Miles Moreau KIC	Todd Rountree Austin American Technology
Constantin Hudon Varitron Technologies Inc.	Venkata Mynampati Flextronics International	Robert Rowland Axiom Electronics, LLC
Joshua Hudson Lockheed Martin Missiles & Fire Control	N. Nagaraj Papros, Inc.	R Sarumathi GETECH
Jennie Hwang H-Technologies Group	Hisao Nishimori Toyota Motor Corporation	Helene Schloter ERSA GmbH
Jonathan Jimenez Creative Electron, Inc.	Jurgen Nunner SMT Maschinen und Vertriebs GmbH & Co. KG	Neaven Seo Keysight Technologies
Kai Kammers ASYS Automatisierungssysteme GmbH	John O'Connor TTM Technologies, Inc.	Chris Shaw Fujitsu Network Communications
	Pat Ortiz FlexLink Systems, Inc.	Cameron Shearon Raytheon Company

Tyler Siebert Lockheed Martin Missiles & Fire Control	Robert Toppel Axiom Electronics LLC	Siew-Siew Wee Keysight Technologies
Carl Silkey ITW EAE	Dave Trail Arch Systems	Eyal Weiss Cybord
Daniel Siran Aster Technologies	Julian Ungureanu Cisco Systems, Inc.	Raymond Whittier BAE Systems
Simon Smith Pillarhouse International, Ltd.	Torsten Vogelahn ASYS Automatisierungssysteme GmbH	Garrett Wong Nordson ASYMTEK
Jason Spera Aegis Software	Richard Vereijssen Yamaha Motor Europe N.V.	Lucas Woods Colder Products
Ata Syed PFC Flexible Circuits	Scott Vorhies Space Exploration Technologies	Fonda Wu Raytheon Company
Raj Takhar Assent Compliance Inc.	John Walls Aegis Software	Feng Xue IBM
Bill Thomas Aegis Software	Mark Waterman ECD	Jack Zhu Veoneer China CO., LTD
Audra Thurston Calumet Electronics Corp.	Jarrod Webb Lockheed Martin Missiles & Fire Control	

---

### Special Recognition

IPC recognizes the following group of people who showed exceptional leadership and effort in the development of IPC-2591, Version 1.4. Their efforts accelerated the process of publishing this much needed revision.

Tim Burke Arch Systems	Michael Kimpton Fuji America Corporation	Jarrod Webb Lockheed Martin Missiles & Fire Control
Michael Ford Aegis Software	Thomas Marktscheffel ASM Assembly Systems	
Alexis Fouquet Europlacer	John Walls Aegis Software	

This Page Intentionally Left Blank

# Table of Contents

<b>1 SCOPE</b> .....	1	2.3	International Organization for Standardization (ISO) .....	4
1.1 Purpose .....	1	2.4	SEMI .....	4
1.2 Application of This Standard .....	1	<b>3 GENERAL REQUIREMENTS</b> .....		4
1.3 CFX and the Hermes Standard .....	1	3.1 Guidance on the Use of This Standard .....		4
1.4 Updates to This Standard .....	2	3.1.1 Technical Reference .....		4
1.5 Definition of Requirements .....	2	3.1.2 Application Reference .....		4
1.6 Order of Precedence .....	2	3.2 Users of CFX .....		4
1.6.1 Conflict .....	2	3.2.1 Automated Assembly Processes .....		4
1.6.2 Clause References .....	2	3.2.2 In-House Manufacturing Solution Development .....		5
1.7 Acronyms .....	2	3.2.3 MES Software Solutions .....		5
1.8 Terms and Definitions .....	2	3.3 Software Development Environment .....		5
1.8.1 Activity .....	2	3.4 CFX Support Declaration .....		5
1.8.2 Component .....	2	<b>4 CFX STRUCTURAL OVERVIEW</b> .....		5
1.8.3 Dashboard .....	2	4.1 Primary Transport Layer: AMQP v1.0 .....		5
1.8.4 Data Integrity .....	3	4.1.1 CFX Message Channels .....		6
1.8.5 Endpoint .....	3	4.1.2 Channel Configuration .....		7
1.8.6 Factory Resource .....	3	4.1.3 CFX Message Types .....		7
1.8.7 Lane .....	3	4.1.4 CFX Compression .....		7
1.8.8 Lock .....	3	4.1.5 CFX – AMQP Message Properties .....		7
1.8.9 Material Carrier .....	3	4.2 Encoding: JSON .....		8
1.8.10 Material Chain .....	3	4.2.1 JSON Data Types .....		8
1.8.11 Material Location .....	3	4.3 CFX-Defined Content .....		8
1.8.12 Material Package .....	3	4.4 CFX Key Parameters .....		8
1.8.13 Material Traceability .....	3	4.4.1 Endpoint Identification (CFX Handle) .....		8
1.8.14 Materials .....	3	4.4.2 TransactionID .....		9
1.8.15 Operator .....	3	4.5 CFX Message Envelope .....		9
1.8.16 Process Endpoint (Station) .....	3	4.6 Operator Information .....		9
1.8.17 Production Unit .....	3	4.7 CFX Endpoint Configuration .....		10
1.8.18 Recipe .....	3	4.7.1 Specific CFX Endpoint Configuration Addresses .....		10
1.8.19 Root .....	3	<b>5 CFX OPERATIONAL MODELING</b> .....		11
1.8.20 Setup .....	3	5.1 Equipment State Model .....		11
1.8.21 State (Production State) .....	3	5.2 Station Fault Event Model .....		13
1.8.22 Station (Process Endpoint) .....	3	5.3 Production Unit Architecture .....		14
1.8.23 Stage .....	3	5.4 Production Station Process Model .....		15
1.8.24 Subassembly .....	3	<b>6 CFX TOPICS AND DYNAMIC STRUCTURES</b> .....		16
1.8.25 Symptom .....	3	6.1 Hierarchy of CFX Topics .....		16
1.8.26 Tool .....	4	6.1.1 CFX Topic Support Declaration .....		17
1.8.27 Transactional Endpoint .....	4	6.2 CFX Message Names .....		17
<b>2 APPLICABLE DOCUMENTS</b> .....	4			
2.1 IPC .....	4			
2.2 ECMA International .....	4			

6.3	CFX Structures . . . . .	17	7.5.3	CFX.Production.Hermes (Level 2) . . . . .	30
6.4	CFX Dynamic Structures . . . . .	17	7.5.4	CFX.Production.LoadingAndUnloading (Level 2) . . . . .	30
6.5	CFX Messaging Requirements by Equipment . .	17	7.5.5	CFX.Production.Processing (Level 2). . . . .	30
<b>7</b>	<b>CFX MESSAGES . . . . .</b>	<b>23</b>	7.5.6	CFX.Production.TestAndInspection (Level 2) . .	30
7.1	Root Level Messages. . . . .	23	7.5.7	CFX.Production.ReworkAndRepair (Level 2) . .	31
7.2	CFX.InformationSystem (Level 1) . . . . .	23	7.6	CFX.ResourcePerformance (Level 1) . . . . .	31
7.2.1	CFX.InformationSystem.ProductionScheduling (Level 2) . . . . .	23	7.6.1	CFX.ResourcePerformance.PressInsertion (Level 2) . . . . .	32
7.2.2	CFX.InformationSystem.UnitValidation (Level 2) . . . . .	24	7.6.2	CFX.ResourcePerformance.SMTPlacement (Level 2) . . . . .	32
7.2.3	CFX.InformationSystem.WorkOrderManagement (Level 2) . . . . .	24	7.6.3	CFX.ResourcePerformance.SolderPastePrinting (Level 2) . . . . .	32
7.2.4	CFX.InformationSystem.DataTransfer (Level 2) . . . . .	24	7.6.4	CFX.ResourcePerformance.THTPlacement (Level 2) . . . . .	32
7.3	CFX.Maintenance (Level 1) . . . . .	25	7.7	CFX.Sensor (Level 1) . . . . .	33
7.4	CFX.Materials (Level 1) . . . . .	25	7.7.1	CFX.Sensor.Identification (Level 2). . . . .	33
7.4.1	CFX.Materials.Management (Level 2) . . . . .	26	7.8	CFX Message Flow . . . . .	33
7.4.2	CFX.Materials.Storage (Level 2) . . . . .	27	7.8.1	Production Endpoint (Station) Connection . . . .	33
7.4.3	CFX.Materials.Transport (Level 2). . . . .	27	7.8.2	Station State Transition . . . . .	34
7.5	CFX.Production (Level 1). . . . .	28	7.8.3	Station Processing . . . . .	35
7.5.1	CFX.Production.Application (Level 2). . . . .	29	<b>8</b>	<b>CFX TECHNICAL REFERENCE . . . . .</b>	<b>36</b>
7.5.2	CFX.Production.Assembly (Level 2) . . . . .	29		<b>APPENDIX A – Version Updates . . . . .</b>	<b>37</b>
7.5.2.1	CFX.Production.Assembly.PressInsertion (Level 3) . . . . .	29		<b>APPENDIX B – Acronyms and Abbreviations . . . . .</b>	<b>43</b>

<b>Figures</b>	
Figure 1-1	Version Change Tracking Example . . . . . 2
Figure 4-1	CFX Channels Between Endpoints . . . . . 6
Figure 4-2	The CFX TransactionID . . . . . 9
Figure 5-1	SEMI E10 Equipment State Model . . . . . 11
Figure 5-2	Examples of Groupings of Production Units . . . . . 14
Figure 5-3	Panelized Printed Board . . . . . 15
Figure 5-4	CFX Unit Locations Identified on Multiple-Board Panel . . . . . 15
Figure 5-5	CFX Production Station Process Model . . . 15
Figure 7-1	CFX Station Connection Example Message Flow . . . . . 33
Figure 7-2	CFX Station State Transition Example Message Flow . . . . . 34
Figure 7-3	CFX Station Processing Example Message Flow . . . . . 35
<b>Tables</b>	
Table 4-1	Types of CFX Messages . . . . . 7
Table 4-2	CFX – AMQP Message Properties . . . . . 7
Table 4-3	CFX Message Envelope . . . . . 9
Table 5-1	Station Event Fault Model . . . . . 13
Table 6-1	CFX Capability Requirements by Equipment Type . . . . . 18
Table 6-2	Required Messages by Capability . . . . . 20
Table 7-1	CFX.Root Messages . . . . . 23
Table 7-2	CFX.InformationSystem.ProductionScheduling Messages . . . . . 24
Table 7-3	CFX.InformationSystem.UnitValidation Messages . . . . . 24
Table 7-4	CFX.InformationSystem. WorkOrderManagement Messages . . . . . 24
Table 7-5	CFX.InformationSystem.DataTransfer Messages . . . . . 24
Table 7-6	CFX.Maintenance Messages . . . . . 25
Table 7-7	CFX.Materials.Management Messages . . . . 26
Table 7-8	CFX.Materials.Management.MSDManagement Messages . . . . . 26
Table 7-9	CFX.Materials.Storage Messages . . . . . 27
Table 7-10	CFX.Materials.Transport Messages . . . . . 27
Table 7-11	CFX.Production Messages . . . . . 28
Table 7-12	CFX.Production.Application Messages . . . . 29
Table 7-13	CFX.Production.Assembly Messages . . . . 29
Table 7-14	CFX.Production.Assembly.PressInsertion Messages . . . . . 29
Table 7-15	CFX.Production.Hermes Messages . . . . . 30
Table 7-16	CFX.Production.LoadingAndUnloading Messages . . . . . 30
Table 7-17	CFX.Production.Processing Messages . . . . 30
Table 7-18	CFX.Production.TestAndInspection Messages30
Table 7-19	CFX.Production.ReworkAndRepair . . . . . 31
Table 7-20	CFX.ResourcePerformance Messages . . . . 31
Table 7-21	CFX.ResourcePerformance.PressInsertion Messages . . . . . 32
Table 7-22	CFX.ResourcePerformance.SMTPlacement Messages . . . . . 32
Table 7-23	CFX.ResourcePerformance.SolderPastePrinting Messages . . . . . 32
Table 7-24	CFX.ResourcePerformance.THTPlacement Messages . . . . . 32
Table 7-25	CFX.Sensor.Identification Messages . . . . 33

This Page Intentionally Left Blank

# Connected Factory Exchange (CFX) Version 1.4

---

## 1 SCOPE

This standard establishes the requirements for the omnidirectional exchange of information between manufacturing processes and associated host systems for assembly manufacturing. This standard applies to communication between all executable processes in the manufacture of printed board assemblies – automated, semiautomated and manual – and is applicable to related mechanical assembly and transactional processes.

**1.1 Purpose** With the growth and acceptance of digital modeling and practices in manufacturing, the lack of a holistic Industrial Internet of Things (IIoT) standard for the transfer of information between machines, systems and processes has become a severe limitation to the growth of digitization and computerization in the electronics manufacturing industry, inhibiting technology innovations such as Industry 4.0 and Smart Factories being available to all companies in the industry, regardless of size, sector and location.

This Connected Factory Exchange (CFX) standard provides a true “plug and play” Internet of Things (IoT) communication environment throughout manufacturing, where all equipment, manufacturing processes and transactional stations can communicate with each other without the need for the development and use of bespoke interfaces. CFX-enabled equipment and solutions from different vendors work seamlessly together.

There are many types of users of this CFX standard, including equipment vendors, solution providers, in-house information technology (IT) groups, etc. The many types of data included in CFX are used in different ways depending on the application; for example, closed-loop feedback systems, live production dashboards, traceability (IPC-1782), manufacturing execution systems (MES) control, lean supply chain management, active quality management, production control, etc.

As CFX data is fully omnidirectional, any CFX endpoint connection can consume data as well as create it. As an illustration, consider the scenario in which a single machine from a certain vendor is connected in-line with other machines from different vendors. CFX messages are sent from the single machine to other machines in the line, and to host systems such as MES. The single machine can also receive CFX messages from all other machines in the line, as well as from the host systems in order to optimize the machine operation and enable the vendor of the machines to create added-value functionality, such as to support machine-specific Industry 4.0. In this way, a smart, digital, Industry 4.0 factory will be comprised of many different Industry 4.0 computerization applications, each of which can be provided by different suppliers, at the machine, line, site and even enterprise levels, all working together, sharing data seamlessly through CFX.

This CFX standard supports the concept of big data by including data of different types from across the factory, including performance, materials, resources, users, quality events, product tracking, etc., all of which can be combined to create a big-data environment. CFX, therefore, provides many kinds of added value opportunities to the whole manufacturing operation, including, for example, improving operational efficiency and productivity, quality and reliability, agility and responsiveness. This CFX standard helps organizations ensure that end users/consumers will receive products and services that meet or exceed their expectations and in the timeliest and most economically viable method.

**1.2 Application of This Standard** This standard defines the communication protocol and content across all assembly production processes, irrespective of type or method of operation. It can also be applied to transactional operations. There are no restrictions in terms of product classification sector, size of operation or location. Surface-mount technology (SMT) production is not required to be a part of the factory. Though intended to support all aspects of printed board production, the use of CFX can be extended downstream to include, for example, mechanical assembly, personalization, packing and shipping, as well as upstream to include, for example, electrical and mechanical subassemblies.

**1.3 CFX and the Hermes Standard** This CFX standard is complementary to IPC-HERMES-9852. The Hermes Standard, as an advanced, intelligent Surface Mount Equipment Manufacturers Association (SMEMA) standard replacement, provides near-instant line control, passing information about production units as they pass down the line. CFX provides vertical messaging that is complementary to Hermes.