



NACE/PODS SP0507-2021
Reaffirmed November 23, 2021

External Corrosion Direct Assessment (ECDA) Integrity Data Exchange (IDX)

©2021 Association for Materials Protection and Performance (AMPP). All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise) without the prior written permission of AMPP.

External Corrosion Direct Assessment (ECDA) Integrity Data Exchange (IDX)

This AMPP standard represents a consensus of those individual members who have reviewed this document, its scope, and provisions. Its acceptance does not in any respect preclude anyone, whether he or she has adopted the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not in conformance with this standard. Nothing contained in this AMPP standard is to be construed as granting any right, by implication or otherwise, to manufacture, sell, or use in connection with any method, apparatus, or product covered by Letters Patent, or as indemnifying or protecting anyone against liability for infringement of Letters Patent. This standard represents minimum requirements and should in no way be interpreted as a restriction on the use of better procedures or materials. Neither is this standard intended to apply in all cases relating to the subject. Unpredictable circumstances may negate the usefulness of this standard in specific instances. AMPP assumes no responsibility for the interpretation or use of this standard by other parties and accepts responsibility for only those official AMPP interpretations issued by AMPP in accordance with its governing procedures and policies which preclude the issuance of interpretations by individual volunteers.

Users of this AMPP standard are responsible for reviewing appropriate health, safety, environmental, and regulatory documents and for determining their applicability in relation to this standard prior to its use. This AMPP standard may not necessarily address all potential health and safety problems or environmental hazards associated with the use of materials, equipment, and/or operations detailed or referred to within this standard. Users of this AMPP standard are also responsible for establishing appropriate health, safety, and environmental protection practices, in consultation with appropriate regulatory authorities, if necessary, to achieve compliance with any existing applicable regulatory requirements prior to the use of this standard.

CAUTIONARY NOTICE: AMPP standards are subject to periodic review and may be revised or withdrawn at any time in accordance with AMPP technical committee procedures. AMPP requires that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of initial publication and subsequently from the date of each reaffirmation or revision. The user is cautioned to obtain the latest edition. Purchasers of AMPP standards may receive current information on all standards and other AMPP/NACE/SSPC publications by contacting AMPP Customer Support, 15835 Park Ten Place, Houston, Texas 77084-5145 (Tel: +1 281-228-6200, email: customersupport@ampp.org).

Document History

2021-11-23: Reaffirmed by AMPP Standards Committee (SC) 10, "Asset Integrity Management" in coordination with the Pipeline Open Data Standard (PODS) Association⁽¹⁾

2014-03-08: Revised by Joint NACE/PODS TG 357, "External Corrosion Direct Assessment (ECDA) Integrity Data Exchange (IDX)"

2007-11-05: Approved by Joint NACE/PODS TG 357

AMPP values your input. To provide feedback on this standard, please contact: standards@ampp.org

⁽¹⁾ Pipeline Open Data Systems (PODS) Association, P.O. Box 273084, Fort Collins, CO 80527, www.pods.org.

External Corrosion Direct Assessment (ECDA) Integrity Data Exchange (IDX)

Foreword	4
Section 1	General	5
	1.1 Introduction.....	5
	1.2 Scope.....	5
	1.3 Benefits.....	5
Section 2	Definitions	6
Section 3	Common Data Format.....	9
	3.1 Introduction.....	9
	3.2 Flat File Tables.....	9
	3.3 Relational Databases.....	10
	3.4 ECDA_INSPECTION_RANGE Table (Header Table).....	11
	3.5 ECDA_REGION Table.....	14
	3.6 ECDA_SURVEY_RUN Table	15
Section 4	Common Data Format.....	17
	4.1 Introduction.....	17
	4.2 ECDA_CENTERLINE Table	17
Section 5	Close-Interval Survey Data Format.....	19
	5.1 Introduction.....	19
	5.2 ECDA_CIS Table	19
Section 6	ECDA_RECTIFIER Table.....	23
	6.1 Introduction.....	23
	6.2 ECDA_RECTIFIER Table	23
Section 7	Aboveground Coating Evaluation Survey Data Format	26
	7.1 Introduction.....	26
	7.2 ECDA_DCVG_ACVG Table (DC/AC VOLTAGE GRADIENT)	26
	7.3 ECDA_ACA Table (AC Attenuation).....	28
	7.4 ECDA_PEARSON Table	30
Section 8	Environment Survey Data Format.....	32
	8.1 Introduction.....	32
	8.2 ECDA_ENVIRONMENT Table.....	32
References	34
Appendix A	Interpreting an Entity Relation Diagram	35
Figure 1	Example Entity Relationship Diagram (ERD) for an ECDA IDX Database	11
Table 1	ECDA Inspection Range Table.....	12
Table 2	ECDA Region Table	14
Table 3	ECDA Survey Run Table	16
Table 4	ECDA Centerline Table	18
Table 5	ECDA CIS Table.....	20
Table 6	ECDA Rectifier Table.....	23
Table 7	ECDA DCVG/ACVG Table	26
Table 8	ECDA ACA Table.....	28
Table 9	ECDA Pearson Table	30
Table 10	ECDA Environment Table.....	32

Foreword

The objective of this standard practice is the development of a new external corrosion direct assessment (ECDA) data interchange data structure that will enable electronic integration of data and standardize reporting of ECDA data associated with indirect inspection data within the pipeline industry, to allow transfer between different software packages or computer systems. This is expected to minimize difficulty in using various programs to analyze or graph data and allow for comparison of data gathered for a given pipeline segment at different times, regardless of the software system used to collect it. The format outlined is the commonly used American Standard Code for Information Interchange (ASCII) comma delimited text file, which is adaptable to all data processing systems. This standard is expected to serve as a template for future internal corrosion direct assessment (ICDA) and stress corrosion cracking direct assessment (SCCDA) data interchange standards. It presents one suggested exchange format to standardize data transfer.

Data collection and testing procedures shall conform to NACE SP0207, "Performing Close-Interval Potential Surveys on Buried or Submerged Metallic Pipelines,"¹ NACE Standard TM0109, "Aboveground Survey Techniques for the Evaluation of Underground Pipeline Coating Condition,"² NACE SP0169,³ and other applicable recommended NACE standards for accurate ECDA pipeline integrity data.

This standard is intended for use by corrosion control personnel and information technology professionals involved with acquiring, analyzing, or maintaining ECDA data, contractors performing ECDA, and regulatory agencies.

For accurate and correct application, this standard must be used in its entirety. Using or citing only specific paragraphs or sections can lead to misinterpretation and misapplication of the recommendations and practices presented. Specific practices are not designated for every situation because of the complexity of conditions to which buried or submerged piping systems are exposed.

In AMPP standards, the terms *shall* and *must* are used to state requirements and are considered mandatory. The term *should* is used to state something that is recommended, but is not considered mandatory. The term *may* is used to state something considered optional.

Section 1: General

1.1 Introduction

- 1.1.1 This standard defines the requirements for a data format suitable for ECDA integrity data management. A standardized format assures accurate data transfer between contractor and operator databases in formats that are convenient and familiar to each. Such standardization accommodates industry-wide data mining and facilitates review by regulatory agencies.
- 1.1.2 ECDA-related data elements to cover a wide variety of data capture needs are presented. Not all fields are mandatory in all applications. The purpose of this standard is to provide a standard field naming and unit format convention (i.e., data dictionary) for using the various ECDA indirect inspection data elements.
- 1.1.3 This standard presents an open format that is intended to accommodate the widest probable range of variables that might be mandatory to document an ECDA survey and subsequent investigation. It is not necessary to enter data or comments in all of the data fields—only those applicable to the current study or those necessary to meet operator requirements. This format also acts as a checklist to remind the surveyor(s) of information to be gathered.

1.2 Scope

- 1.2.1 This standard addresses ECDA indirect inspection data, including close-interval surveys (CIS), aboveground coating evaluation surveys (e.g., direct-current voltage gradient [DCVG] and Pearson survey), and corrosiveness of environment surveys (e.g., linear polarization resistance [LPR] probe surveys and pH/soil resistivity surveys).
- 1.2.2 This standard does not address specific procedures for performing surveys, validating, or interpreting indirect inspection data.
- 1.2.3 Sound engineering practice and common sense should be used to assure that survey data are valid. Error checks should be made at regular intervals to ensure the quality of data recorded and stored.
- 1.2.4 Some users may not find it applicable to their use.

1.3 Benefits

- 1.3.1 The use of common field names allows users (vendors and operators) to exchange data in a predictable and reliable manner without the need for custom data conversion. This minimizes the risk of data translation errors.
- 1.3.2 The use of a common exchange format allows operators to use various vendors without the need for multiple data transformation concerns.
- 1.3.3 A common data exchange format should enable more industry ECDA-related applications to be developed.
- 1.3.4 These benefits may be realized in a similar fashion as has the in-line inspection (ILI) data exchange standard.⁴ An operator may validate ILI survey data prior to formally accepting the survey from the vendor, and load it to an enterprise database for electronic integration and alignment with the operator's common linear reference. Realignment may take place nightly or at another desired frequency, keeping the survey synchronized with pipeline reroutes and other changes to pipe length. This in turn enables reclassification of anomalies as changes that require reclassification are detected. Costs of manual integration for an annual risk ranking are eliminated.