

IN-LB

Inch-Pound Units

SI

International System of Units

Mass Concrete—Guide

Reported by ACI Committee 207

ACI PRC-207.1-21



American Concrete Institute
Always advancing



Mass Concrete—Guide

Copyright by the American Concrete Institute, Farmington Hills, MI. All rights reserved. This material may not be reproduced or copied, in whole or part, in any printed, mechanical, electronic, film, or other distribution and storage media, without the written consent of ACI.

The technical committees responsible for ACI committee reports and standards strive to avoid ambiguities, omissions, and errors in these documents. In spite of these efforts, the users of ACI documents occasionally find information or requirements that may be subject to more than one interpretation or may be incomplete or incorrect. Users who have suggestions for the improvement of ACI documents are requested to contact ACI via the errata website at <http://concrete.org/Publications/DocumentErrata.aspx>. Proper use of this document includes periodically checking for errata for the most up-to-date revisions.

ACI committee documents are intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. Individuals who use this publication in any way assume all risk and accept total responsibility for the application and use of this information.

All information in this publication is provided “as is” without warranty of any kind, either express or implied, including but not limited to, the implied warranties of merchantability, fitness for a particular purpose or non-infringement.

ACI and its members disclaim liability for damages of any kind, including any special, indirect, incidental, or consequential damages, including without limitation, lost revenues or lost profits, which may result from the use of this publication.

It is the responsibility of the user of this document to establish health and safety practices appropriate to the specific circumstances involved with its use. ACI does not make any representations with regard to health and safety issues and the use of this document. The user must determine the applicability of all regulatory limitations before applying the document and must comply with all applicable laws and regulations, including but not limited to, United States Occupational Safety and Health Administration (OSHA) health and safety standards.

Participation by governmental representatives in the work of the American Concrete Institute and in the development of Institute standards does not constitute governmental endorsement of ACI or the standards that it develops.

Order information: ACI documents are available in print, by download, through electronic subscription, or reprint and may be obtained by contacting ACI.

Most ACI standards and committee reports are gathered together in the annually revised the ACI Collection of Concrete Codes, Specifications, and Practices.

American Concrete Institute
38800 Country Club Drive
Farmington Hills, MI 48331
Phone: +1.248.848.3700
Fax: +1.248.848.3701

www.concrete.org

Mass Concrete—Guide

Reported by ACI Committee 207

Christopher C. Ferraro, Chair

Katie J. Bartojay, Secretary

Fares Y. Abdo
Oscar R. Antommattei
Terrence E. Arnold
Teck L. Chua
Timothy P. Dolen
Barry D. Fehl

John W. Gajda
Mario Garza
Melissa O. Harrison
Michael G. Hernandez
James K. Hicks
Ronald L. Kozikowski Jr.

Tibor J. Pataky
Jonathan L. Poole
Henry B. Prenger
Kyle Austin Riding
Ernest A. Rogalla
Ernest K. Schrader

Kuntay K. Talay
Nathaniel F. Tarbox
Michael A. Whisonant
James Steve Williamson II
Fouad H. Yazbeck

Consulting Members

Jeffrey C. Allen
Randall P. Bass
Anthony A. Bombich

Robert W. Cannon
Eric J. Ditchey
Brian A. Forbes

Rodney E. Holderbaum
Allen J. Hulshizer
Richard A. Kaden

William F. Kepler
David E. Kiefer
Stephen B. Tatro

This guide contains a history of the development of mass concrete practice and discussion of materials and concrete mixture proportioning, properties, construction methods, and equipment. It covers traditionally placed and consolidated mass concrete for massive structures such as dams and provides information applicable to mass structural heavily reinforced concrete and for thermally controlled concrete such as bridge elements and building foundations. This guide does not cover roller-compacted concrete.

Keywords: cement; cracking; fly ash; heat of hydration; mass concrete; mixture proportioning; supplementary cementitious materials; temperature rise; thermal control plan; thermal expansion; volume change.

ACI Committee Reports and Guides are intended for guidance in planning, designing, executing, and inspecting construction. This document is intended for the use of individuals who are competent to evaluate the significance and limitations of its content and recommendations and who will accept responsibility for the application of the material it contains. The American Concrete Institute disclaims any and all responsibility for the stated principles. The Institute shall not be liable for any loss or damage arising therefrom.

Reference to this document shall not be made in contract documents. If items found in this document are desired by the Architect/Engineer to be a part of the contract documents, they shall be restated in mandatory language for incorporation by the Architect/Engineer.

CONTENTS

CHAPTER 1—INTRODUCTION AND HISTORICAL DEVELOPMENTS, p. 2

- 1.1—Scope, p. 2
- 1.2—History, p. 2

CHAPTER 2—DEFINITIONS, p. 6

CHAPTER 3—MATERIALS AND MIXTURE PROPORTIONING, p. 7

- 3.1—General, p. 7
- 3.2—Cements, p. 8
- 3.3—Supplementary cementitious materials, p. 8
- 3.4—Chemical admixtures, p. 9
- 3.5—Aggregates, p. 10
- 3.6—Water, p. 11
- 3.7—Selection of proportions, p. 11

CHAPTER 4—PROPERTIES, p. 15

- 4.1—General, p. 15

ACI PRC-207.1-21 supersedes ACI 207.1R-05(12), was adopted November 3, 2021, and was published February 2022.

Copyright © 2022, American Concrete Institute.

All rights reserved including rights of reproduction and use in any form or by any means, including the making of copies by any photo process, or by electronic or mechanical device, printed, written, or oral, or recording for sound or visual reproduction or for use in any knowledge or retrieval system or device, unless permission in writing is obtained from the copyright proprietors.

- 4.2—Strength, p. 18
- 4.3—Temperature, p. 19
- 4.4—Elastic properties, p. 21
- 4.5—Creep, p. 21
- 4.6—Volume change, p. 22
- 4.7—Permeability, p. 22
- 4.8—Thermal properties, p. 23
- 4.9—Shear properties, p. 23
- 4.10—Durability, p. 23

CHAPTER 5—CONSTRUCTION, p. 24

- 5.1—Batching, p. 24
- 5.2—Mixing, p. 25
- 5.3—Placing, p. 25
- 5.4—Curing, p. 27
- 5.5—Forms, p. 28
- 5.6—Placement height and time between adjoining placements, p. 29
- 5.7—Cooling and temperature control, p. 29
- 5.8—Instrumentation, p. 30
- 5.9—Grouting contraction joints in dams, p. 31

CHAPTER 6—REFERENCES, p. 31

Authored documents, p. 32

CHAPTER 1—INTRODUCTION AND HISTORICAL DEVELOPMENTS

1.1—Scope

Mass concrete covered by this guide generally falls into two classifications, or types. The first type is the traditional mass concrete of structures such as dams, where most of the structure is mass concrete and is constructed of intertwined placements. The second type consists of individual or distinct placements such as high-rise building foundations or bridges, and is increasingly referred to as thermally controlled concrete. Both types of mass concrete have similar principles and basic considerations; however, thermally controlled concrete is often constructed with commercial ready mixed concrete. Thus, it may be designed to be pumpable and can consist of self-consolidating, high-strength, or high-performance concrete, which typically results in concrete containing much higher cementitious materials content than traditional mass concrete. Although this guide mainly focuses on guidance for traditional mass concrete, much of the information can also be applicable to thermally controlled concrete.

The design of traditional mass concrete structures, such as dams, is generally based on durability, economy, and thermal requirements. Strength performance is often a secondary requirement, rather than a primary concern, and is sometimes specified to be achieved at an age of 56 or 90 days instead of 28 days.

The one characteristic that distinguishes mass concrete from other concrete work is thermal behavior. Because the reaction between water and cement is exothermic by nature, the temperature rise within a large concrete mass, where the heat is not quickly dissipated, can be quite high.

Significant tensile stresses and strains may result from a decline in temperature as heat from hydration is dissipated at the volume extremities but not at the mass core. Measures should be taken where cracking due to thermal behavior may adversely affect structural integrity, durability, or aesthetics.

This guide contains a history of the development of mass concrete practice and a discussion of materials and concrete mixture proportioning, properties, construction methods, and equipment.

Mass concreting practices were developed largely from concrete dam construction, where temperature-related cracking was first identified. Temperature-related cracking has also been experienced in other concrete structures, including mat foundations, pile caps, bridge piers, superstructure elements, roadway patches, and tunnel linings.

High compressive strengths are not typically required in traditional mass concrete structures; however, there are some cases, such as thin arch dams, where high-strength concrete may be specified. Massive structures, such as gravity dams, resist loads primarily by their shape and mass; strength is of secondary importance. Of more importance are durability and properties connected with temperature behavior and the tendency for cracking.

The effects of heat generation, restraint, and volume changes on the design and behavior of massive reinforced elements and structures are discussed in [ACI 207.2R](#). Cooling and insulating systems for mass concrete are addressed in [ACI 207.4R](#).

1.2—History

Historically, mass concrete considerations evolved out of the use of concrete in dams. The first concrete dams were relatively small, and the concrete was mixed by hand. The portland cement usually had to be aged to comply with a boiling soundness test, the aggregate was bank-run sand and gravel, and proportioning was by the shovelful ([Davis 1963](#)). Tremendous progress has been made since the early 1900s, and the art and science of dam building practiced today has reached a highly advanced state. Presently, the selection and proportioning of concrete materials to produce suitable strength, durability, and impermeability of the finished product can now be predicted and controlled with accuracy.

Covered herein are the principal steps from those very small beginnings to the present. In large dam construction, there is now exact and automatic proportioning and mixing of materials. Concrete in 12 yd³ (9 m³) buckets can be placed by conventional methods at the rate of 10,000 yd³/day (7650 m³/day) at a temperature of less than 50°F (10°C) as placed, even during extremely hot weather. Grand Coulee Dam still holds the record monthly placing rate of 536,250 yd³ (410,020 m³), followed by the Itaipu Dam on the Brazil-Paraguay border with 440,550 yd³ (336,840 m³) ([Itaipu Binacional 1981](#)).

1.2.1 Before 1900—Before the beginning of the twentieth century, much of the portland cement used in the United States was imported from Europe. All cements were very coarse by present standards, and quite commonly they were underburned and had a high free lime content. For dams of