

# Recovery and Repassivation after Low pH Excursions in Open Recirculating Cooling Water Systems

# Recovery and Repassivation after Low pH Excursions in Open Recirculating Cooling Water Systems

This AMPP standard represents a consensus of those individual members who have reviewed this document, its scope, and provisions. Its acceptance does not in any respect preclude anyone, whether he or she has adopted the standard or not, from manufacturing, marketing, purchasing, or using products, processes, or procedures not in conformance with this standard. Nothing contained in this AMPP standard is to be construed as granting any right, by implication or otherwise, to manufacture, sell, or use in connection with any method, apparatus, or product covered by Letters Patent, or as indemnifying or protecting anyone against liability for infringement of Letters Patent. This standard represents minimum requirements and should in no way be interpreted as a restriction on the use of better procedures or materials. Neither is this standard intended to apply in all cases relating to the subject. Unpredictable circumstances may negate the usefulness of this standard in specific instances. AMPP assumes no responsibility for the interpretation or use of this standard by other parties and accepts responsibility for only those official AMPP interpretations issued by AMPP in accordance with its governing procedures and policies which preclude the issuance of interpretations by individual volunteers.

Users of this AMPP standard are responsible for reviewing appropriate health, safety, environmental, and regulatory documents and for determining their applicability in relation to this standard prior to its use. This AMPP standard may not necessarily address all potential health and safety problems or environmental hazards associated with the use of materials, equipment, and/or operations detailed or referred to within this standard. Users of this AMPP standard are also responsible for establishing appropriate health, safety, and environmental protection practices, in consultation with appropriate regulatory authorities, if necessary, to achieve compliance with any existing applicable regulatory requirements prior to the use of this standard.

CAUTIONARY NOTICE: AMPP standards are subject to periodic review and may be revised or withdrawn at any time in accordance with AMPP technical committee procedures. AMPP requires that action be taken to reaffirm, revise, or withdraw this standard no later than five years from the date of initial publication and subsequently from the date of each reaffirmation or revision. The user is cautioned to obtain the latest edition. Purchasers of AMPP standards may receive current information on all standards and other AMPP/NACE/SSPC publications by contacting AMPP Customer Support, 15835 Park Ten Place, Houston, Texas 77084-5145 (Tel: +1 281-228-6200, email: [customersupport@ampp.org](mailto:customersupport@ampp.org)).

## Document History

2022-01-18: Developed by AMPP Standards Committee (SC) 18, Water & Wastewater

AMPP values your input. To provide feedback on this standard, please contact: [standards@ampp.org](mailto:standards@ampp.org)

## AMPP SP21518-2022

©2022 Association for Materials Protection and Performance (AMPP). All rights reserved.

# Recovery and Repassivation after Low pH Excursions in Open Recirculating Cooling Water Systems

Document History .....	2
Foreword, Scope, and Rationale .....	5
Section 1    General .....	6
Section 2    Preplanning .....	7
Section 3    Recovery .....	8
3.1    General .....	8
3.2    Procedure I.....	9
3.3    Procedure II.....	9
3.4    Procedure III.....	10
3.5    Procedure IV .....	11
Section 4    Limited or Non-Discharge Recovery .....	12
4.1    General.....	12
4.2    Procedure I.....	12
4.3    Procedure II.....	13
4.4    Procedure III.....	14
4.5    Procedure IV .....	15
Section 5    Repassivation.....	17
References .....	18
Bibliography .....	19
Appendix A    Defining Terms and Associated Information and Calculations (Nonmandatory) .....	20
Appendix B    Indicative Comparison of Common Biofouling Ratings (Mandatory).....	27
Figures	
Figure 1    Decision Plan to Select Recovery Plan for Low pH Excursions in Open Recirculating Cooling Water Systems .....	8
Figure A1    Cooling System Hydraulic Balances .....	24
Figure A2    Back Flushing Heat Exchanger Layout.....	26
Figure A3    Air Bumping Heat Exchanger Layout.....	27
Tables	
Table 1    Passivation Time in Days .....	17
Table 2    Typical Corrosion Control Agents Used .....	18

Table A1	Dispersant to Contaminant Ratio .....	20
Table A2	On-Line Sensors Available and Applicable Detection Use.....	21
Table A3	Volume Calculations and Estimations .....	22
Table A4	Terms and Calculations Defined .....	23
Table A5	Cooling System Time Constraints .....	25
Table A6	Back Flushing/Air Bumping Heat Exchangers .....	25
Table B1	Checklist to Prepare for a pH Excursion .....	28
Table B2	Minimum Inventory and Maximum Feed Rate for Maximum Excursion below pH 2.5.....	29
Table B3	Estimated Alkaline Chemical Requirements to Raise pH from 4.5 to 7.0 .....	29
Table B4	Estimated Alkaline Chemical Requirements to Raise pH from 1.0 and Above to 4.5 .....	30
Table B5	Estimated Fresh Caustic Soda Requirements to Raise pH from 1.0 and Above to 2.5 .....	30

## Foreword

This standard practice presents guidelines for preplanning for, recovering from, and repassivation after a low pH excursion in open recirculating water systems, no matter what the cause. The procedures presented in this standard in no way preclude the use of other procedures but are presented as best practices developed over years of experience in a variety of plants. The provisions of this standard should be applied under the direction of qualified water-treatment personnel from water-treatment suppliers and/or consultants and plant personnel.

Low pH excursions in open recirculatory cooling water systems will result in stripping of scales and protective metal oxide films and elevated corrosion rates of 25 to 100 times higher than normal. The accelerated corrosion leads to greater equipment depreciation rates, reduced life expectancy and premature heat exchanger failures. Stripped scales, oxides and subsequent generation of suspended solids lead to fouling of heat exchangers and cooling tower fill, thus reducing water flow, heat extraction and heat rejection rates. If low pH excursion corrective action is not taken quickly, cooling capacity decreases and derating of process side throughput may be expected, with the potential of a forced shutdown outage. This standard provides the sequential corrective actions, chemical alkali selection and applied concentrations that must be adhered to in order to reduce the degree of corrosion and fouling while also avoiding a forced shutdown and minimizing the duration of the derated process side throughput. Secondary benefits of these processes are those associated with reduced prepared water consumption and reduced cost of post-treatment of discharge waters and of achieving environmental compliance.

This standard will assist the following personnel associated with the process;

- Water treatment suppliers and / or consultants to develop the site-specific contingency plan, complete with water and chemical inventory requirements to allow for corrective actions that successfully remediate the upset.
- Managers are ensured success of the application.
- Plant operating personnel are provided with the tools to counteract the upset successfully in a timely manner (hours as opposed to weeks).
- Owners can now reasonably manage the total cost of ownership (TCO) of the excursion.

## Scope

The scope of this standard practice is that of pH depression detection, correction, and restoration to safe operating conditions that ensure future avoidance of excessive corrosion and fouling rates as well as process throughput capacity derating. A discussion of the importance of preplanning, the elements that comprise it, in the form of a check list and populated tables containing the types of chemicals, their federate and inventory required that are site specific for the cooling system volume and maximum blowdown rates are provided. Auditing and identifying high-risk unit processes that could be a source of low pH ingressors to be completed. Sampling and monitoring the outlets of the high-risk areas with the appropriate on-line sensors or grab sample test apparatus with sufficient reagent inventories are also noted. Knowledge of the site environmental discharge limits and the management of the cooling system discharge during the recovery are addressed. The contingency processes to restore the pH, recover from excursion and completion of repassivation are based upon four degrees of severity associated with excursions. The individual contingencies are defined in the text and illustrated in Figure 1.

## Rationale

This standard replaces NACE standard RP0392-2001, which was withdrawn in 2011. This standard includes more information on repassivation, approximation of contingency dispersant requirements and demands, heat exchanger clean-up methods and improved directions on how to convert the general concepts and procedures to the site-specific operational hydraulic balances experienced than did RP0392. Appendix A (Nonmandatory) provides such direction which would also provide contingency chemical additives and inventories required, determination when the test result values were representative and to allow for predicting the time to achieve the maximum resultant outcome.

In AMPP standards, the terms *shall* and *must* are used to state requirements and are considered mandatory. The term *should* is used to state something that is recommended, but is not considered mandatory. The term *may* is used to state something considered optional.