



BSI Standards Publication

Disinfection using ultraviolet radiation — Methods for quantitative testing of automated ultraviolet disinfection activities by direct illumination — Determination of bactericidal, mycobactericidal, sporicidal, yeasticidal, fungicidal, virucidal and phagocidal activities

Publishing and copyright information

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2022

Published by BSI Standards Limited 2022

ISBN 978 0 539 04029 6

ICS 11.080.20; 71.100.35

The following BSI references relate to the work on this document:

Committee reference CH/216

Draft for comment 21/30390982 DC

Amendments/corrigenda issued since publication

Date	Text affected
------	---------------

Contents

	Page
Foreword	ii
Introduction	1
1 Scope	1
2 Normative references	2
3 Terms and definitions	2
4 Requirements – Efficacy tests	3
5 Test procedure	3
5.1 General	3
5.2 Materials and reagents	4
5.3 Apparatus and glassware	5
5.4 Preparation and counting of test suspensions	5
5.5 Procedure for evaluating the process activity	7
5.6 Experimental data and calculations (bacteria, yeasts, moulds, bacterial spores and bacteriophages and mycobacteria)	11
5.7 Interpretation of results	11
5.8 Test report	11
Annex A (normative) Summary of tests objectives and conditions	13
<i>Table A.1 — Efficacy tests: Control that minimal efficacy requirements are obtained for each type of activity claimed and for the targeted application(s)</i>	13
Annex B (informative) Experimental setup – small enclosure	15
<i>Figure B.1 — Carrier positioning for small enclosure testing with positionable UV emitter</i>	15
<i>Figure B.2 — Carrier positioning where the small enclosure is designed to disinfect a specific, well-defined object or target area</i>	16
Annex C (informative) Experimental setup – large enclosure	17
<i>Figure C.1 — Example layout of large enclosure test setup, showing side and plan views</i>	17
Annex D (normative) Measurement of ultraviolet radiation	18

Summary of pages

This document comprises a front cover, an inside front cover, pages I to II, pages 1 to 18, an inside back cover and a back cover.

Foreword

Publishing information

This British Standard is published by BSI Standards Limited, under licence from The British Standards Institution, and came into effect on 31 March 2022. It was prepared by Technical Committee CH/216, *Chemical disinfectants and antiseptics*. A list of organizations represented on this committee can be obtained on request to the committee manager.

Information about this document

This publication can be withdrawn, revised, partially superseded or superseded. Information regarding the status of this publication can be found in the Standards Catalogue on the BSI website at bsigroup.com/standards, or by contacting the Customer Services team.

Where websites and webpages have been cited, they are provided for ease of reference and are correct at the time of publication. The location of a webpage or website, or its contents, cannot be guaranteed.

Presentational conventions

The provisions of this standard are presented in roman (i.e. upright) type. Its methods are expressed as a set of instructions, a description, or in sentences in which the principal auxiliary verb is “shall”.

Commentary, explanation and general informative material is presented in smaller italic type, and does not constitute a normative element.

Where words have alternative spellings, the preferred spelling of the Shorter Oxford English Dictionary is used (e.g. “organization” rather than “organisation”).

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient’s own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

Compliance with a British Standard cannot confer immunity from legal obligations.

Introduction

This British Standard specifies a standard method for confirming under controlled laboratory conditions that automated ultraviolet (UV) radiation systems meet the efficacy objectives for which they are intended and to allow cross-comparison of different systems based on a defined surface-to-emitter distance and direct line-of-sight application. The standard defines the log reductions required to support microbicidal activity claims.

It applies to surface disinfection within a space, where the UV travels to the surface through the air, via an automated process.

Efficacy against each type of microorganism can be claimed independently; however, to claim compliance with the standard a pass needs to be achieved against vegetative bacteria and yeasts as the minimum requirement.

A claim for activity against a type of microorganism can only be made if a pass is achieved against all the test microorganisms in that group relevant to the use claim (see [Annex A](#)).

UV radiation travels in straight lines and objects within the path of travel prevent passage of the UV and create a shadow. It is not possible to standardize the microbicidal effects of UV in shadow areas; however, the efficacy of UV radiation within a shadowed area is lower than the efficacy achieved in direct illumination. This British Standard evaluates the efficacy of UV systems based on direct line-of-sight application of UV to a surface. The use of carriers located horizontally replicates the challenge of many important surfaces and represents a reasonable worst case. There are implications for users of UV systems of shadowed areas when applying UV disinfection technologies.

The UV systems are tested at a defined distance from the microorganism challenge. The intensity of UV radiation decreases with increasing distance from the emitting source, so users should be aware of the impact of distance on microbicidal efficacy when positioning UV systems.

Every automated UV disinfection cycle/application is unique and enclosure treatment can be influenced by the design and geometry of the treated area(s). This British Standard provides a defined challenge to be met for an automated UV disinfection system to be considered efficacious. This standard test method should therefore be regarded as a useful starting point and not as a validation for all intended treatments in all areas with a particular automated UV disinfection system.

The standard draws on the microorganism preparation, carrier inoculation and microorganism recovery methodology specified in BS EN 17272:2020.

1 Scope

This British Standard specifies a method of determining the disinfection capability of processes for enclosures in the human health, veterinary, food, industrial and institutional sectors using ultraviolet (UV) radiation.

The objective of the processes concerned is to disinfect the surfaces of the overall area, including the external surfaces, of the equipment contained in such enclosures.

This British Standard is applicable to UV disinfection systems for which microbicidal activity is claimed against the following types of microorganism:

- vegetative bacteria, including mycobacteria;
- bacterial spores;
- yeasts;
- fungal spores;