

AS 3778.3.3:2022
ISO 1070:2018



STANDARDS
Australia



Measurement of water flow in open channels

**Part 3.3: Velocity-area methods — Measurement by slope-area method
(ISO 1070:2018, IDT)**



AS 3778.3.3:2022

This Australian Standard ® was prepared by CE-024, Measurement Of Water Flow In Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 30 May 2022.

This Standard was published on 10 June 2022.

The following are represented on Committee CE-024:

- Australian Bureau of Meteorology
- Australian Hydrographers Association
- Australian Industry Group
- Department of Planning, Industry and Environment, NSW
- Engineers Australia
- Institute of Instrumentation, Control & Automation Australia
- Irrigation Australia
- Joint Accreditation System of Australia & New Zealand
- National Measurement Institute
- Water NSW

This Standard was issued in draft form for comment as DR AS 3778.3.3:2022.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76113 815 7

Measurement of water flow in open channels

Part 3.3: Velocity-area methods — Measurement by slope-area method (ISO 1070:2018, IDT)

Originated as AS 3778.3.3—1990.
Previous edition 2001.
Third edition 2022.

COPYRIGHT

© ISO 2022 — All rights reserved
© Standards Australia Limited 2022

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Standards Australia Committee CE-024, Measurement of water flow in open channels and closed conduits, to supersede AS 3778.3.3:2001.

The objective of this document is to specify a method of determining discharge in open channels from observations of the surface slope and cross-sectional area of the channel.

It is applicable to use under special conditions when direct measurement of discharge by typically more accurate methods, such as the velocity-area method, is not possible. Generally, the method can be used to determine discharge —

- (a) for a peak flow that left high-water marks along the stream banks;
- (b) for a peak flow that left marks on a series of water-level gauges or where peak stages were recorded by that series of gauges; and
- (c) for flow observed at the time of determining gauge heights from a series of gauges.

The method is commonly used to undertake the extension of stage discharge relationships above the highest gauged flows.

It does not apply to determining discharges in tidal reaches.

This document is identical with, and has been reproduced from, ISO 1070:2018, *Hydrometry — Slope-area method*.

As this document has been reproduced from an International document, a full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

Contents

Preface	ii
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle of the method of measurement	1
5 Selection and demarcation of site	3
5.1 Initial survey of site	3
5.2 Selection of site	3
5.3 Demarcation of site	4
6 Measurement of slope	4
6.1 High-water marks	4
6.2 Crest-stage gauges	4
6.3 Pressure transmitters	4
6.4 Reference gauge	4
7 Determination of slope	5
8 Cross sections of a stream	5
8.1 Number and location of cross sections	5
8.2 Measurement of cross-sectional profiles	5
9 Computation of discharge	5
9.1 General	5
9.2 Uniform cross sections	6
9.2.1 General	6
9.2.2 Determination of the mean cross-sectional area and mean wetted perimeter of the reach	6
9.2.3 Determination of hydraulic radius	6
9.2.4 Determination of the mean velocity in the reach	7
9.3 Non-uniform cross sections (2-cross-section formulation)	8
9.3.1 General	8
9.3.2 Computation of conveyance	8
9.3.3 Evaluation of the friction slope	9
9.4 Composite cross sections	11
9.5 Computation of discharge using three or more cross sections	12
9.6 State of flow	13
10 Alternative methods to estimate conveyance	14
10.1 General	14
10.2 Divided channel method	14
10.3 Conveyance estimation system	14
11 Uncertainty in flow measurement	14
11.1 Definition of uncertainty	14
11.2 Sources of uncertainty for a uniform reach	15
11.2.1 General considerations	15
11.2.2 Uncertainty of the mean cross-sectional area	15
11.2.3 Uncertainty in the calculation of the mean wetted perimeter	15
11.2.4 Uncertainties in determination of the friction slope	16
11.2.5 Uncertainty due to the choice of the rugosity coefficient	16
11.2.6 Overall uncertainty in the measurement of discharge	16
Annex A (informative) Approximate value of coefficients n and C for open channels	17

Annex B	(informative) Approximate value of Strickler-coefficients k_{St} for natural streams	20
Annex C	(informative) US Soil Conservation Service method of estimating Manning's n	22
Annex D	(informative) Conveyance estimation system	24
Bibliography	26

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 113, *Hydrometry*.

This third edition cancels and replaces the second edition (ISO 1070:1992), which has been technically revised. It also incorporates the amendment ISO 1070:1992/Amd.1:1997. The main changes compared to the previous edition are as follows:

- the document has been reorganized to first present two-section computations followed by multiple reach computations;
- a third governing formula has been added;
- three annexes have been added.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

The slope–area method is an indirect method of determining discharge in open channels when direct measurement of the flow is not possible because of the timing of the flow or because the site is too hazardous for direct measurement techniques. The method is usually used to document the discharge of a flood and to extend the stage–discharge rating of a stream flow gauging station above direct measurements of discharge. The method can also be used at locations where bridge, cableway or boat measurements are not possible. Water discharge is computed using flow resistance formulae based on channel characteristics, water-surface profiles, and a roughness or friction coefficient.

Australian Standard®

Measurement of water flow in open channels

Part 3.3: Velocity-area methods — Measurement by slope-area method (ISO 1070:2018, IDT)

1 Scope

This document specifies a method of determining discharge in open channels from observations of the surface slope and cross-sectional area of the channel.

It is applicable to use under special conditions when direct measurement of discharge by typically more accurate methods, such as the velocity-area method, is not possible. Generally, the method can be used to determine discharge

- a) for a peak flow that left high-water marks along the stream banks,
- b) for a peak flow that left marks on a series of water-level gauges or where peak stages were recorded by that series of gauges, and
- c) for flow observed at the time of determining gauge heights from a series of gauges.

The method is commonly used to undertake the extension of stage–discharge relationships above the highest gauged flows.

It does not apply to determining discharges in tidal reaches.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 772, *Hydrometry — Vocabulary and symbols*

ISO 4373, *Hydrometry — Water level measuring devices*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 772 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Principle of the method of measurement

A measuring reach is chosen for which the mean area of the stream or river cross section is determined, and the surface slope of the flowing water in that reach is measured. The mean velocity is then established using known empirical formulae that relate the velocity to the hydraulic radius. The surface slope is corrected to account for the kinetic energy of the flowing water and the characteristics of the bed and bed material. The discharge is computed as the product of the mean velocity and the mean area of the stream cross section.