

AS 3778.6.4:2022
ISO 4366:2007



Measurement of water flow in open channels

Part 6.4: Measuring devices, instruments and equipment — Echo sounders for water depth measurements (ISO 4366:2007, IDT)



AS 3778.6.4:2022

This Australian Standard ® was prepared by CE-024, Measurement Of Water Flow In Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 16 May 2022.

This Standard was published on 10 June 2022.

The following are represented on Committee CE-024:

- Australian Bureau of Meteorology
- Australian Hydrographers Association
- Australian Industry Group
- Department of Planning, Industry and Environment, NSW
- Engineers Australia
- Institute of Instrumentation, Control & Automation Australia
- Irrigation Australia
- Joint Accreditation System of Australia & New Zealand
- National Measurement Institute
- Water NSW

This Standard was issued in draft form for comment as DR AS 3778.6.4:2022.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76113 806 5

Measurement of water flow in open channels

Part 6.4: Measuring devices, instruments and equipment — Echo sounders for water depth measurements (ISO 4366:2007, IDT)

Originated as AS 3778.6.4—1992.
Second edition 2022.

COPYRIGHT

© Standards Australia Limited 2022

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Standards Australia Committee CE-024, Measurement of water flow in open channels and closed conduits, to supersede AS 3778.6.4—1992, *Measurement of water flow in open channels, Part 6.4: Measuring devices, instruments and equipment — Echo sounders for water depth measurements*.

The objective of this document is to provide information concerning the principles of operation, selection and performance criteria for echo sounders used in depth measurements for open-channel flow (and related) measurements. The use of standard terminology is promoted.

This document is identical with, and has been reproduced from, ISO 4366:2007, *Hydrometry — Echo sounders for water depth measurements*.

As this document has been reproduced from an International document, the following apply:

- (a) In the source text “this International Standard” should read “this document”.
- (b) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

Contents

Preface	ii
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Units of measure	1
5 Principles of operation	1
5.1 General	1
5.2 Theory of operation	1
5.3 System components	2
5.4 Non-recording echo sounders	3
5.5 Analog recording echo sounders	3
5.6 Digital echo sounders	4
5.6.1 General	4
5.6.2 Digitization techniques	4
5.6.3 Multiple-transducer systems	5
5.6.4 Single-transducer swath systems	5
6 Selection of instrument	6
6.1 General	6
6.2 Effect of operating frequency	6
6.3 Effect of beamwidth	7
6.4 Type of data display	8
6.4.1 Non-recording echo sounders	8
6.4.2 Analog recording echo sounders	8
6.4.3 Digital echo sounders	8
6.5 Accuracy	9
6.6 Type of transducer system	9
7 Instruments performance criteria	9
7.1 General	9
7.2 Information to be specified by the user	9
7.3 Information to be specified by the manufacturer	10
7.4 Housing	10
7.5 Additional features	10
7.5.1 Non-recording instruments	10
7.5.2 Recording instruments	10
7.5.3 Digital instruments	11
8 Field use of echo sounders	11
8.1 Calibration	11
8.2 Interpretation of data	12
8.3 Precautions	12
9 Operations manual	12
Bibliography	13

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 4366 was prepared by Technical Committee ISO/TC 113, *Hydrometry*, Subcommittee SC 5, *Instruments, equipment and data management*.

This second edition cancels and replaces the first edition (ISO 4366:1979), which has been technically revised.

Australian Standard®

Measurement of water flow in open channels

Part 6.4: Measuring devices, instruments and equipment — Echo sounders for water depth measurements (ISO 4366:2007, IDT)

1 Scope

This International Standard provides information concerning the principles of operation, selection and performance criteria for echo sounders used in depth measurements for open-channel flow (and related) measurements. The use of standard terminology is promoted.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 772, *Hydrometric determinations — Vocabulary and symbols*

ISO 6420, *Liquid flow measurement in open channels — Position fixing equipment for hydrometric boats*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 772 and the following apply.

3.1

tracking window

vertical distance of limited size that follows and automatically centres itself on the depth indicated by the last received echo

Note 1 to entry: If the next echo falls within the window, the signal is accepted as correct; if it does not, the signal is rejected. The purpose of a tracking window is to screen out erroneous readings caused by reflecting materials in the water (fish, debris, etc.).

4 Units of measure

The units of measurement used in this International Standard are SI units and decibels.

5 Principles of operation

5.1 General

The state-of-the-art of echo sounders is well advanced, and sounders have been put into widespread use for many different applications. Consequently, a variety of specialized echo sounders have evolved to best meet the specific requirements of the application. A digital echo sounder with an integrated analog chart generated by a thermal or inkjet print head is the most common echo sounder used for open-channel applications. Multiple-transducer systems are in common use by many professional surveyors and the use of single-transducer, multibeam-swath systems is expanding rapidly.

5.2 Theory of operation

The echo sounder is an electroacoustic instrument that determines the depth of water by measuring the time required for a burst of acoustic energy to travel from a transducer to the streambed and reflect