

AS 3778.3.7:2022
ISO 6416:2017



Measurement of water flow in open channels

**Part 3.7: Velocity-area methods — Measurement by ultrasonic method
(ISO 6416:2017, IDT)**



AS 3778.3.7:2022

This Australian Standard ® was prepared by CE-024, Measurement of Water Flow in Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 30 May 2022.

This Standard was published on 10 June 2022.

The following are represented on Committee CE-024:

- Australian Bureau of Meteorology
- Australian Hydrographers Association
- Australian Industry Group
- Department of Planning, Industry and Environment, NSW
- Engineers Australia
- Institute of Instrumentation, Control & Automation Australia
- Irrigation Australia
- Joint Accreditation System of Australia & New Zealand
- National Measurement Institute
- Water NSW

This Standard was issued in draft form for comment as DR AS 3778.3.7:2022.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76113 818 8

Measurement of water flow in open channels

Part 3.7: Velocity-area methods — Measurement by ultrasonic method (ISO 6416:2017, IDT)

Originated as AS 3778.3.7—2007.
Second edition 2022.

COPYRIGHT

© ISO 2022 — All rights reserved
© Standards Australia Limited 2022

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Standards Australia Committee CE-024, Measurement of water flow in open channels and closed conduits, to supersede AS 3778.3.7 — 2007, *Measurement of water flow in open channels, Part 3.7: Velocity-area methods - Measurement by ultrasonic (acoustic) method*.

The objective of this document is to specify the requirements for the establishment and operation of an ultrasonic (transit-time) gauging station for the continuous measurement of discharge in a river, an open channel or a closed conduit. It also specifies the basic principles on which the method is based, the operation and performance of associated instrumentation and procedures for commissioning.

It is limited to the “transit time of ultrasonic pulses” technique, and is not applicable to systems that make use of the “Doppler shift” or “correlation” or “level-to-flow” techniques.

This document is not applicable to measurement in rivers with ice.

NOTE This document focuses on open channel flow measurement. IEC 60041 covers the use of the technique for full pipe flow measurement.

This document is identical with, and has been reproduced from, ISO 6416:2017, *Hydrometry — Measurement of discharge by the ultrasonic transit time (time of flight) method*.

As this document has been reproduced from an International document, a full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

Contents

Preface	ii
Foreword	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Applications	1
4.1 Types of applications	1
4.2 Attributes and limitations	2
5 Method of measurement	2
5.1 Discharge	2
5.2 Calculation of discharge from the transit-time measurement	3
6 Flow velocity determination by the ultrasonic (transit time) method	3
6.1 Principle	3
6.2 Sound propagation in water	5
6.2.1 General	5
6.2.2 Speed of sound in water	6
6.2.3 Propagation losses	6
6.2.4 Signal path bending	8
6.2.5 Reflection	9
7 Gauge configuration	10
7.1 General	10
7.2 Single-path systems	10
7.3 Multi-path systems	11
7.4 Crossed-path systems	11
7.5 Reflected-path systems	13
7.6 Systems using transponders	14
7.7 Wireless systems (if a cable crossing is not possible)	15
7.8 Systems using divided cross-sections	16
7.9 Sloping paths	16
8 Determination of discharge	17
8.1 Single-path systems	17
8.2 Multi-path systems	18
8.2.1 General	18
8.2.2 Mid-section method	19
8.2.3 Mean-section method	20
8.3 Systems with transducers in the channel	21
9 System verification and calibration	22
10 Site selection	23
11 Site survey — Before design and construction	23
11.1 General	23
11.2 Visual survey	23
11.3 Survey of the cross-section	24
11.4 Survey of velocity distribution	24
11.5 Survey of signal propagation	24
12 Operational measurement requirements	24
12.1 General	24
12.2 Basic components of flow determination	25
12.3 Water velocity determination	25
12.4 Determination of water stage or depth	25

12.5	Determination of mean bed level.....	26
12.6	Channel width.....	27
13	Gauging station equipment.....	27
13.1	General.....	27
13.2	Design and construction of equipment.....	28
13.2.1	Transducers.....	28
13.2.2	Transducer cables.....	29
13.3	Reflectors.....	29
13.4	Civil engineering works.....	32
13.5	Signal timing and processing.....	32
13.5.1	General.....	32
13.5.2	Signal-to-noise ratio.....	32
13.5.3	Signal maintenance (gain control).....	33
13.5.4	Signal detection.....	33
13.5.5	Post-detection filtering.....	34
13.6	System self-checking.....	34
13.7	Site-specific data (or site parameters).....	35
13.8	Clock and calendar.....	35
13.9	System performance criteria.....	35
13.9.1	General.....	35
13.9.2	Operating environment.....	36
13.9.3	Water environment.....	36
13.9.4	Mechanical environment.....	36
13.9.5	Extreme environmental conditions.....	36
13.9.6	Power source.....	36
13.9.7	Measurement uncertainty.....	36
13.10	System output.....	37
13.10.1	Local display.....	37
13.10.2	Local record.....	37
13.10.3	Remote record.....	37
13.10.4	Diagnostic information.....	37
13.11	Installation.....	37
13.12	Commissioning.....	38
13.13	Operating manual.....	38
13.14	Maintenance.....	38
14	Measurement uncertainties.....	40
14.1	General.....	40
14.2	Definition of uncertainty.....	40
14.3	Uncertainty in discharge.....	41
14.3.1	Uncertainty equation.....	41
14.3.2	Effective number of paths.....	42
14.3.3	Uncertainty in the line velocity, U_{lv}	42
14.3.4	Uncertainty in the channel width estimation, U_w	42
14.3.5	Examples of uncertainty estimation.....	42
14.3.6	Uncertainty estimate at low flow.....	44
14.3.7	Uncertainty estimate at high flow.....	45
Annex A	(informative) Principle of measurement uncertainty.....	47
Annex B	(informative) Performance guide for hydrometric equipment for use in technical standard examples.....	54
Bibliography	58

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 113, *Hydrometry*, Subcommittee SC 1, *Velocity area methods*.

This fourth edition cancels and replaces the third edition (ISO 6416:2004), which has been technically revised. The main changes from the previous edition are:

- the title has been changed;
- a new [subclause \(7.7\)](#) on wireless systems has been added;
- former subclauses 9.2 and 11.6 have been removed;
- [Clause 10](#) on site selection has been revised;
- [Annex A](#) (*Principle of measurement uncertainty*) and [Annex B](#) (*Performance guide for hydrometric equipment for use in technical standards*) have been added.

NOTES

Australian Standard®

Measurement of water flow in open channels

Part 3.7: Velocity-area methods — Measurement by ultrasonic method (ISO 6416:2017, IDT)

1 Scope

This document describes the establishment and operation of an ultrasonic (transit-time) gauging station for the continuous measurement of discharge in a river, an open channel or a closed conduit. It also describes the basic principles on which the method is based, the operation and performance of associated instrumentation and procedures for commissioning.

It is limited to the “transit time of ultrasonic pulses” technique, and is not applicable to systems that make use of the “Doppler shift” or “correlation” or “level-to-flow” techniques.

This document is not applicable to measurement in rivers with ice.

NOTE This document focuses on open channel flow measurement. IEC 60041 covers the use of the technique for full pipe flow measurement.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 772, *Hydrometry — Vocabulary and symbols*

ISO 4373, *Hydrometry — Water level measuring devices*

ISO/TS 25377, *Hydrometric uncertainty guidance (HUG)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 772 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <http://www.electropedia.org/>

4 Applications

4.1 Types of applications

- a) Open channels
- b) Multiple channels
- c) Closed conduits

This method does not need a man-made or natural control, as it does not rely upon the establishment of a unique relationship between water level and discharge.