



**CGA V-14—2022**  
**PERFORMANCE STANDARD**  
**FOR SEALING GASKETS USED**  
**ON CGA 870 CONNECTIONS**  
**FOR MEDICAL OXYGEN**  
**SERVICE AT A**  
**MAXIMUM SERVICE**  
**PRESSURE OF 3000 PSI**

**THIRD EDITION**

**PLEASE NOTE:**

The information contained in this document was obtained from sources believed to be reliable and is based on technical information and experience currently available from members of the Compressed Gas Association, Inc. and others. However, the Association or its members, jointly or severally, make no guarantee of the results and assume no liability or responsibility in connection with the information or suggestions herein contained. Moreover, it should not be assumed that every acceptable commodity grade, test or safety procedure or method, precaution, equipment or device is contained within, or that abnormal or unusual circumstances may not warrant or suggest further requirements or additional procedure.

This document is subject to periodic review, and users are cautioned to obtain the latest edition. The Association invites comments and suggestions for consideration. In connection with such review, any such comments or suggestions will be fully reviewed by the Association after giving the party, upon request, a reasonable opportunity to be heard. Proposed changes may be submitted via the Internet at our web site, [www.cganet.com](http://www.cganet.com).

This document should not be confused with federal, state, provincial, or municipal specifications or regulations; insurance requirements; or national safety codes. While the Association recommends reference to or use of this document by government agencies and others, this document is purely voluntary and not binding unless adopted by reference in regulations.

A listing of all publications, audiovisual programs, safety and technical bulletins, and safety posters is available via the Internet at our website at [www.cganet.com](http://www.cganet.com). For more information contact CGA at Phone: 703-788-2700, ext. 799. E-mail: [customerservice@cganet.com](mailto:customerservice@cganet.com).

Work Item 23-006  
Cylinder Valve Committee

---

NOTE—Technical changes from the previous edition are underlined.

NOTE—Appendix A (Normative) is a requirement.

THIRD EDITION: 2022  
SECOND EDITION 2018  
FIRST EDITION: 2011

© 2022 The Compressed Gas Association, Inc. All rights reserved.

All materials contained in this work are protected by United States and international copyright laws. No part of this work may be reproduced or transmitted in any form or by any means, electronic or mechanical including photocopying, recording, or any information storage and retrieval system without permission in writing from The Compressed Gas Association, Inc. All requests for permission to reproduce material from this work should be directed to The Compressed Gas Association, Inc., 8484 Westpark Drive, Suite 220, McLean, VA 22102. You may not alter or remove any trademark, copyright or other notice from this work.

<b>Contents</b>	<b>Page</b>
1 Scope .....	1
2 Definitions.....	1
3 Dimensions.....	2
4 Materials.....	2
5 Leak rate or leakage.....	2
6 Qualification testing procedures .....	2
6.1 Cycle test.....	2
6.2 Temperature test .....	4
7 Documentation .....	4
8 References .....	5
 <b>Figure</b>	
Figure 1—Example of a sealing gasket side load test fixture .....	3
 <b>Table</b>	
Table 1—Compressive force to torque conversion values (approximate) .....	4
 <b>Appendix</b>	
Appendix A—Leak rate testing flow chart (Normative) .....	6
 <b>Appendix figures</b>	
Figure A-1—Cycle test procedure (see 6.1).....	6
Figure A-2—Temperature test procedure (see 6.2) .....	7

## 1 Scope

This publication covers the performance standards required for crush-style and encircled elastomeric gaskets used in medical oxygen service up to 3000 psi at 70 °F (21.1 °C). Sealing gaskets designed to be used with a CGA connection no. 870 shall be qualified at the time of design by the manufacturer in accordance with this performance standard.

For additional information, see V-24, *Guideline for Use of Gaskets in High Pressure Medical Oxygen Cylinder Service* [1].<sup>1</sup>

It is acknowledged that previous editions of this standard used a lower test pressure for qualification of gaskets as the CGA connection no. 870 is currently rated at 3000 psi at 70 °F (20 680 kPa at 21.1 °C) as per CGA V-1, *Standard for Compressed Gas Cylinder Valve Outlet and Inlet Connections* [2].<sup>2</sup> The test pressures in this edition were increased to 3600 psi (24 800 kPa). Gaskets qualified at the lower test pressure as specified in previous editions of this publication (2400 psi) are acceptable for continued use in medical oxygen service up to 2216 psi.

The effective date of this standard is two years from the date of the publication of this edition, which was August 19, 2022. Gaskets manufactured on and after the effective date of this standard shall be in compliance with this standard.

## 2 Definitions

For the purpose of this publication, the following definitions apply.

### 2.1 Publication terminology

#### 2.1.1 Shall

Indicates that the procedure is mandatory. It is used wherever the criterion for conformance to specific recommendations allows no deviation.

#### 2.1.2 Should

Indicates that a procedure is recommended.

#### 2.1.3 May

Indicates that the procedure is optional.

#### 2.1.4 Will

Is used only to indicate the future, not a degree of requirement.

#### 2.1.5 Can

Indicates a possibility or ability.

### 2.2 Technical definitions

#### 2.2.1 Compressive force

Load expressed in pounds of force placed on the sealing gasket as a result of tightening the yoke or regulator T-screw handle.

#### 2.2.2 Gasket

O-shaped object made of an elastomer or other material placed between the valve face and the regulator inlet connection to provide a gas-tight seal.

NOTE—A gasket is sometimes also incorrectly referred to as a washer.

---

<sup>1</sup> References are shown by bracketed numbers and are listed in order of appearance in the reference section.

<sup>2</sup> psi, bar, and kPa shall indicate gauge pressure unless otherwise noted as (psia; bar, abs; and kPa, abs) for absolute pressure or (psid; bar, dif; and kPa, dif) for differential pressure. All kPa values are rounded off per CGA P-11, *Guideline for Metric Practice in the Compressed Gas Industry* [3].